NOT MEASUREMENT SENSITIVE

MIL-L-11484/186A
14 January 1994
SUPERSEDING
MIL-L-11484/186
10 February 1992

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, BUREAU OF INDIAN AFFAIRS, DEPARTMENT OF THE INTERIOR

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.090 inch ± 0.010 inch (0.229 cm ± 0.025 cm)

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:15Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

3. Each lapel button shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches (2.86 cm) square and 5/8 inch (1.59 cm) in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button when the lid is closed.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other - DOI

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:15Z
Check the source to verify that this is the current version before use.