NOT MEASUREMENT SENSITIVE

MIL-L-11484/191A
14 January 1994
SUPERSEDING
MIL-L-11484/191
21 December 1992

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, CAREER ACHIEVEMENT AWARD, DEFENSE INFORMATION SYSTEMS AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS: 0.075 inch ± 0.010 inch (0.190 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:17Z
Check the source to verify that this is the current version before use.

2. The attaching device shall be prong with pick and flat ball clutch type. The prong shall be centered on the reverse side and fused or soldered to the label button.

3. Each lapel button shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches (2.86 cm) square and 5/8 inch (1.59 cm) in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button when the lid is closed.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0745)

User activities:
Other - DISA

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:17Z
Check the source to verify that this is the current version before use.