INCH-POUND

MIL-B-70511B(AR)
AMENDMENT 2
21 December 1993
SUPERSEDING
AMENDMENT 1
31 July 1993

MILITARY SPECIFICATION

BOLT, AUTOMATIC WEAPON: (PRACTICE) M2

This Amendment forms a part of MIL-B-70511B(AR), dated 4 January 1993, and is approved for use by U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* 3.4.3: Delete in its entirety and substitute the following:

"3.4.3 Cyclic rate of fire. The cyclic rate of fire for 3 rounds of burst firing using a 30 round magazine shall be within 600 to 950 rounds per minute. The cyclic rate of fire measurement shall be taken on a three round burst, occurring on the 6th or 7th trigger pull. Testing shall be as specified in 4.5.3."

* 3.4.4: Delete in its entirety and substitute the following:

"3.4.4 Endurance. The M2 bolt shall be capable of withstanding the firing of 10,000 rounds of M862 ammunition with not more than 127 malfunctions attributable to the M2 bolt."

PAGE 6

* TABLE I, under Performance Tests:

Delete	"Function	10	3.4.2	4.3.3.1/4.5.2.1
and substitute	"Function	6	3.4.2	4.3.3.3.1/4.5.2

PAGE 8

4.3.1.1, second line: Delete "shall be 800" and substitute "shall be 1000".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

PAGE 12

* 4.3.3.2, under Performance Tests:

Delete	"Function	90	3.4.2	4.5.2"
and substitute	"Function	60	3.4.2	4.3.3.3.2/4.5.2"

PAGE 13

* 4.3.3.3.1, line 2: Delete "If 4 or more" and substitute "If 3 or more".

* 4.3.3.3.2, line 4: Delete "A total of 21 or more" and substitute "A total of 14 or more".

* 4.5.2, line 2: Delete "Government approved M16, M16A1 and M16A2 Rifles" and substitute "Government approved M16A1 and M16A2 Rifle".

* 4.5.2.1: Delete in its entirety and substitute the following:

"4.5.2.1 Function (first article). Six M2 bolts shall be function tested during first article by firing 30 rounds with each bolt. Six magazines, fully loaded with 5.56mm, M862 Short Range Training ammunition shall be used for this test. Three M2 Bolts shall be tested in the M16A1 Rifle and three in the M16A2 Rifle. For the M16A1 each thirty round firing shall consist of two bursts of approximately three rounds with the remaining rounds fired in one burst. With the M16A2, all firings shall be in three round bursts."

PAGE 14

* 4.5.2.2, under Function (Lot Acceptance): Delete:

"15	M16	Semi	30
15	Ml 6	Auto	30"

* 4.5.3: Delete in its entirety and substitute the following:

"4.5.3 Cyclic rate. Thirty (30) rounds shall be fired in 3 round burst firing from a 30 round magazine with the M16A2 rifle. The cyclic rate of fire measurement shall be taken on a three round burst, occurring on the 6th or 7th trigger pull. All malfunctions shall be recorded."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

* 4.5.4: Delete in its entirety and substitute the following:

"4.5.4 Endurance. A minimum of two rifles shall be used for this test. At least one half of the test rifles shall be M16A2 rifles and the remainder of the rifles shall be M16A1 rifles. Testing shall be performed from a Government approved test fixture. A total of 10,000 rounds shall be fired on each M2 Bolt. Testing shall be conducted in cycles consisting of firing four 30-round magazines for a total of 120 rounds. Start the endurance test with a M2 bolt in a M16A2 rifle. After each firing cycle, the M2 bolt shall be sequentially rotated through the total number of test rifles, alternating between M16A2 and M16A1 rifles. Firing sequence for both the M16A1 and M16A2 rifles for a test cycle is as follows:

Rifle	1st Magazine	2nd Magazine	3rd Magazine	4th Magazine
M16A1	Semi	Auto	Semi	Auto
M16A2	Semi	Burst	Semi	Burst

After each cycle, the barrel shall be cooled to the point that it is capable of being held by the bare hand. Supplemental cooling is permissible. Lubricant conforming to MIl-L-63460 shall be used. After every five cycles, the M2 Bolt shall be lubricated, and cleaned and lubricated after every 10 cycles. At the completion of 4,800 rounds fired and again at the end of the 10,000 round endurance test, each bolt carrier (P/N 11833494) and each bolt (P/N 11833495) shall be inspected using magnetic particle inspection. Any cracked or broken bolt carrier or bolt shall result in failure of the endurance test. If there are any other broken, cracked or unserviceable parts, they shall be replaced. Both the M16A1 and M16A2 rifles shall be cleaned and lubricated as stated in paragraph 4.5.4.1. Cyclic rate of fire measurements shall be performed during the first testing cycle, and during the first testing cycle using an M16A2 rifle after the M2 bolt has been lubricated, as stated above. Cyclic rate of fire measurements shall be performed on the second magazine of a cycle using a M16A2 rifle. The cyclic rate of fire shall be measured in accordance with 4.5.3. All malfunctions shall be recorded. If more than the number of malfunctions specified in 3.4.4 occur, that are attributable to an individual M2 bolt, the sample shall have failed the endurance test.

* 4.5.4.1: Delete "Rifles shall be lubricated as specified below at the beginning of the test and after the third cycle in every 5 cycle increment. Rifles shall be cleaned and lubricated at the end of every 5 cycles." and substitute "Each rifle shall be lubricated as specified below at the beginning of the test and at the end of each 5 cycle increment fired on that rifle. Each

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

rifle shall be cleaned and lubricated at the end of every 10 cycle increment fired on that rifle."

PAGE 16

* 4.5.4.2, line 1: Delete "Twenty-one 30 round magazines shall be numbered and used in rotation with each M16A2 rifle" and substitute "Forty 30 round magazines shall be numbered and used in rotation with each rifle".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005-A818)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.