MILITARY SPECIFICATION

CHARGES, EXPELLING, FOR
PROJECTILE, 155MM, ILLUMINATING, M485A2
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-48254A (AR), dated 30 July 1984, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.4.2.1 Delete Major Defects 101, 102, 103 and substitute the following:

"Major				
101	Total length	.40%	3.1	Gage
102	Shell wall thickness	.40%	3.1	Gage
103	Presence of 4 slots at inner bottom of cup	.40%	3.1	Visual
104	Presence of protrusion at bottom of cup	.40%	3.1	Visual
105	Inside diameter	.40%	3.1	Gage
106	Inverted weight test (Note 1)	.40%	3.1	4.4.3.3/4.5.3"

Delete Minor Defects 201 through 211, and substitute the following:

"Minor				
201	Evidence of poor Workmanship	.65%	3.5	Visual"

Add note to bottom of page:

"1. Test to be performed after expelling charge cover is snap fitted onto expelling charge cup."

DISTIRBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:19Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.2 Delete Major Defect 101 and substitute the following:

"Major			
101	Thickness of inside rim	.40%	Gage
102	Thickness at center	.40%	Gage
103	Inverted weight test (Note 1)	.40%	4.4.3.3/4.5.3"

Delete Minor Defects 201 through 205 and substitute the following:

"Minor				
201	Radii or chamfer missing or incorrect	0.65%	3.1	Visual
202	Evidence of poor workmanship	0.65%	3.5	Visual"

Add note to bottom of page:

"1. Test to be performed after expelling charge cover is snap fitted onto expelling charge cup."

PAGE 11

4.4.2.4 Delete Minor Defect 202.

PAGE 15

Add the following paragraph:

"4.4.3.3 Inverted weight test. The expelling charge assembly (less black powder and an ultrasonic seal) shall be subjected to an inverted weight gravity test in accordance with 4.5.3. Any assembly that fails to comply with the applicable requirements shall be cause for rejection of the lot."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:19Z
Check the source to verify that this is the current version before use.

Change 4.5.3 to read as follows:

"4.6 Dimensional control of molded or plastic parts."

Add the following paragraph:

"4.5.3 Inverted weight test procedure. The expelling charge cup shall be loaded with a 100 gram weight (sand optional) and a cover pressed and snap fitted completely onto the cup. Then the cup is inverted so that the cover of the cup is on the bottom (i.e. the stand off projection is on the top) and held for 3 seconds. The cover shall remain completely snap fitted to the cup."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-AC59)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:19Z
Check the source to verify that this is the current version before use.