MILITARY SPECIFICATION SHEET

PLUG ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Plug Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for

DRAWINGS

ORDNANCE CORPS

8800546 - Bag, Packing, Ammunition for Cable Assembly
8808362 - Packing and Marking for Storage and Shipments
8836674 - Plug
8836675 - Plug Assembly
8854368 - Test Fixture
EL-8836675 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table I

Circuit resistance (see dwg 8836675)

From connector Shell Pin	To other connector Shell Pin	Ohms Max
		0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.2 Inspection and testing to be performed in first article testing (see Table I, MIL-C-50288(MU). Add the following test:

Examination or test	Contractors inspection permissable before submission	Non-Dest.	Assembly
Pull	X	X	X

4.3 Classification of characteristics.

4.3.1 Plug assembly (see dwg 8836675).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for plug in accordance with dwg 8836674.....Visual

102. Length.....*Measure

* Measure with suitable scale.

Minor: None defined.

4.4 Testing.

4.4.1 Pull (see dwg 8836675). Each plug shall be tested in accordance with 4.6.1. If any cable assembly fails to comply with drawing requirements, the assembly shall be rejected and removed from the lot.

4.5 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50288(MU) and EL-8836675.

4.6 Test Methods.

4.6.1 Pull (see 4.4.1). The pull test shall be performed by utilizing test fixture dwg 8854368. In addition, the cable shall be gripped not

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

closer than 12 inches from the connector in such a manner that there will be no damage to the cable by gripping or slippage during the test. The test shall be applied for the minimum time specified on the drawing and after the test the cable assembly shall comply with Circuit and Insulation resistance, section 3, MIL-C-50288(MU)

4.6.2 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg 8836675)

Positive potential applied to plug Pin	Minus potential to other plug Shell

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800546 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800546 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800546 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing agency
Army - MU

Project No. - 1125-A041

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C-50288/3(MU) Plug Assembly

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.