MIL-C-60190(MU)
23 February 1965
SUPERSEDING
FA(FC)-PD-140
28 April 1961

MILITARY SPECIFICATION

CHOKE: 10525930

1. SCOPE

1.1 This specification covers one type of Choke (Type Designation: TF5RX04ZZ) used for voltage regulation in the Gun Direction Computer: M18.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-T-27	Transformers and Inductors (Audio, Power, and High Power Pulse) General Specification For
MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel: Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of
MIL-C-46357	Computer, Gun Direction: M18; Manufacturing Processes and Inspection of

STANDARDS

Military

MIL-STD-105	Sampling Procedure and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

DRAWINGS

U.S. Army Munitions Command

C10525930	Choke

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

MIL-P-14232/P10525930 Packaging of Choke

(Copies of specifications, standards, drawings, and packaging data sheets, required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The Choke (Type Designation: TF5RX04ZZ) shall be manufactured in accordance with Drawing C10525930 and drawings pertaining thereto.

3.1.1 Case and potting.- The case shall be of molded flame resistant fiber glass and resin construction and shall be potted with a self-extinguishing semi-flexible epoxy resin compound.

3.2 General specifications.- The choke shall meet the requirements of MIL-T-27 for its particular type designation or classification. The choke shall also meet the specified requirements of MIL-C-46357:

(a) Installation of hardware
(b) Securing leads
(c) Soldering
(d) Solvent vapor degreasing
(e) Marking ink for non-metals
(f) Application of decals
(g) Twenty-four hour test procedure for transformers and inductors

3.2.1 Order of precedence.- Should any conflict occur between the general specifications and the detailed specification the order of precedence shall be as follows:

(a) Detailed specification
(b) MIL-C-45357
(c) MIL-T-27

3.3 Environmental service conditions.

3.3.1 Vibration.- The choke shall be subjected to a simple harmonic motion having an amplitude of 0.03 inch (0.06 inch total excursion). The frequency shall be varied uniformly from 10 to 55 cycles per second (cps) and return to 10 cycles. This cycle shall be traversed in 1 minute ± 15 seconds. The motion shall be applied to the choke for a period of 10 minutes in each direction of the 3 mutually perpendicular axes (total of 30 minutes), relative to its normal operational position. Subsequent to vibration, the choke shall not be damaged or adversely affected and shall meet the requirements of 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

3.3.2 Shock.- The choke shall withstand 3 shock impulses in each of 3 mutually perpendicular directions. The acceleration of the shock impulses shall be 5 gravity units (G's). Pulse duration of each impulse shall be 11 ± 1 milliseconds. Subsequent to shock the item shall not have been damaged or adversely affected and shall meet the requirements of 3.4.

3.3.3 Temperatures.

3.3.3.1, Operating.- The choke shall meet the requirements of 3.4 while exposed to temperatures of -40°F and +135°F.

3.3.3.2 Storage.- The choke shall meet the requirements of 3.4 at a temperature of between 60°F and 90°F after having been exposed to each temperature of -80°F and +220°F.

3.3.4 Humidity.

3.3.4.1 Operating.- The choke shall meet the requirements of 3.4 while exposed to an atmosphere with a relative humidity (RH) up to 97% at a temperature of 135°F.

3.3.4.2 Non-operating.- The choke shall meet the requirements of 3.4 after exposure to (and when thoroughly dried) and atmosphere with a RH of 100 percent including condensation, for a period of 4 hours.

3.3.5 Fungus resistance.- The choke shall show no evidence of damage and shall meet the requirements of 3.4, after being inoculated with the composite spore suspension specified in MIL-F-13926 and incubated at an ambient temperature of between 77°F and 84°F with a RH of 97 ± 2%.

3.4 Performance.- Unless otherwise specified the transformer shall meet the performance requirements of this specification at ambient temperatures between 60 and 90°F; a barometric pressure of 28 to 32 inches of mercury; and a RH up to 90%.

3.4.1 Inductance.- The inductance shall be 0.005 henry ± 10 percent at 5 volts rms, 400 cps, with 7 amperes dc applied to terminal 1-2.

3.4.2 DC resistance.- The dc resistance shall be within the limits of .15 ohms maximum, and 0.085 ohms minimum.

3.4.3 Insulation resistance.- The insulation resistance shall be 10,000 megohms minimum between the winding and mounting inserts.

3.4.4 Dielectric strength.- The dielectric strength at sea level, shall be 500 volts rms.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Submission of Product.- Unless otherwise specified herein, or by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examinations and tests.- Except where otherwise specified herein, components and sub-assemblies shall be inspected in accordance with the "Inspection provisions for components and sub-assemblies" and the Sampling Plan Tables contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed in accordance with Table I, II, and III and the test methods and procedures in 4.5. Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein.

4.2.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.2.4 Functional tests.- The requirements and tests in Table I shall be inspected on a 100% basis. All examinations and tests shall be conducted at the standard ambient temperature (60 to 90°F.).

TABLE I
(100 percent inspection)

Characteristics	Requirement	Test Procedures
101. Inductance	3.4.1	4.5.2.1
102. DC resistance	3.4.2	4.5.2.2
103. Insulation resistance	3.4.3	4.5.2.3
104. Dielectric strength	3.4.4	4.5.2.4

4.3 Standard sampling.

4.3.1 General.- One unit shall be selected at random by a Government representative as a standard sample from each 100 produced. The sample shall meet the requirements and tests in Table II,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

TABLE II

Characteristics	Requirement	Test Procedures
301. Fabrication	3.1	Applicable drawings - visual
302. General specifications	3.2	MIL-T-27 and MIL-C-46337

4.3.2 Environmental.- Three units shall be selected at random by a Government representative as a standard sample from each 50 produced or from each month's production, whichever occurs first. The samples shall have met the requirements and tests in Table I and shall then meet the requirements and tests in Table III.

TABLE III

Characteristics	Requirement	Test Procedures
303. Vibration	3.3.1	4.5.1.1
304. Shock	3.3.2	4.5.1.2
305. Humidity-Operating	3.3.4.1	4.5.1.3.2
306. Humidity-Non-operating	3.3.4.2	4.5.1.3.1
307. Operating temperature	3.3.3.1, 3.4	4.5.1.4
308. Storage temperature	3.3.3.2	4.5.1.4.1

4.3.3 Failure of sampling.- Should any one item of a standard sample fail to meet the specified test requirements, acceptance of the represented production lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (See 4.2.3).

4.4 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply equipment in accordance with the applicable requirements of MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 Contractor design.- The contractor shall provide inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5 and with the "Component Inspection" and "Test facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

4.4.1.1 Test equipment.- In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5:

Item	Description
1	Vacuum tube ac rms voltmeter, accuracy ± 1 percent of full scale
2	Kelvin type resistance bridge
3	Incremental inductance bridge, accuracy ± 10 percent
4	DC ammeter, accuracy ± 1/2 percent of full scale
5	Megohmmeter, accuracy ± 10 percent at 10,000 megohms
6	Dielectric strength (hi-pot) tester to operate at 60 cps, see paragraph 4.5.2.4

4.5 Test methods and procedures.

4.5.1 Environmental.

4.5.1.1 Vibration.- The vibration test shall be made on a device with means provided for measuring and controlling the direction of vibration and adjusting the amplitudes and frequencies to keep them within the specified limits of 3.3.1. The measuring instruments of the testing device shall be capable of measuring the vibration amplitude within plus or minus 5 percent, and capable of measuring the frequency within plus or minus 2 percent. The test shall be performed in accordance with the requirements specified in 3.3.1 with the unit rigidly mounted in its normal operating position. Subsequent to the vibration test, the unit shall show no damage or defect resulting from the test when examined by visual and tactile means. The unit shall then be inspected as specified in 4.5.1.2 prior to determining compliance with requirements specified under 3.4.

4.5.1.2 Shock.- This test shall be conducted in accordance with procedure II of the shock test defined in MIL-F-13926 except that impact shocks shall not exceed 50's. The unit shall be subsequently inspected for physical damage or defects in compliance with 3.3.2. The unit shall then be inspected as specified in 4.5.1.3 prior to determining compliance with the requirements of 3.4 as specified in 3.3.2.

4.5.1.3 Humidity.

4.5.1.3.1 Non-operating.- This test shall be conducted in accordance with the humidity test defined in Procedure I of MIL-F-13926 except that the 4-1/2 hour period shall be reduced to 2 hours, the 6 hour period reduced to 2 hours, and the test period shall not exceed 5.5 hours per cycle. The unit shall then be thoroughly dried and then subjected to the test in 4.5.1.3.2 prior to meeting the specified requirements of 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926 except that the humidity shall be maintained at 95 ± 5 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test the unit shall be operated in accordance with paragraph 4.5.2 of this specification, and shall meet the specified requirements of 3.3.4.1.

4.5.1.4 Temperature.- (operating and storage): After being subjected to all environmental tests specified above, the unit shall be subjected to Test Procedure I specified in MIL-F-13926, except the temperatures specified in 3.3.3 shall apply. While at the operating temperature of 3.3.3.1 the unit shall be tested in accordance with 4.5.1.4 to determine compliance with the requirements of 3.4 as required by 3.3.3.1. The temperature shall then be returned to standard temperature (60° to 90°F) and the unit shall be tested in accordance with 4.5.2 to determine compliance with 3.3.3.2.

4.5.2 Performance.- The choke shall be tested to conform with 3.4 and the general test requirements of Specification MIL-T-27.

4.5.2.1 Inductance test.- Using an incremental inductance bridge or equivalent, apply 5 ± 10 percent volts rms, 400 ± 5 percent cps, and 7 amperes ± 1/2 percent to terminals 1-2. The inductance measured shall be 0.005 henry ± 10 percent as specified in 3.4.1.

4.5.2.2 DC resistance test.- The dc resistance shall be measured on a Kelvin type bridge and shall be within the limits specified in paragraph 3.4.2.

4.5.2.3 Insulation resistance test.- To determine compliance with 3.4.3 this test shall be made using a source potential of 500 ± 10 vdc and a megohmmeter having an accuracy of ± 10 percent or better. The resistance between the winding and mounting inserts shall be 10,000 megohms minimum. The voltage shall be applied for a period not to exceed 1 minute.

4.5.2.4 Dielectric strength test.- This test shall be performed in accordance with the dielectric strength test of Specification MIL-T-27, after the choke has been encapsulated, and shall meet the requirements of 3.4.4 of this specification. All tests shall be made by means of equipment expressly designed for high potential testing. The equipment shall include a calibrated leakage current indicator. Indications of leakage current on the 60 cycle dielectric strength test equipment (when adjusted per manufacturer's recommendations) shall establish the need for further diagnostic tests such as DC dielectric strength test (set to 1.4 times the required AC test voltage) or DC leakage current tests performed at the same peak voltage level as the dielectric strength test. The additional tests shall be considered as final authority for acceptance or rejection of units that have indications of AC leakage current. AC leakage current can be expected on this choke because of the electro-static shields.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P10525930. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The choke is used in an LC filter circuit for energy storage and AC ripple filtering in a voltage regulator of the computer.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Applicable packaging data sheet (see 5.1).
(c) Selection of applicable level of preservation, packaging and packing.
(d) A block of serial numbers to identify each choke.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A185Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-5500
Philadelphia, Pa. 19137

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.