MIL-P-63268A (AR)
AMENDMENT 2
22 April 1988
SUPERSEDING
AMENDMENT 1
27 October 1983

MILITARY SPECIFICATION

PLUG, SHOCK ATTENUATING

This amendment forms a part of Military Specification MIL-P-63268A (AR), dated 4 June 1981, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Under "SPECIFICATIONS" add the following:

"FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surface for Organic Coatings".

PAGE 3

4.3.1: Delete in its entirety and substitute the following:

"4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Plug, Shock Attenuating	9341742	25 minimum

When a multiple cavity mold is to be used in production, the sample shall include at least three plugs from each cavity in the mold. The plug shall exhibit a permanent cavity identification."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

PAGE 4

Table I:

Delete "25" and substitute "25 min, Note 1."

Add Note 1 as follows:

"1. Minimum of 3 per cavity from multiple cavity molds."

* Add the following test:

"Salt spray test	2	3.2	4.5.5".

PAGE 6

4.4.2.1:

Major 101: Under Category column, Delete "W".

Major 112: Delete "pitch" and substitute "major".

PAGE 7

4.4.2.1:

Minor 209: Delete in its entirety.

PAGE 8

4.4.3.1: Delete in its entirety and substitute:

"4.4.3.1 Mechanical properties tests. The minimum sample size for these tests shall be 20 parts per lot. If a multiple cavity mold is used, the sample shall be divided equally among the cavities. If more than 20 cavities are used, the sample shall consist of one part from each cavity. If any sample part fails to meet any requirement, the lot represented by the failing part shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

* Add the following:

"4.5.5 Salt spray test. The sampling plan for this test shall be as specified in TT-C-490. The test shall be performed on the plugs as specified in TT-C-490. The number of hours and the percentage of sodium chloride solution shall be as indicated on the applicable drawing. Examination shall be made for any evidence of corrosion of the painted areas. If any plug fails to comply with the specified requirements, it shall be classified defective and corrective action taken as specified in TT-C-490."

5.1.1: Delete in its entirety and substitute the following two new paragraphs:

"5.1.1 Level A. Lifting plugs shall be semi-bulk packaged, moisture-proof packaged (barrier bag only), packed, marked and palletized in accordance with MIL-STD-1169. Plugs shall be separated in the unit pack to protect the paint surfaces.

5.1.2 Level B. Lifting plugs shall be semi-bulk packaged, packed and marked in accordance with MIL-STD-1169. Palletization is optional. Alternative packaging lifting plugs shall be semi-bulk packed in a Type 1, Class II Spec PPP-B-587, wire bound pallet box (modified as required). Plugs shall be separated in the unit package to protect the paint surfaces."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AB01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.