MIL-G-50960 (MU)
27 August 1971

MILITARY SPECIFICATI0N

GASKET

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation. For delivery criteria for one type of gasket for the indicator humidity plug for containers.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling procedures and tables for Inspection by Attributes
MIL-STD-l169(MU) - Packaging,Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8791668 - Gasket
8791670 - Gasket
8808362 - Packing and Marking for Storage and Shipments
8848472 - Bag, Packing, Ammunition for Gasket

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:45Z
Check the source to verify that this is the current version before use.

EL8791668 - Equipment List
EL8791670 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials - The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The gasket shall comply with all requirements specified on the drawing (dwg) 8791668 or 8791670, with all requirements specified herein and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity,or any similar characteristics.

3.3.2 Burrs. Parts shall be free from burrs.

3.3.3 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.4 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performnace of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not Applicable.

4.3 Product acceptance inspection.

4.3.1 Inspection lot. A lot or batch and its formation, size, and presentation is described in ML-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items. In the inspection lot. a sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2) Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:
4.3.2.1.1 Gasket (see dwg 8791668) or gasket (see dwg 8791670).

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

Major:
101. Outside diameter . . . . . .Gage
102. Thickness . . . . . .Gage
103. Inside diameter . . . . . Visual
104. Materia1 (see 3.1) . . . . . Visual
105. No tears, cracks or holes in gasket . . . . . .Visual

Minor:
201. Workmanship (see 3.3) . . . . . Visual/Manual

4.3.2.1.2 Preparation for delivery (see 5.1) .

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Preservation, packaging, packing and marking in accordance with MIL-P-l169(MU) . . Visual/Manual

Minor: None defined.

4.3.2.1.3 Bag, packing, ammunition, for gasket (see dwg. 8848472 covering dwg part nos 8848472-1 or 2 as applicable and 5.)

Categories	Characteristics	Method of Inspection

Critical: none defined.

Major:
101. Material (See 3.1) . . . . . Visual
102. Length before Packing, min . . . . . *Measure
103. Width before packing, min. . . . . Measure
104. Properly packed . . . . . Visual/Manual
105. Proper heat seal . . . . . Visual/Manual
106. No crack or hole in bag . . . . . Visual
107. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116 . . . . . Visual
108. Stiffeners present. . . . . Manual

*Measure with suitable scale.

Minor:
201. Marking. . . . . Visual
202. Workmanship (see 3. 3) . . . . . .Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:45Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Manual
103.	Properly packed	Visual/Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual/Manual

4.3.3 Testing. Not Applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8791668 or EL-8791670). When either of the ocnditions listed below exist the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).

b. The code “CD” is listed in the "Part or Identifying Number” column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests- Acceptance inspection equipment for minor characteristics is not specified On ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:45Z
Check the source to verify that this is the currentversion before use.

5* PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and Packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5:1.1.1 Level A. The gasket shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU) .

5.1.1.2 Level C. The gasket shall be preserved and packaged accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The gasket shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU) .

5.1.3 Marking Marking shall be in accordance with MIL-STD-1169 (MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and Packaqinq shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The gasket shall be packaged in accordance with dwg 8848472 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The gasket shall be packaged in accordance with dwg 8808362 except that the moisture! barrier may be omitted;

5.2,2 Packing.

5.2,2.1 Level A and C. The gasket shall be packed in accordance with dwg 8848472 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwg 8848472 and 8868362 as applicable,

6. NOTES

6.1 ordering data. Procurement documents should specify:

6.1.1 Procurement requirements.

a. Title, number and date of this specifiecation
b. Production or Repair Part
c. Selection of applicable level of packaging and and packing required (see 5.1 and 5.2).
d. Selection of applicable dwg part number for Bag for packaging (see 4.3.2.1.3).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be Verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No.l195A 103

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:45Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* - Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* - Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* - Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-G-50960 (AR)
NOTICE 3
21 June 1995

MILITARY SPECIFICATION

GASKET

This notice should be filed in front of MIL-G-50960 (AR), dated 27 August 1971.

MIL-G-50960 (AR) dated 27 August 1971, with Validation Notice 2, dated 20 August 1991 is inactive for new design and is no longer used, except for replacement purposes.

Preparing Activity
Army-AR

AMSC N/A

FSC 1195

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.