MILITARY SPECIFICATION -

LAUNCHER, GUIDED MISSILE AERO 5A-1 AND AERO 5B-1

This amendment forms a part of Military Specification MIL-L-81437(AS) dated " l March 1968,

Page 1

Title: Add "and AER0 5B-1".

Paragraph 1.1 Scope: After AERO 5A-1, add "and AERO 5B-1".

Page 3

Drawings: Add:

DL 248AS100 Data List, Launcher, Airborne, Guided Missile, Aero 5B-1

Page 5

Add new paragraph:

3.3.15 Missile retention mechanism for AERO 5b-1 - The launcher shall contain a forward retention mechanism. This mechanism consists of a ratio linkage and a solenoid. When the mechanism is unlocked, a compression spring connected to the linkage restrains the missile with a force of no less than 837 pounds and no more than 2079 pounds. When the mechanism is locked, the missile is restrained from leaving the launcher and self-contained switches prevent ignition of the missile's engine.

Page 8

Delete paragraph 3.5.6 Missile Retention Mechanism.

Renumber paragraph from 3.5.7 to 3.5.6 ~~vibration~~.

Renumber paragraph from 3.5.8 to 3.5.7 ~~Structural Strength~~.

Renumber paragraph from 3.5.9 to 3.5.8 Shock.

FSC 1055

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:24Z
Check the source to verify that this is the current version before use.

paragraph 4.4.1 Tolerances: Change (4) Vibration frequency tolerance from plus on minus 2 percent to plus or minus 5 percent. Change (5) Vibration amplitude tolerance from plus on minus 5 percent to plus or minus 10 percent.

Custodian:

Navy - AS

Preparing Activity:

Navy - AS

*U.S. GOVERNMENT PRINTING OFFICE :1972-714-538/2172

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:24Z
Check the source to verify that this is the current version before use.