PERFORMANCE SPECIFICATION SHEET

CAPACITOR, FIXED, CERAMIC DIELECTRIC, SWITCH MODE POWER SUPPLY (GENERAL PURPOSE AND TEMPERATURE STABLE), UNENCAPSULATED, HORIZONTALLY STACKED, STYLE PS01

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-49470.




FIGURE 1. Style PS01 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

Dimensions					
Case code	C ± .025	D		E (max)	Number of leads per side
		Min	Max		
1	.450	1.950	2.075	.500	20
2	.800	1.450	1.535	.870	15
3	.450	.950	1.075	.500	10
4	.400	.350	.425	.440	4
5	.250	.224	.275	.300	3
6	1.250	1.950	2.075	1.350	20

Inches	mm	Inches	mm
.002	0.05	.425	10.80
.010	0.25	.440	11.18
.020	0.51	.450	11.43
.025	0.64	.500	12.70
.050	1.27	.800	20.32
.055	1.40	.870	22.10
.070	1.78	.950	24.13
.100	2.54	1.075	27.30
.224	5.69	1.250	31.75
.250	6.35	1.350	34.29
.275	6.98	1.450	36.83
.300	7.62	1.535	38.99
.350	8.89	1.950	49.53
.400	10.16	2.075	52.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 inch (0.25 mm).
4. Lead frame configuration is shown as typical above the seating plane.
5. See table I for specific maximum A dimension. For maximum B dimension, add .065 inch (1.65 mm) to the appropriate A dimension. For all lead styles, the number of chips is determined by the capacitance and voltage rating.
6. For case code 5, dimensions shall be .100 (2.54 mm) maximum and .012 inch (0.30 mm) minimum.
7. Lead alignment within pin rows shall be within ±.005 inch (0.13 mm).

FIGURE 1. Style PS01 capacitors - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Precautionary note: Capacitors covered by this specification sheet are very susceptible to thermal shock damage due to their large ceramic mass. Temperature profiles used should provide adequate temperature rise and cool-down time to prevent damage from thermal shock.

Dimensions and configurations: See figure 1.

Case type: Unencapsulated, horizontally stacked.

Capacitance: See table I.

Capacitance tolerance: J = ±5 percent, K = ±10 percent, M = ±20 percent.

Operating temperature range: -55°C to +125°C.

Voltage rating: See table I.

Dielectric types: BP, BQ, BR, and BX in accordance with MIL-PRF-49470.

Temperature coefficient: 0 ppm/°C ±30 ppm/°C (BP), ±15 percent (BQ, BR, BX).

Voltage-temperature limits: In accordance with MIL-PRF-49470.

Symbol	Capacitance change with reference to +25°C	
	Step A through step D of voltage-temperature limit cycle table of MIL-PRF-49470	Step E through step G of voltage-temperature limit cycle table of MIL-PRF-49470
BP	0 ppm/°C ± 30 ppm/°C	0 ppm/°C ± 30 ppm/°C
BQ	±15 percent	+15, -50 percent
BR	±15 percent	+15, -40 percent
BX	±15 percent	+15, -25 percent

Marking: In accordance with MIL-PRF-49470.

Body insulation: Not applicable.

Solderability: The leads shall be solderable up to the seating plane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
50 V						
M49470P01563-A-	0.056	J,K	BP	5	J,L,N	.120 (3.05)
M49470P01683-A-	0.068	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01823-A-	0.082	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01104-A-	0.1	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01124-A	0.12	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01154-A-	0.15	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01184-A-	0.180	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01224-A-	0.220	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01274-A-	0.270	J,K	BP	5	J,L,N	.650 (16.51)
M49470P01334-A-	0.330	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01394-A-	0.390	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01474-A-	0.470	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01564-A-	0.560	J,K	BP	4	J,L,N	.650 (16.61)
M49470P01684-A-	0.680	J,K	BP	3	J,L,N	.240 (6.10)
M49470P01824-A-	0.820	J,K	BP	3	J,L,N	.240 (6.10)
M49470P01105-A-	1.0	J,K	BP	3	J,L,N	.360 (9.14)
M49470X01105-A-	1.0	K,M	BX	5	J,L,N	.120 (3.05)
M49470P01125-A-	1.2	J,K	BP	3	J,L,N	.360 (9.14)
M49470X01125-A-	1.2	K,M	BX	5	J,L,N	.120 (3.05)
M49470P01155-A-	1.5	J,K	BP	3	J,L,N	.480 (12.19)
M49470X01155-A-	1.5	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01185-A-	1.8	J,K	BP	3	J,L,N	.480 (12.19)
M49470X01185-A-	1.8	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01225-A-	2.2	J,K	BP	3	J,L,N	.650 (16.51)
M49470X01225-A-	2.2	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01275-A-	2.7	J,K	BP	1	J,L,N	.360 (9.14)
M49470X01275-A-	2.7	K,M	BX	5	J,L,N	.360 (9.14)
M49470P01335-A-	3.3	J,K	BP	1	J,L,N	.480 (12.19)
M49470X01335-A-	3.3	K,M	BX	5	J,L,N	.360 ((9.14)
M49470P01395-A-	3.9	J,M	BP	1	J,L,N	.480 (12.19)
M49470X01395-A-	3.9	K,M	BX	5	J,L,N	.480 (12.19)
M49470P01475-A-	4.7	J,M	BP	1	J,L,N	.650 (16.51)
M49470X01475-A-	4.7	K,M	BX	5	J,L,N	.480 (12.19)
M49470P01565-A-	5.6	J,K	BP	2	J,L,N	.650 (16.51)
M49470X01565-A-	5.6	K,M	BX	5	J,L,N	.650 (16.51)
M49470P01685-A-	6.8	J,K	BP	6	J,L,N	.360 (9.14)
M49470X01685-A-	6.8	K,M	BX	4	J,L,N	.360 (9.14)
M49470P01825-A-	8.2	J,K	BP	6	J,L,N	.360 (9.14)
M49470X01825-A-	8.2	K,M	BX	4	J,L,N	.360 (9.14)
M49470P01106-A-	10	J,K	BP	6	J,L,N	.480 (12.19)

1/ See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

PIN 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
50V						
M49470X01106-A-	10	K,M	BX	4	J,L,N	.480 (12.19)
M49470P01126-A-	12	J,K	BP	6	J,L,N	.480 (12.19)
M49470X01126-A-	12	K,M	BX	4	J,L,N	.480 (12.19)
M49470P01156-A-	15	J,K	BP	6	J,L,N	.650 (16.51)
M49470X01156-A-	15	K,M	BX	4	J,L,N	.650 (16.51)
M49470X01186-A-	18	K,M	BX	3	J,L,N	.240 (6.10)
M49470X01226-A-	22	K,M	BX	3	J,L,N	.360 (9.14)
M49470X01276-A-	27	K,M	BX	3	J,L,N	.360 (9.14)
M49470X01336-A-	33	K,M	BX	3	J,L,N	.360 (9.14)
M49470X01396-A-	39	K,M	BX	3	J,L,N	.480 (12.19)
M49470X01476-A-	47	K,M	BX	3	J,L,N	.650 (16.51)
M49470X01566-A-	56	K,M	BX	1	J,L,N	.360 (9.14)
M49470X01686-A-	68	K,M	BX	1	J,L,N	.480 (12.19)
M49470X01826-A-	82	K,M	BX	1	J,L,N	.480 (12.19)
M49470X01107-A-	100	K,M	BX	1	J,L,N	.650 (16.51)
M49470X01127-A-	120	K,M	BX	2	J,L,N	.480 (12.19)
M49470X01157-A-	150	K,M	BX	2	J,L,N	.650 (16.51)
M49470X01187-A-	180	K,M	BX	6	J,L,N	.480 (12.19)
M49470X01227-A-	220	K,M	BX	6	J,L,N	.480 (12.19)
M49470X01277-A-	270	K,M	BX	6	J,L,N	.650 (16.51)
100V						
M49470P01473-B-	0.047	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01563-B-	0.056	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01683-B-	0.068	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01823-B-	0.082	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01104-B-	0.1	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01124-B-	0.12	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01154-B-	0.15	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01184-B-	0.18	J,K	BP	5	J,L,N	.650 (16.51)
M49470P01224-B-	0.22	J,K	BP	5	J,L,N	.650 (16.51)
M49470P01274-B-	0.27	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01334-B-	0.33	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01394-B-	0.39	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01474-B-	0.47	J,K	BP	4	J,L,N	.650 (16.51)
M49470P01564-B-	0.56	J,K	BP	4	J,L,N	.650 (16.51)
M49470P01684-B-	0.68	J,K	BP	3	J,L,N	.240 (6.10)
M49470X01684-B-	0.68	K,M	BX	5	J,L,N	.120 (3.05)
M49470P01824-B-	0.82	J,K	BP	3	J,L,N	.120 (3.05)
M49470X01824-B-	0.82	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01105-B-	1	J,K	BP	3	J,L,N	.360 (9.14)

1/ See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

PIN 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
100V						
M49470X01105-B-	1	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01125-B-	1.2	J,K	BP	3	J,L,N	.480 (12.19)
M49470X01125-B-	1.2	K,M	BX	5	J,L,N	.240 (6.10)
M49470P01155-B-	1.5	J,K	BP	3	J,L,N	.480 (12.19)
M49470X01155-B-	1.5	K,M	BX	5	J,L,N	.360 (9.14)
M49470P01185-B-	1.8	J,K	BP	3	J,L,N	.650 (16.51)
M49470X01185-B-	1.8	K,M	BX	5	J,L,N	.360 (9.14)
M49470P01225-B-	2.2	J,K	BP	1	J,L,N	.480 (12.19)
M49470X01225-B-	2.2	K,M	BX	5	J,L,N	.480 (12.19)
M49470P01275-B-	2.7	J,K	BP	1	J,L,N	.480 (12.19)
M49470X01275-B-	2.7	K,M	BX	5	J,L,N	.480 (12.19)
M49470P01335-B-	3.3	J,K	BP	1	J,L,N	.650 (16.51)
M49470X01335-B-	3.3	K,M	BX	5	J,L,N	.650 (16.51)
M49470P01395-B-	3.9	J,K	BP	2	J,L,N	.480 (12.19)
M49470X01395-B-	3.9	K,M	BX	4	J,L,N	.360 (9.14)
M49470P01475-B-	4.7	J,K	BP	2	J,L,N	.650 (16.51)
M49470X01475-B-	4.7	K,M	BX	4	J,L,N	.360 (9.14)
M49470P01565-B-	5.6	J,K	BP	6	J,L,N	.360 (9.14)
M49470X01565-B-	5.6	K,M	BX	4	J,L,N	.480 (12.19)
M49470P01685-B-	6.8	J,K	BP	6	J,L,N	.360 (9.14)
M49470X01685-B-	6.8	K,M	BX	4	J,L,N	.480 (12.19)
M49470P01825-B-	8.2	J,K	BP	6	J,L,N	.480 (12.19)
M49470X01825-B-	8.2	K,M	BX	4	J,L,N	.650 (16.51)
M49470P01106-B-	10	J,K	BP	6	J,L,N	.650 (16.51)
M49470X01106-B-	10	K,M	BX	3	J,L,N	.240 (6.10)
M49470P01126-B-	12	J,K	BP	6	J,L,N	.650 (16.51)
M49470X01126-B-	12	K,M	BX	3	J,L,N	.240 (6.10)
M49470X01156-B-	15	K,M	BX	3	J,L,N	.360 (9.14)
M49470X01186-B-	18	K,M	BX	3	J,L,N	.360 (9.14)
M49470X01226-B-	22	K,M	BX	3	J,L,N	.480 (12.19)
M49470X01276-B-	27	K,M	BX	3	J,L,N	.650 (16.51)
M49470X01336-B-	33	K,M	BX	1	J,L,N	.360 (9.14)
M49470X01396-B-	39	K,M	BX	1	J,L,N	.480 (12.19)
M49470X01476-B-	47	K,M	BX	1	J,L,N	.480 (12.19)
M49470X01566-B-	56	K,M	BX	1	J,L,N	.650 (16.51)
M49470X01686-B-	68	K,M	BX	2	J,L,N	.480 (12.19)
M49470X01826-B-	82	K,M	BX	2	J,L,N	.650 (16.51)
M49470X01107-B-	100	K,M	BX	6	J,L,N	.360 (9.14)
M49470X01127-B-	120	K,M	BX	6	J,L,N	.360 (9.14)
M49470X01157-B-	150	K,M	BX	6	J,L,N	.480 (12.19)
M49470X01187-B-	180	K,M	BX	6	J,L,N	.650 (16.51)

1/ See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

PIN 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
200V						
M49470P01223-C-	0.022	J,K	BP	5	J,L,N	.120 (3.05)
M49470P01273-C-	0.027	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01333-C-	0.033	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01393-C-	0.039	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01473-C-	0.047	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01563-C-	0.056	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01683-C-	0.068	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01823-C-	0.082	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01104-C-	0.1	J,K	BP	5	J,L,N	.650 (16.51)
M49470P01124-C-	0.12	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01154-C-	0.15	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01184-C-	0.18	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01224-C-	0.22	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01274-C-	0.27	J,K	BP	4	J,L,N	.650 (16.51)
M49470P01334-C-	0.33	J,K	BP	3	J,L,N	.240 (6.10)
M49470P01394-C-	0.39	J,K	BP	3	J,L,N	.240 (6.10)
M49470P01474-C-	0.47	J,K	BP	3	J,L,N	.360 (9.14)
M49470R01474-C-	0.47	K,M	BR	5	J,L,N	.240 (6.10)
M49470P01564-C-	0.56	J,K	BP	3	J,L,N	.360 (9.14)
M49470R01564-C-	0.56	K,M	BR	5	J,L,N	.240 (6.10)
M49470P01684-C-	0.68	J,K	BP	3	J,L,N	.480 (12.19)
M49470R01684-C-	0.68	K,M	BR	5	J,L,N	.360 (9.14)
M49470P01824-C-	0.82	J,K	BP	3	J,L,N	.650 (16.51)
M49470R01824-C-	0.82	K,M	BR	5	J,L,N	.360 (9.14)
M49470P01105-C-	1	J,K	BP	3	J,L,N	.650 (16.51)
M49470R01105-C-	1	K,M	BR	5	J,L,N	.480 (12.19)
M49470P01125-C-	1.2	J,K	BP	1	J,L,N	.480 (12.19)
M49470R01125-C-	1.2	K,M	BR	5	J,L,N	.480 (12.19)
M49470P01155-C-	1.5	J,K	BP	1	J,L,N	.480 (12.19)
M49470R01155-C-	1.5	K,M	BR	5	J,L,N	.650 (16.51)
M49470P01185-C-	1.8	J,K	BP	1	J,L,N	.650 (16.51)
M49470R01185-C-	1.8	K,M	BR	4	J,L,N	.360 (9.14)
M49470P01225-C-	2.2	J,K	BP	2	J,L,N	.480 (12.19)
M49470R01225-C-	2.2	K,M	BR	4	J,L,N	.360 (9.14)
M49470P01275-C-	2.7	J,K	BP	2	J,L,N	.650 (16.51)
M49470R01275-C-	2.7	K,M	BR	4	J,L,N	.480 (12.19)
M49470P01335-C-	3.3	J,K	BP	6	J,L,N	.360 (9.14)
M49470R01335-C-	3.3	K,M	BR	4	J,L,N	.480 (12.19)
M49470P01395-C-	3.9	J,K	BP	6	J,L,N	.360 (9.14)
M49470R01395-C-	3.9	K,M	BR	4	J,L,N	.650 (16.51)

1/ See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

PIN 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
200V						
M49470P01475-C-	4.7	J,K	BP	6	J,L,N	.480 (12.19)
M49470R01475-C-	4.7	K,M	BR	3	J,L,N	.240 (6.10)
M49470P01565-C-	5.6	J,K	BP	6	J,L,N	.650 (16.51)
M49470R01565-C-	5.6	K,M	BR	3	J,L,N	.240 (6.10)
M49470R01685-C-	6.8	K,M	BR	3	J,L,N	.360 (9.14)
M49470R01825-C-	8.2	K,M	BR	3	J,L,N	.360 (9.14)
M49470R01106-C-	10	K,M	BR	3	J,L,N	.480 (12.19)
M49470R01126-C-	12	K,M	BR	3	J,L,N	.650 (16.51)
M49470R01156-C-	15	K,M	BR	1	J,L,N	.360 (9.14)
M49470R01186-C-	18	K,M	BR	1	J,L,N	.480 (12.19)
M49470R01226-C-	22	K,M	BR	1	J,L,N	.650 (16.51)
M49470R01276-C-	27	K,M	BR	1	J,L,N	.650 (16.51)
M49470R01336-C-	33	K,M	BR	2	J,L,N	.480 (12.19)
M49470R01396-C-	39	K,M	BR	2	J,L,N	.650 (16.51)
M49470R01476-C-	47	K,M	BR	6	J,L,N	.240 (6.10)
M49470R01566-C-	56	K,M	BR	6	J,L,N	.360 (9.14)
M49470R01686-C-	68	K,M	BR	6	J,L,N	.360 (9.14)
M49470R01826-C-	82	K,M	BR	6	J,L,N	.480 (12.19)
M49470R01107-C-	100	K,M	BR	6	J,L,N	.650 (16.51)
M49470R01127-C-	120	K,M	BR	6	J,L,N	.650 (16.51)
500V						
M49470P01103-E-	0.01	J,K	BP	5	J,L,N	.120 (3.05)
M49470P01123-E-	0.012	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01153-E-	0.015	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01183-E-	0.018	J,K	BP	5	J,L,N	.240 (6.10)
M49470P01223-E-	0.022	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01273-E-	0.027	J,K	BP	5	J,L,N	.360 (9.14)
M49470P01333-E-	0.033	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01393-E-	0.039	J,K	BP	5	J,L,N	.480 (12.19)
M49470P01473-E-	0.047	J,K	BP	5	J,L,N	.650 (16.51)
M49470P01563-E-	0.056	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01683-E-	0.068	J,K	BP	4	J,L,N	.360 (9.14)
M49470P01823-E-	0.082	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01104-E-	0.1	J,K	BP	4	J,L,N	.480 (12.19)
M49470P01124-E-	0.12	J,K	BP	4	J,L,N	.650 (16.51)
M49470P01154-E-	0.15	J,K	BP	3	J,L,N	.240 (6.10)
M49470Q01154-E-	0.15	K,M	BQ	5	J,L,N	.120 (3.05)
M49470P01184-E-	0.18	J,K	BP	3	J,L,N	.240 (6.10)
M49470Q01184-E-	0.18	K,M	BQ	5	J,L,N	.240 (6.10)
M49470P01224-E-	0.22	J,K	BP	3	J,L,N	.360 (9.14)

1/ See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

PIN 1/	Capacitance µF	Capacitance tolerance	Characteristic	Case code	Lead style	Maximum A dimension inch (mm)
500V						
M49470Q01224-E-	0.22	K,M	BQ	5	J,L,N	.240 (6.10)
M49470P01274-E-	0.27	J,K	BP	3	J,L,N	.360 (9.14)
M49470Q01274-E-	0.27	K,M	BQ	5	J,L,N	.240 (6.10)
M49470P01334-E-	0.33	J,K	BP	3	J,L,N	.480 (12.19)
M49470Q01334-E-	0.33	K,M	BQ	5	J,L,N	.360 (9.14)
M49470P01394-E-	0.39	J,K	BP	3	J,L,N	.650 (16.51)
M49470Q01394-E-	0.39	K,M	BQ	5	J,L,N	.360 (9.14)
M49470P01474-E-	0.47	J,K	BP	1	J,L,N	.360 (9.14)
M49470Q01474-E-	0.47	K,M	BQ	5	J,L,N	.360 (9.14)
M49470P01564-E-	0.56	J,K	BP	1	J,L,N	.480 (12.19)
M49470Q01564-E-	0.56	K,M	BQ	5	J,L,N	.480 (12.19)
M49470P01684-E-	0.68	J,K	BP	1	J,L,N	.480 (12.19)
M49470Q01684-E-	0.68	K,M	BQ	5	J,L,N	.650 (16.51)
M49470P01824-E-	0.82	J,K	BP	1	J,L,N	.650 (16.51)
M49470Q01824-E-	0.82	K,M	BQ	4	J,L,N	.360 (9.14)
M49470P01105-E-	1	J,K	BP	2	J,L,N	.480 (12.19)
M49470Q01105-E-	1	K,M	BQ	4	J,L,N	.360 (9.14)
M49470P01125-E-	1.2	J,K	BP	2	J,L,N	.650 (16.51)
M49470Q01125-E-	1.2	K,M	BQ	4	J,L,N	.360 (9.14)
M49470P01155-E-	1.5	J,K	BP	6	J,L,N	.360 (9.14)
M49470Q01155-E-	1.5	K,M	BQ	4	J,L,N	.480 (12.19)
M49470P01185-E-	1.8	J,K	BP	6	J,L,N	.480 (12.19)
M49470Q01185-E-	1.8	K,M	BQ	4	J,L,N	.650 (16.51)
M49470P01225-E-	2.2	J,K	BP	6	J,L,N	.650 (16.51)
M49470Q01225-E-	2.2	K,M	BQ	3	J,L,N	.240 (6.10)
M49470Q01275-E-	2.7	K,M	BQ	3	J,L,N	.360 (9.14)
M49470Q01335-E-	3.3	K,M	BQ	3	J,L,N	.360 (9.14)
M49470Q01395-E-	3.9	K,M	BQ	3	J,L,N	.360 (9.14)
M49470Q01475-E-	4.7	K,M	BQ	3	J,L,N	.480 (12.19)
M49470Q01565-E-	5.6	K,M	BQ	3	J,L,N	.650 (16.51)
M49470Q01685-E-	6.8	K,M	BQ	1	J,L,N	.480 (12.19)
M49470Q01825-E-	8.2	K,M	BQ	1	J,L,N	.480 (12.19)
M49470Q01106-E-	10	K,M	BQ	1	J,L,N	.480 (12.19)
M49470Q01126-E-	12	K,M	BQ	1	J,L,N	.650 (16.51)
M49470Q01156-E-	15	K,M	BQ	2	J,L,N	.650 (16.51)
M49470Q01186-E-	18	K,M	BQ	2	J,L,N	.650 (16.51)
M49470Q01226-E-	22	K,M	BQ	6	J,L,N	.360 (9.14)
M49470Q01276-E-	27	K,M	BQ	6	J,L,N	.360 (9.14)
M49470Q01336-E-	33	K,M	BQ	6	J,L,N	.480 (12.19)
M49470Q01396-E-	39	K,M	BQ	6	J,L,N	.650 (16.51)

1/ Complete PIN shall include additional symbols to indicate capacitance tolerance and lead configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - MC
Air Force - 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-1809-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.