INCH-POUND

MIL-W-63377 (AR)
AMENDMENT 3
12 October 1992
SUPERSEDING
AMENDMENT 2
1 February 1991

MILITARY SPECIFICATION

WARHEAD, ILLUMINATING, M257 W/M442 FUZE (2.75 INCH ROCKET ILLUMINATING FLARE)

This amendment forms a part of Military Specification MIL-W-63377 (AR), dated 29 April 1987, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1.1: Add "MIL-W-63468 - Warhead, 2.75 Inch Rocket, H.E.: M261".

PAGE 3

* 2.1.2: Add "233AS431 - Rocket Motor, Inert, MK66".

* Add "1-2-601 - Laboratory Inspection Schedules, International Test Operation Procedures (ITOP), TECOM".

3.4.1: Delete in its entirety and substitute:

"3.4.1 Function Time. The time between rocket motor ignition and flare candle ignition shall be 13.5 ± 2.0 seconds with Mk40 motor and 13.5 ± 2.5 seconds with Mk 66 motor."

PAGE 5

* 3.14, 2 places: Delete "Gas Generator" and substitute "2 second delay".

* Delete "20 pounds is applied to the sear." and substitute "20 ± .50 pounds is applied to the pull wire."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

"3.14.1 Nonfunction Drop Test. The 2 second delay shall not function when subjected to a seven foot drop to a steel plate five times in a pipe fixture."

* 3.15, 2 places: Delete "Gas Generator" and substitute "2 second delay".

3.17: Delete "50 pounds minimum and 75 pounds maximum" and substitute, "40 pounds minimum and 65 pounds maximum".

3.18: Delete "16 g's plus or minus .5 g's" and substitute, "12 to 14 g's".

3.19: Delete "twenty-two (22) g's plus or minus .5 g's" and substitute, "20 to 22 g's".

PAGE 7

* 4.3.1: Delete "Gas Generator 9332277 30"
and substitute "2 Second Delay 9332277 50"

PAGE 11

Table I, Under "Gas Generator" Examination or Test: Add

"Nonfunction Drop Test 20 3.14.1 4.4.2.20".

* Delete "Gas Generator" and substitute "2 second delay".

PAGE 34

4.4.2.16: Delete Major 102 in its entirety.

PAGE 38

* 4.4.2.20: Delete "Gas Generator" and substitute "2 second delay".

Add Critical 2 as follows:

"2 Nonfunction Drop Test 10 --- 3.14.1 4.5.7".

PAGE 47

4.5.3.1: Delete "4.3.4" and substitute "4.4.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

PAGE 51

4.4.2.33: Delete Major 102 in its entirety.

PAGE 53

* 4.4.2.35, 2 places: Delete "Gas Generator" and substitute "2 second delay".

Delete Major 108 in its entirety.

PAGE 58

* 4.5.3: Delete "except that dummy 2.75 Inch Rocket Motors" and substitute "except that inert 2.75 Inch Rocket Motors".

* Delete "in accordance with Method 514.2-7 of MIL-STD-810C. Resonance testing does not apply." and substitute "in accordance with TECOM ITOP 1-2-601 (dtd. 1 Mar 88)."

PAGE 59

* 4.5.4: Delete "performed in accordance with Method 514.2,Category d.3, procedure IIc, Table 514.2-IVA and figures 514.2-4B, 4C, 5D, 4E, and 4F of MIL-STD-810C"
and substitute
"performed in accordance with the vibration schedule listed in para. 4.5.4 of MIL-W-63468(AR), Warhead, 2.75 Inch Rocket, H.E.: M261".

* In second paragraph: Delete "The sample warheads, assembled with dummy 2.75 Inch Rocket Motors, shall be loaded in a Government furnished launcher."
and substitute
"The sample warheads, assembled with inert MK40 2.75 Inch Rocket Motors, shall be loaded in a Government approved launcher (M200 or M261). When sample warheads are assembled with inert MK66 2.75 Inch Rocket Motors, they shall be loaded in a Government approved launcher (M261)."

PAGE 61

* 4.5.7, 5 places: Delete "Gas Generator" and substitute "2 second delay".

* Delete "20 pounds is applied to the sear." and substitute "20. $\pm$ .50 pounds on the pull wire."

* Delete "10 pounds on the sear." and substitute "10. $\pm$ .25 pounds on the pull wire.".

Delete "sear movement or gas generator function." and substitute "pull wire extraction or 2 second delay function."

Source: https://assist.dla.mil -- Downloaded: 20260-23T02:45Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

* "4.5.7.1 2 Second delay nonfunction drop test. For First Article, twenty (20) 2 second delays shall be subject to a drop test. Each 2 second delay shall be installed loosely into a 0.50 in. dia. x 6.00 in. long steel pipe and dropped (5) five times. The ends of the pipe shall be capped to prevent ejecting the 2 second delay during testing. The test fixture shall be dropped horizontal from a height of seven (7) feet min. to a steel plate. The First Article sample shall be rejected if one or more 2 second delay has functioned. For production, a sample of ten (10) 2 second delays from each production lot shall be subjected to the drop test. Each 2 second delay shall be dropped (5) five times in a manner as described above. If one or more 2 second delay has functioned, the production lot shall be rejected."

* 4.5.8, 4 places: Delete "Gas Generator" and substitute "2 second delay".

* Delete "$30^{o} \pm 2^{o}$" and substitute "$30^{o} - 2^{o}$".

PAGE 62

4.5.10: Delete "16 g's plus or minus .50 g's" and substitute "12 to 14 g's".

In last sentence: Delete "classed defective." and substitute "classed defective and removed from the lot."

4.5.11: Delete "22 g's plus or minus .50 g's" and substitute "20 to 22 g's".

In last sentence: Delete "classed defective." and substitute "classed defective and removed from the lot."

4.5.12, In last sentence: Delete "classed defective." and substitute "classed defective and removed from the lot."

4.5.13: Delete "A complete round left out of the conditioning cabinet/container over five minutes prior to firing shall be placed at ambient temperature for not less than eight hours and then reconditioned to the applicable temperature."

and substitute the following:

"A complete round left out of the conditioning cabinet/container over five minutes prior to firing shall be placed back in the conditioning cabinet/container for not less than twice the actual time it has been out of conditioning prior to launch."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

4.5.13, paragraph a: Delete the following:

"This time shall be 13.0 ± 2.0 seconds or 13.5 ± 2.0 seconds depending on the type of motor used. (see 3.4.1)."

and substitute the following:

"This time shall be 13.5 ± 2.0 seconds or 13.5 ± 2.5 seconds depending on the type of motor used. (see 3.4.1)."

The margins of this document are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A874)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.