INTERIM FEDERAL STANDARD

CORD, FLEXIBLE, AND WIRE, FIXTURE,

(ELECTRICAL 0- TO 600- VOLT SERVICE)

This Interim Federal Standard was developed by General Services Administration, Federal Supply Service, to reflect standard types and sizes of electrical flexible cord and fixture wire. It is recommended that Federal agencies use it in procurement and forward any recommendations for changes to the General Services Administration, Federal Supply Service, Standardization Division, Washington 25, D.C.

S1. Purpose and scope. The purpose of this standard is the establishment of a standard list for electrical flexible cord and fixture wire as required for ordinary maintenance and extension of circuits by Government maintenance activities. This standard will keep the varieties of such cord and wire which are to be procured and stocked to the minimum consistent with such requirements.

S2. Application. Purchases from commercial sources under Federal Specification J-C-580 of the issue in effect on date of invitation for bids, shall be limited to items which have characteristics conforming to the standard items specified herein. Existing Government stocks of items with other characteristics shall continue to be utilized until exhausted. In those cases where this Federal Standard eliminates supply items and the items so eliminated are under contract, if the contract cannot be negotiated or amended to conform to the standard items, the Federal Standard becomes mandatory at the contract expiration date.

S3. Standard characteristics and identification. The standard items with their applicable Federal Stock Numbers shall conform to the characteristics of Federal Specification J-C-580 listed below:

TYPE	VOLTS	AWG SIZE	NO. OF COND.	FSN
		Flexible Cord		
C	300	18	2	6145-188-3657/ (1)
C	300	16	2	6145-191-3297/ (1)
P	600	14	2	6145-191-3618
P-2	300	16	2	6145-191-3619
S	600	18	2	6145-191-3275
S	600	16	2	6145-188-3653

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:55Z
Check the source to verify that this is the current version before use.

FSC 6145

TYPE	VOLTS	AWG SIZE	NO. OF COND.	FSN
		Flexible Cord		
S	600	14	2	6145-299-6254
S	600	14	3	6145-643-3482
S	600	12	2	6145-351-3099
S	600	12	3	6145-162-7918
S	600	10	2	6145-195-0300
S	600	10	3	6145-188-3651
S	600	10	4	6145-191-3614
SO	600	18	2	6145-299-7023
SO	600	18	3	6145-299-6256
SO	600	16	3	6145-299-6257
SO	600	14	3	6145-299-6258
SJ	300	18	2	6145-244-8152
SJ	300	16	2	6145-244-8151
SP-2	300	18	2	6145-553-8823/(2)
SP-2	300	18	2	6145-557-7163/(3)
SP-2	300	16	2	6145-191-3588/(2)
HPD	300	16	2	6145-191-3613
HPD	300	16	3	6145-191-3611
HPD	300	14	2	6145-191-3612
HPD	300	14	3	6145-191-3610
SVT	300	18	3	6145-682-3445
		Fixture Wire		
RF-2	600	16	1	6145-234-8548/(2)
AF	300	16	1	6145-191-3048/(2)
AF	300	16	1	6145-635-4607/(3)

(1) Yellow and green braid
(2) Black jacket
(3) White jacket

S4. Changes. When a Federal agency considers that this standard does not provide for its essential needs, written request for changing or adding to the standard supported by adequate justification, shall be sent to the Administration. This justification shall explain wherein the standard does not provide for essential needs. The request shall be sent in duplicate to the General Services Administration, Federal Supply Service, Standardization Division, Washington 25, D.C. The Administration will determine the appropriate action to be taken and will notify the agency.

S5. Conflict with referenced specification. Where the requirements specified in this standard conflict with any requirements

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:55Z
Check the source to verify that this is the current version before use.

in a referenced specification, the requirements of the standard will apply. Nature of conflict between the standard and the referenced specification shall be submitted in duplicate to the General Services Administration, Federal Supply Service, Standardization Division, Washington 25, D.C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:55Z
Check the source to verify that this is the current revision before use.