FEDERAL STANDARD

LATH, SHEATHING, AND WALLBOARD, GYPSUM

Authority. This standard is issued pursuant to the Federal Property and Administrative Services Act of 1949, as amended, and its application to purchase of commodities referred to herein is mandatory on all Federal agencies.

S1. Purpose and scope. This standard establishes a list of gypsum lath, sheathing, and wallboard, believed necessary to achieve the highest practical degree of standardization.

The list of nonstandard FIIN's identifies items which will no longer be procured by GSA.

S2. Application. Purchases under Federal Specification SS-L-30 of the issue in effect on date of invitation for bids shall be limited to the standard items listed herein. Existing Government stocks of nonstandard items listed shall be issued until exhausted. In those cases where this Federal Standard eliminates supply items and the items so eliminated are under contract, if the contract cannot be negotiated or amended to conform to the standard items, the Federal Standard becomes mandatory at the contract expiration date.

S3. Standard items. The standard items with their applicable Federal Stock Numbers shall conform to the characteristics listed below:

Type I - Lath
Grade R - Regular core
Class 1 - Plain surface
Form b - Perforated
Style 1 or 5 - Square or round edge

Size (inches)	Federal Stock Number
3/8 thick, 16 wide, 48 long	5640-248-1918

Type II - Sheathing
Grade R - Regular core
Class 2 - Water repellent surface
Form a - Uninsulated
Style 1 or 2 - Square or V-tongue and groove edges

Size (inches)	Federal Stock Number
1/2 thick, 24 wide, 96 long	5640-235-0309

Type III - Wallboard
Grade R - Regular core
Class 1 - Plain surface
Form a - Uninsulated
All type III wallboards are 48 inches wide
Style 1 - Square edged

Size (inches) Thickness	Length	Federal Stock Number
3/8	96	5640-235-0283
1/2	96	5640-235-0297

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:55Z
Check the source to verify that this is the current version before use.

Style 3 - Taper or recessed edges

Size (inches) Thickness	Length	Federal Stock Number
3/8	96	5640-235-0276
3/8	120	5640-527-8290
3/8	144	5640-527-8337
1/2	96	5640-235-0255
1/2	120	5640-527-8336
1/2	144	5640-527-8292

Type III - Wallboard
Grade X - Fire retardant core
Class 1 - Plain surface
Form a - Uninsulated
Style 3 - Taper or recess edges

Size (inches)	Federal Stock Number
5/8 thick, 48 wide, 96 long	5640-847-0235

S4. Changes. When a Federal agency considers that this standard does not provide for its essential needs, written request for changing or adding to the standard, supported by adequate justification, shall be sent to the Administration. This justification shall explain wherein the standard does not provide for essential needs. The request shall be sent in duplicate to the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C., 20406.

S5. Conflict with referenced specifications. Where the requirements stated in this standard conflict with any requirement in a referenced specification, the requirements of the standard shall apply. Nature of conflict between the standard and the referenced specification shall be submitted in duplicate to the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C., 20406.

S6. Nonstandard items. The nonstandard items are listed as follows:

Lath, Sheathing, and Wallboard, Gypsum FSC 5640

FIIN Sequence	Recommended replacement FIIN
223-5109	None
223-5110	"
235-0247	235-0276
235-0277	None
235-0278	527-9290
235-0280	527-8337
235-0284	None
235-0285	527-8290
235-0287	527-8337
235-0290	235-0255
235-0292	527-8290
235-0294	527-8292
235-0299	527-8336
240-0888	None
260-0569	"
270-1432	"
270-1433	"
270-1434	"
270-1435	"
527-8280	"
527-8281	"
527-8282	"
527-8283	"
527-8284	"
527-8285	"
527-8286	"
527-8287	"
527-8288	235-0276
527-8289	None
527-8291	"
527-8293	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:55Z
Check the source to verify that this is the current version before use.

Lath, Sheathing, and Wallboard, Gypsum FSC 5640 (continued)

FIIN Sequence	Recommended replacement FIIN
527-8294	None
527-8295	"
527-8296	"
527-8297	"
527-8298	"
527-8299	"
527-8300	"
527-8301	"
527-8302	"
527-8303	"
527-8304	"
527-8305	"
527-8306	"
527-8307	"
527-8308	"
527-8309	"
527-8320	"
527-8321	"
527-8322	"
527-8323	"
527-8324	"
527-8325	"
527-8326	"
527-8327	"
527-8328	"
527-8329	"
527-8330	"
527-8331	"
527-8332	"
527-8333	None
527-8334	235-0255
527-8335	None
527-8338	"
527-8339	"
527-8340	"
527-8341	"
527-8342	"
527-8343	"
527-8344	"
527-8345	"
527-8346	"
527-8347	"
738-0653	"
738-0654	"
825-6559	"
979-3292	None
988-7706	"
988-7707	847-0235
988-7708	None
988-7709	"

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:55Z
Check the source to verify that this is the current version before use.

S7. Notes. Using a knife, wallboard may be scored on both sides penetrating into the gypsum. With care, the wallboard may be broken where scored with no appreciable loss of material. This recommendation is intended for possible small quantity replacement repairs.

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. Single copies of this standard are available without charge at the GSA Business Service Centers in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Forth Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash. Additional copies may be purchased for 5 cents each from the General Services Administration, Specifications Activity, Printed Materials Supply Division, Building 197, Naval Weapons Plant, Washington, D. C., 20407.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:55Z
Check the source to verify that this is the current version before use.