PPP-B-1122
October 31, 1968
SUPERSEDING
MIL-B-43426
28 April 1966

FEDERAL SPECIFICATION

BALANCES, SCALES, AND ACCESSORIES, PACKAGING AND PACKING OF

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers optional detailed requirements or performance requirements for preservation, packaging, packing and marking of balances, scales, and accessories, except as specified in 6.1.

1.2 Classification.

1.2.1 Options (see 3.3.1, 3.4.1 and 3.4.2).

Option I - Detailed requirements.
Option II - Performance requirements.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-378	-	Plastic Sheet and Strip (Polyolefin).
QQ-S-781	-	Steel, Strapping, Flat.
UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
UU-P-553	-	Paper, Wrapping, Tissue.
UU-T-81	-	Tags, Shipping and Stock.
PPP-B-26	-	Bag, Plastic, Polyethylene.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-585	-	Boxes, Wood, Wirebound.
PPP-B-591	-	Boxes, Fiberboard, Wood-Cleated.

FSC PACK
FSC 6670

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-665	-	Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676	-	Boxes, Setup.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-291	-	Paperboard, Wrapping, and Cushioning.
PPP-P-600	-	Porcelain Enamel Products and Household Appliances, Electrical and Mechanical - Requirements for Packaging and Packing.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative montly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, Seattle, Wash.)

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation, Methods of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.
MIL-B-43291 - Boxes: Fiberboard; Corrugated, Double-Wall, Weather Resistant.

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized and Containerized Unit Loads 40" X 48" Pallets, Skids, Runners, or Pallet Type Base.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials used for cleaning, preservation, packaging, packing and marking shall conform to the applicable specifications as specified herein.

3.2 Disassembly and matchmarking.

3.2.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of parts susceptible to damage during shipment and storage, and for the reduction in cubage. Attaching hardware shall be replaced on one of the mating parts or placed in a cloth drawstring bag, and the bag attached to one of the mating parts. Disassembly shall not be such that special skills or special tools are required to place the equipment into operation.

3.2.2 Matchmarking. When in the opinion of the manufacturer, detached parts and accessories may cause difficulty in reassembly, they shall be matchmarked. Matchmarking information shall be on shipping tags conforming to type B, class 2 of UU-T-81, and attached to mating parts.

3.3 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

3.3.1 Level A. Scales, with a combined gross weight (complete scale and shipping container) not exceeding 500 pounds, and balances shall be preserved and packaged in accordance with either option I or II at the discretion of the supplier. Scales with a combined gross weight exceeding 500 pounds shall be preserved and packaged in accordance with option I.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.1 Option I, detailed requirements, (see 3.3.1 and 6.1).

3.3.1.1.1 Cleaning. Critical functioning or close tolerance surfaces of each balance, scale and accessory requiring a contact preservative in accordance with the preservative application criteria of MIL-P-116 shall be cleaned by process C-5. All other surfaces requiring a contact preservative shall be cleaned by process C-1.

3.3.1.1.2 Drying. Surfaces, cleaned by process C-5, shall be dried by procedure D-1 or D-3 of MIL-P-116. Surfaces, cleaned by process C-1, shall be dried by any of the procedures specified in MIL-P-116.

3.3.1.1.3 Preservation.

a. Electrically or electronically operated scales and accessories shall be individually preserved method II-b of MIL-P-116 without the use of contact preservatives. Boxes used shall conform to style RSC, type CF, class domestic, variety optional, grade 275 of PPP-B-636.

b. All other balances, scales and accessories shall be preserved method I of MIL-P-116. Surfaces cleaned and dried as specified in 3.3.1.1.1 and 3.3.1.1.2 shall be coated with an appropriate preservative selected from the list of preservative compounds specified in MIL-P-116.

3.3.1.1.4 Packaging (balances).

3.3.1.1.4.1 Knife edges and bearings. Knife edges and bearings shall be protected against physical and mechanical damage in the following manner as applicable:

a. Bearings and knife edges shall be separated by means of an arresting mechanism which can be locked in position to assure that bearings and knife edges do not come in contact during shipment.

b. Use of aluminum shims, cushioning or wood blocking, as applicable.

c. Disassembly of knife edges or bearings, or both. When knife edges or bearings, or both, are removed, they shall be packaged as specified in 3.3.1.1.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.1.4.2 Disassembled components. Disassembled components of knockdown type balances shall be stowed within the area provided by the manufacturer or shall be packaged in one or more snug-fitting boxes conforming to PPP-B-566, PPP-B-676 or PPP-B-636, style, type, class, variety and grade optional. Components, such as, but not limited to, beams, bows, columns, pans, plates or scoops, having highly finished surfaces, shall be individually wrapped in neutral tissue conforming to type II, class 2 of UU-P-553, and the wrap secured with tape or individually placed in a polyethylene bag conforming to type I or II of PPP-B-26. The film shall be minimum 0.001-inch thick conforming to type II, grade A, B, or C, finish 1 of L-P-378. All seams and closures shall be accomplished by heat sealing. Prior to or during heat sealing closure operation, excess air within the bag shall be expelled. Prior to packaging, components shall be cushioned with material conforming to type II, class A of PPP-C-843, or type I, style 1 or 2 of PPP-P-291, as required to prevent movement or damage during shipment. Each box when used shall be closed in accordance with the appendix of the applicable specification.

3.3.1.1.4.3 Removable balance beam riders. Removable balance beam riders shall be packaged in accordance with method III of MIL-P-116 in a metal or plastic container.

3.3.1.1.4.4 Hydraulic dampening devices. Hydraulic dampening devices shall be prepared for shipment in accordance with the manufacturer's recommendations. When the removal of fluid is required, the needed volume of fluid for each balance shall be filled into a leakproof container having a removable top for pouring purposes. Each fluid container shall be packaged in a snug-fitting paperboard or fiberboard box as specified in 3.3.1.1.4.2. Each glass fluid container shall be completely wrapped in minimum 1-inch thick cushioning material conforming to type I, class B of PPP-C-843 prior to placing in the box. Closure shall be in accordance with the box specification.

3.3.1.1.4.5 Weight sets. Components of each weight set shall be stowed in their respective places within the drawer, weight case or weight block as applicable. A fiberboard or paperboard pad, or cushioning material conforming to type II, class A of PPP-C-843 shall be used as required to immobilize the contents during shipment. Cases or blocks with covers shall have the covers closed and secured by means provided thereon. Weight blocks without covers shall be placed in paperboard boxes as specified in 3.3.1.1.4.2 and the contents immobilized as specified herein. Finished surfaces of each weight case or block shall be protected against abrasion by completely wrapping in machine-glazed or highly-calendered kraft paper or waxed paper having a minimum basis weight of 30 pounds per ream (24 by 36-500) and the wrap secured with tape.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.1.4.6 Technical publications. Technical publications, when furnished, shall be packaged in accordance with method IC-1 of MIL-P-116 and attached to the balance.

3.3.1.1.4.7 Balances complete. Movable components of each balance shall be secured in a fixed position in a manner as to prevent movement or damage during shipment or storage. Each balance together with detached components and accessories, preserved and packaged as specified herein, shall be further packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, class domestic, variety DW, grade 275 of PPP-B-636. Detached components and accessories shall be positioned in the box away from glass panels. Contents of each fiberboard box shall be cushioned, blocked, and braced as required to prevent movement or damage during shipment. Cushioning, blocking and bracing shall be accomplished by means of pads and forms made from fiberboard conforming to type CF, class domestic, variety SW or DW, grade 275 of PPP-F-320; or cushioning material conforming to type II, class A of PPP-C-843; or type I or II, style 1 or 2 of PPP-P-291. Finished surfaces of each balance case shall be protected against abrasion as specified in 3.3.1.1.4.5, or covered with the plastic dust cover when one is furnished. Closure shall be in accordance with the appendix of the box specification.

3.3.1.1.5 Packaging (scales).

3.3.1.1.5.1 Knife edges and bearings. Knife edges and bearings of all scales, except scale, person-weighing, dial indicating ("bathroom" type) and those in the under structure of scale, person-weighing, beam indicating, shall be protected against physical and mechanical damage as specified in 3.3.1.1.4.1.

3.3.1.1.5.2 Detached subassemblies. Detached subassemblies, such as beam assemblies, column assemblies and platform assemblies, shall be individually packaged in a snug-fitting fiberboard box conforming to style optional, type CF, variety optional, class domestic of PPP-B-636. Securing of movable components, cushioning, blocking, bracing, and box closure shall be as specified in 3.3.1.1.4.7.

3.3.1.1.5.3 Detached components. Detached components of scales furnished with carrying cases shall be stowed in their respective places within the case. Detached components of all other type scales shall be packaged as specified in 3.4.1.1.4.2, as applicable, except that load receivers, scoops, or plates may be packaged unboxed with the scale when reduction of cubage is achieved without any sacrifice of physical protection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.1.5.4 Counterpoise weights. Counterpoise weights for each complete scale shall be packaged in a snug-fitting paperboard or fiberboard box conforming to any type, class, or style of PPP-B-566 or PPP-B-676, or style optional, type CF or SF, class domestic, variety optional, of PPP-B-636. Weight of contents of each box shall not exceed the weight limits of the applicable box specification. Closure shall be in accordance with the appendix of the applicable box specification.

3.3.1.1.5.5 Mounting accessories and stands. Mounting accessories and stands shall be individually packaged in a snug-fitting fiberboard box as specified in 3.3.1.1.5.4. Cushioning, blocking and bracing shall be as specified in 3.3.1.1.4.7. Painted surfaces shall be covered or wrapped in minimum 40-pound kraft paper conforming to grade B of UU-P-268 to prevent abrasion. Closure shall be in accordance with the appendix of the box specification.

3.3.1.1.5.6 Commodity indicator keys and commodity racks. Commodity indicator keys as required for each prepackaged food scale system shall be packaged in a snug-fitting metal-stayed paperboard box or fiberboard box conforming to style A of PPP-B-665 or style RSC, type CF or SF, class domestic, variety optional of PPP-B-636, respectively. Each commodity rack, together with the packaged commodity indicator keys, shall then be packaged in a snug-fitting fiberboard box as specified herein.

3.3.1.1.5.7 Hydraulic dampening devices. Hydraulic dampening devices shall be prepared for shipment as specified in 3.3.1.1.4.4.

3.3.1.1.5.8 Scales complete with components and accessories. Movable components of each scale shall be secured in a fixed position in a manner as to prevent movement or damage during shipment. Except as specified herein, each scale complete with detached components and accessories, not exceeding 120 pounds, shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, class domestic, variety DW of PPP-B-636. Scales, which are disassembled into subassemblies, and are packaged as specified in 3.3.1.1.5.2, shall not require further packaging as specified herein. Contents of each box shall be blocked, braced, cushioned and protected against abrasion as specified in 3.3.1.1.4.7. Closure shall be in accordance with the appendix of the box specification.

3.3.1.2 Option II, performance requirements, (see 3.3.1).

3.3.1.2.1 Preservation. Preservation shall be as specified in 3.3.1.1 through 3.3.1.1.3, except that electrically-operated scales and accessories shall be preserved method II, submethod optional of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.2.2 Packaging. Knife edges and bearings shall be protected as specified in 3.3.1.1.4.1 and 3.3.1.1.5.1, as applicable. Disassembled components, detached components, devices, and accessories shall be packaged as specified in 3.3.1.1.4 or 3.3.1.1.5, as applicable or in a manner to prevent movement or damage to the component or unit during shipment and handling. As a minimum there shall be no evidence of damage to these components when the complete balance or scale is packed and tested for the applicable level of pack in PPP-P-600.

3.3.2 Level C. Balances, scales and accessories shall be preserved and packaged to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the first receiving activity or for controlled humidity storage. The supplier may use his standard practice when it meets these requirements.

3.4 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

3.4.1 Level A. Scales, with a combined gross weight (complete scale and shipping container) not exceeding 500 pounds, and balances shall be packed either option I or II, at the discretion of the supplier. Scales with a combined gross weight exceeding 500 pounds shall be packed option I.

3.4.1.1 Option I, detailed requirements, (see 3.4.1 and 6.1).

3.4.1.1.1 Balances with glass case enclosures having glass windows or doors. Each balance with a glass case enclosure having glass windows or doors, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall unless otherwise specified (see 3.4.1.1.1.1) be packed in a shipping container conforming to overseas type, style A, B or J of PPP-B-601 or class 2, style 2 or 4 of PPP-B-621. The contents shall be cushioned by lining all 6 inner surfaces of each shipping container with a minimum of 3-inch thick cushioning material conforming to type II, class A of PPP-C-843. Each shipping container shall be provided with a type I or II, grade B or C case liner conforming to MIL-L-10547. The liner shall be placed between the cushioning material and the inner surfaces of the shipping container. Each shipping container shall be closed and strapped in accordance with the applicable appendix of PPP-B-601 or PPP-B-621.

3.4.1.1.1.1 When specified (see 6.2), balances with glass enclosures having glass windows or doors, preserved and packaged as specified in 3.3.1.1 or 3.3.2 shall be packed in a fiberboard shipping container conforming to class 2, grade A, style optional of PPP-B-640. Each fiberboard container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-640.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.1.1.2 Balances (except as specified in 3.4.1.1.1). Balances, except as specified in 3.4.1.1.1 or 3.4.1.1.1.1, preserved and packaged as specified in 3.3.1.1, or 3.3.2, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V3s, V4s or V2s of PPP-B-636. Weight of contents of each V3s or V4s shipping container shall not exceed 40 pounds and V2s 70 pounds. Each shipping container shall be closed, waterproofed by means of tape and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636.

3.4.1.1.3 Beam indicating portable platform type scales. Each beam indicating portable platform type scale, disassembled, preserved and packaged as specified in 3.2, 3.3.1.1 or 3.3.2, shall be packed in a shipping container conforming to overseas type, style A, B, or J of PPP-B-601, class 2, style 2 or 4 of PPP-B-621, class 3 use, type 3 load of PPP-B-585 or type I, IV, or V, style A of PPP-C-650. Scales not disassembled or knocked down and having a net weight not exceeding 250 pounds shall be packed in a type I, style A crate and those exceeding 250 pounds shall be packed in a type IV or V, style A crate conforming to PPP-C-650. Each shipping container having a gross weight of over 250 pounds shall be provided with skids as specified in the applicable specification. The contents of each shipping container shall be blocked, braced and cushioned in accordance with MIL-STD-1186. When wheels are not removed from the scale, a minimum of 1-inch clearance shall be provided between the interior base of the shipping container and the wheels of the scale. Boxes containing counterpoise weights of disassembled parts shall be secured in an unused portion of the shipping container. The contents of each shipping container provided with skids shall be waterproofed by means of a full height shroud in accordance with MIL-STD-1186. The contents of all other shipping containers shall be provided with a case liner unless the disassembled components are packaged in water-resistant fiberboard containers in accordance with PPP-B-636 and waterproofed with tape as specified therein. The sealed case liner shall conform to MIL-L-10547. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable specification.

3.4.1.1.4 Folding type portable scales. Each folding type portable scale enclosed within its own carrying case, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be protected by a solid fiberboard cap tray extending down the sides to not less than 1/2 inch from the bottom of the scale. The flaps of each end shall be folded under the sides and secured by steel staples or steel stitching wire (not less than 5 per corner).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

The staples or stitching wire shall be not less than 0.093-inch thick or equivalent cross section formed into staples approximately 7/16 inch wide. Staples or wire shall have a commercially applied coating or plating, such as galvanized (zinc coated), or copper wash. The cap tray shall be fabricated in such a manner as to insure a snug fit on the scale case and be made of fiberboard conforming to type SF, class weather-resistant, grade W5s of PPP-F-320. The fiberboard cap tray shall be secured to the scale with two steel straps, minimum 1/2 inch by 0.020 inch, conforming to type I, class A of QQ-S-781.

3.4.1.1.5 Scales not exceeding 65 pounds. Scales together with accessories and parts not exceeding 65 pounds, preserved and packaged as specified in 3.3.1.1 and 3.3.2, shall be packed as specified in 3.4.1.1.2.

3.4.1.1.6 Scales not exceeding 120 pounds. Each scale together with accessories and parts not exceeding 120 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall, unless otherwise specified (see 3.4.1.1.6.1), be packed in a snug-fitting shipping container conforming to overseas type, style A, B, or J of PPP-B-601 or class 2, style 2 or 4 of PPP-B-621. Each shipping container shall be provided with a type I or II, grade B or C case liner conforming to MIL-L-10547. Each shipping container shall be closed and strapped in accordance with the applicable appendix of PPP-B-601 or PPP-B-621.

3.4.1.1.6.1 When specified (see 6.2), scales not exceeding 120 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2 shall be packed in a snug-fitting shipping container conforming to type CF, class weather resistant, variety DW, grade V11c, style RSC of MIL-B-43291; class 2, style optional of PPP-B-640 or class II, style A or B of PPP-B-591. Each cleated fiberboard container shall be provided with a case liner as specified in 3.4.1.1.6 and each fiberboard container shall be closed and waterproofed by means of tape in accordance with the appendix of PPP-B-640. All shipping containers shall be reinforced in accordance with the appendix of the applicable container specification.

3.4.1.1.7 Scales not exceeding 800 pounds (except as specified in 3.4.1.1.3 and 3.4.1.1.4). Each scale (except as specified in 3.4.1.1.3 and 3.4.1.1.4), together with accessories and parts not exceeding 800 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed in a wood-cleated plywood or nailed wood shipping container conforming to overseas type style A, B, or J of PPP-B-601 or class 2, style 2, 4 or 7 of PPP-B-621. Shipping containers exceeding 250 pounds gross weight shall be provided with skids in accordance with the appendix of the applicable container specification. The contents shall be secured within each

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

container by means of cushioning, blocking, and bracing in accordance with MIL-STD-1186. Scales with wheels attached shall be blocked to provide a minimum of 1-inch clearance between the interior base of the container and the wheels. The contents of shipping containers conforming to PPP-B-621 or PPP-B-601 shall be provided with a full height shroud as specified in MIL-STD-1186. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

3.4.1.1.8 Scales exceeding 800 pounds. Each scale, together with accessories and parts exceeding 800 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104. Contents shall be secured as specified in 3.4.1.1.7.

3.4.1.2 Option II, performance requirements, (see 3.3.1). Balances, scales and accessories, preserved and packaged as specified in 3.3.1.2 or 3.3.2, shall be packed in accordance with the level A requirements of PPP-P-600. The packed units shall meet the level A performance requirements as specified therein.

3.4.2 Level B. Scales with a combined gross weight (complete scale and shipping container) not exceeding 500 pounds and balances shall be packed either option I or II, at the discretion of the supplier. Scales with a combined gross weight exceeding 500 pounds shall be packed with option I.

3.4.2.1 Option I, detailed requirements, (see 3.4.2).

3.4.2.1.1 Balances with glass case or enclosures having glass windows or doors. Each balance with a glass case or enclosure having glass windows or doors, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed as specified in 3.4.1.1.1, except that the shipping containers shall be domestic type or class, and waterproofing shall not be required, or multiples of each balance shall be packed in a snug-fitting container conforming to style RSC, type CF, class domestic, variety DW, grade 350 of PPP-B-636. The weight of contents for grade 350 containers shall not be exceeded. When specified (see 6.2), fiberboard shipping containers shall be style RSC, V3c of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.2.1.2 Balances (except as specified in 3.4.2.1.1). Balances (except as specified in 3.4.2.1.1), preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, class domestic, variety optional of PPP-B-636. Weight of contents of each shipping container shall not exceed the limitations for the applicable grade. Closure shall be in accordance with the appendix of the container specification. When specified (see 6.2), the fiberboard shipping container shall be style RSC, V3c of PPP-B-636.

3.4.2.1.3 Beam indicating, portable platform, floor type scales. Each beam indicating, portable platform, floor type scale, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed as specified in 3.4.1.1.3, except that waterproofing shall be required only for open crates conforming to PPP-C-650 and may be accomplished by the use of nominal 0.004-inch thick plastic film in lieu of the material specified. All seams in the plastic shroud shall be heat sealed.

3.4.2.1.4 Folding type portable scales. Each folding type portable scale, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be protected by a solid fiberboard cap tray as specified in 3.4.1.1.4.

3.4.2.1.5 Scales not exceeding 65 pounds. Scales together with accessories and parts not exceeding 65 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed as specified in 3.4.2.1.2.

3.4.2.1.6 Scales not exceeding 120 pounds. Each scale, together with accessories and parts not exceeding 120 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF or SF, or class domestic, variety optional, applicable grade of PPP-B-636, or class 1, grade A, style optional of PPP-B-640, class I, style A or B of PPP-B-591, or class 1, style 2 or 4 of PPP-B-621. Closure shall be in accordance with the appendix of the applicable container specification. When specified (see 6.2), containers conforming to PPP-B-636 and PPP-B-640 shall be fabricated from weather-resistant material, or shipping container shall conform to V13c of MIL-B-43291.

3.4.2.1.7 Scales not exceeding 800 pounds (except as specified in 3.4.2.1.3 and 3.4.2.1.4). Each scale (except as specified in 3.4.2.1.3 and 3.4.2.1.4), together with accessories and parts not exceeding 800 pounds, preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed as specified in 3.4.1.1.7, except that shipping containers shall be domestic type and class, and waterproofing of contents or lining of interior surfaces of shipping containers with waterproof barrier material shall not be required.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.2.1.8 Scales exceeding 800 pounds (except as specified in 3.4.2.1.3 and 3.4.2.1.4). Each scale together with accessories and parts exceeding 800 pounds (except as specified in 3.4.2.1.3 and 3.4.2.1.4), preserved and packaged as specified in 3.3.1.1 or 3.3.2, shall be packed as specified in 3.4.1.1.8, except that waterproof barrier material shall not be required.

3.4.2.2 Option II, performance requirements, (see 3.4.2). Balances, scales and accessories, preserved and packaged as specified in 3.3.1.2 or 3.3.2, shall be packed in accordance with the level B requirements of PPP-P-600. The packed units shall meet the level B performance requirements as specified therein.

3.4.3 Level C. Balances, scales and accessories, preserved and packaged as specified in 3.3, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

3.5 Marking.

3.5.1 Civilian agencies. Interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

3.5.2 Military requirements.

3.5.2.1 Interior packages. Interior packages shall be marked in accordance with MIL-STD-129. Component parts that have been overwrapped and secured in their respective locations will not require marking.

3.5.2.2 Shipping containers. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

3.5.2.2.1 Special handling marking. Special handling marking requirements in MIL-STD-129, applicable to fragile items, such as "arrows", the words "UP", "THIS SIDE UP", and "CENTER OF BALANCE" shall apply.

3.6 Palletization and unitization. When specified (see 6.2) balances and scales packed as specified herein shall be palletized or containerized in accordance with MIL-STD-147.

3.7 Workmanship. Preservation, packaging, packing and marking shall conform to the quality and grade of product established by this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to test such items to determine the validity of certification.

4.2 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3 Inspection of the end item.

4.3.1 Examination of the end item. Each unit shall be examined for defects as listed below. Presence of one or more defects shall be cause for rejection of the unit presented.

TABLE I. Examination of end item

Examine	Defect
Disassembly	Detachable parts and accessories not removed to prevent damage. Attaching hardware not replaced on mating parts or in cloth bag. Cloth bag with attaching hardware not attached to mating part.
Matchmarking	Tags with information not attached to mating parts (when required).

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the currentversion before use.

TABLE I. Examination of end item (cont'd)

Examine	Defect
Option I	
Packaging (balances and scales as applicable)	
Knife edges and bearings	Not protected and immobilized by method specified (see 3.3.1.1.4.1).
Disassembled components	Not wrapped and taped as specified. Not stowed and secured in area specified or packaged as specified. Seams and closures of bag not heat sealed. Film less than 0.001-inch thick. Excess air in bag. Cushioning not adequate to prevent movement or damage during shipment.
Removable balance beam riders	Not packaged in metal or plastic container as specified.
Hydraulic dampening devices	Fluid not removed when specified. Container for fluid leaks. Less than required volume of fluid in container. Glass fluid container not cushioned with 1-inch minimum thickness of cushioning material.
Weight sets (including counterpoise weights as applicable)	Not stowed in respective places as specified. Pad or cushioning material missing. Not sufficient padding to immobilize contents. Covers when furnished not closed and secured. Finished surfaces not protected with nonabrasive paper. Paper wrap not secured with tape. Weight blocks without covers not placed in paperboard boxes specified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Examination of end item (cont'd)

Examine	Defect
Option I (cont'd)	
Technical publications	Not attached to balance. Missing when specified.
Balances and scales	Movable components not secured in fixed positions. Not overpacked with components and accessories. Detached components and accessories packed adjacent to glass panels. Insufficient cushioning, blocking and bracing to prevent damage. Finished surfaces not protected as specified (see 3.3.1.1.4.5).
Mounting accessories and stands	Not in individual boxes. Painted surfaces not covered to prevent abrasion.
Commodity indicator keys and racks	Box not snug-fitting. Racks packed separate from keys.
Packing	
Balances and scales	Container not type specified. Less than 3 inches of cushioning on all inner surfaces when specified. Case liner missing when specified. Case liner not placed between cushioning and inner surfaces of container. Weight of contents exceeds 40 pounds when packed in V3s or V4s containers and 70 pounds in V2s containers. Less than 1-inch clearance between base of container and wheels on scales. Shroud not full height. Shroud missing when specified. Plastic shroud film less than 0.004 inch. Seams in plastic shroud not heat sealed. Cap tray less than 1/2 inch from bottom of scales. Flaps of ends folded on outside of sides. Staples or stitching not size or material specified. Less than 5 fasteners per corner on cap tray. Cap tray secured with less than two straps. Skids not provided when specified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Examination of end item (cont'd)

Examine	Defect
Marking	Omitted, incomplete, incorrect; illegible, of improper size, location, sequence or method of application.

4.3.2 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, PPP-B-621, PPP-B-636, PPP-B-640, PPP-B-591, PPP-B-650, and MIL-B-43291 examination for closure and strapping shall be in accordance with the applicable appendix of those specifications.

4.3.3 Examination of palletization or containerization. Each pallet load or containerized load shall be examined to assure that components, materials, and procedures conform to MIL-STD-147. The presence of one or more deviations from the requirements of MIL-STD-147 shall be cause for rejection of the unit load presented.

5. PREPARATION FOR DELIVERY

(Not applicable).

6. NOTES

6.1 Intended use. The preservation, packaging, packing and marking requirements of this specification are intended for the preparation of delivery of balances and scales, except as specified herein, and accessories in accordance with either of two options (see 3.3.1, 3.4.1 and 3.4.2). The requirements of this specification are not intended to be used for the following type scales:

(a) Scales requiring permanently installed foundations within the structure of a building.
(b) Railroad weighing scales.
(c) Motor truck weighing scales.
(d) Aircraft weighing scales.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of preservation, packaging and packing (see 3.3 and 3.4).
(c) When balances and scales should be packed in fiberboard or cleated fiberboard containers (see 3.4.1.1.1.1 or 3.4.1.1.6.1).
(d) Whether weather-resistant fiberboard containers are required (see 3.4.2.1.1, 3.4.2.1.2, and 3.4.2.1.6).
(e) When palletization or containerization is required (see 3.6).

6.3 Level C packing. Level C packing should be specified only for direct domestic shipment from the supply source to the first receiving activity for immediate use.

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 82

Preparing activity:

Army - GL

Review activities:

Army - SM
Navy - YD
Air Force - 82

User activities:

Army - MD, ME
Navy - MC, SH

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION
PPP-B-1122; Balances, Scales, and Accessories, Packaging and Packing Of

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.