PPP-B-1980
November 18, 1977
SUPERSEDING
MIL-B-40640A
12 July 1967

FEDERAL SPECIFICATION

BOARDS; BULLETIN AND CONTROL; PACKAGING AND PACKING OF

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the packaging, packing, and marking for shipment of bulletin and control boards.

1.2 Classification. For packaging and packing, bulletin boards shall be classified as follows:

Type I - Wall.
Type II - Portable, with stand.
Class 1 - Open face.
Class 2 - Glass front, with lock and key.
Style 1 - With illumination.
Style 2 - Without illumination.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin.
UU-P-268	-	Paper, Kraft, Wrapping.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated Triple-Wall

FSC 7195 (for DoD only)
FSC PACK

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:52Z
Check the source to verify that this is the current version before use.

PPP-C-843 - Cushioning Material, Cellulosic.
PPP-E-911 - Excelsior, Wood, Fabricated Pads and Bulk Form.
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.
PPP-T-60 - Tape: Packaging, Waterproof.

Federal Standard:

FED-STD-123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:52Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

3.1.1 Level A.

3.1.1.1 Stands. The stand for type II bulletin boards shall be removed. Removed bolts, nuts, spacers and washers shall be placed in mating parts and secured to prevent loss. Each strand shall then be wrapped in minimum 30-pound (24 x 36 - 500) basis weight kraft paper conforming to type I, grade B of UU-P-268 and secured with not less than 2 inch wide tape conforming to type III, grade A of PPP-T-45.

3.1.1.2 Style 1 boards. The fluorescent tube or light bulbs and the coiled electrical cable shall be secured in place with tape conforming to type III, class 2 of PPP-T-60. The width of the tape shall be not less than 3/4 inch.

3.1.1.3 Posting boards. Each bulletin board containing a posting board shall have the board cushioned as specified in 3.1.1.5 and secured in place to prevent movement or damage during transit or storage. The slide cover of the letterbox containing large and small letter plates shall be secured in closed position with not less than 2-inch wide tape conforming to type III, grade A of PPP-T-45.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:52Z
Check the source to verify that this is the current version before use.

3.1.1.4 Class 1 boards. Class 1 bulletin boards shall be wrapped in minimum 30-pound (24 x 36 - 500) basis weight kraft paper conforming to type I, grade B of UU-P-268 or minimum 0.0015 inch thick polyethylene film conforming to type I, class 1, grade C, finish 1 of L-P-378, applied to prevent marring or abrasive action to the finished surfaces of the bulletin board. Kraft paper wraps shall be secured with not less than 2-inch wide tape conforming to type III, grade A of PPP-T-45. Polyethylene film wraps shall be secured with not less than 3/4-inch wide tape conforming to type III, class 2 of PPP-T-60.

3.1.1.5 Class 2 boards. Class 2 bulletin boards shall have the door locked, the keys placed in a cotton cloth drawstring bag and the bag fastened to the back of the bulletin board. Each bulletin board shall then be wrapped with kraft paper or polyethylene film specified in 3.1.1.4 and then wrapped with an excelsior pad conforming to type II weight number optional of PPP-E-911, or a pad conforming to type II, class A of PPP-C-843 to fully protect the glass surface from shock. The thickness of the pad shall be not less than 1/2 inch. The outer wrap shall be secured by not less than 3/4-inch wide tape conforming to type III, class 2 of PPP-T-60.

3.1.2 Level C. Bulletin boards shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity.

3.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

3.2.1 Level A. Each bulletin board and bulletin board stand, packaged as specified in 3.1, shall be packed in a shipping container conforming to style FOL, grade V2s of PPP-B-636, or overseas type of PPP-B-601, or class 2, style 2 or 4 of PPP-B-621. The letter box and the stand, when applicable, shall be packed in a void within the shipping container away from the glass of the class 2 bulletin boards. The contents of each shipping container, including the letter box and stand, when applicable, shall be cushioned, blocked and braced in accordance with MIL-STD-1186. Style 1 bulletin boards shall be placed within the shipping container in such a manner as to prevent damage to the coiled electrical cable during transit or storage. Each fiberboard shipping container shall be closed in accordance with method III, waterproofed in accordance with method V as specified in the appendix of PPP-B-636. Cleated plywood and nailed wood shipping containers shall be provided with a type I or II, grade C sealed case liner conforming to MIL-L-10547. Each shipping container shall be closed and reinforced with flat strapping or tape banding in accordance with the appendix of the applicable container specification. The weight of contents shall not exceed 65 pounds for V2s containers.

3.2.2 Level B. Each bulletin board and bulletin board with stand, packaged as specified in 3.1, shall be packed in a shipping container conforming to style FOL, type CF, variety SW or DW, or type SF, class

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:52Z
Check the source to verify that this is the current version before use.

domestic of PPP-B-636, or domestic type, style A or B of PPP-B-601, or class 1, style 2 or 4 of PPP-B-621 or class 1 of PPP-B-640. The letter box and the stand, when applicable, shall be packed in a void within the shipping container, away from the glass of class 2 bulletin boards. The contents of each shipping container, including the letter box and stand, when applicable, shall be cushioned, blocked and braced in accordance with MIL-STD-1186. Style 1 bulletin boards shall be placed within the shipping container in such a manner as to prevent damage to the coiled electrical cable during transit or storage. Each fiberboard shipping container shall be closed in accordance with method II of the appendix of PPP-B-636 or PPP-B-640, as applicable. The weight of contents and dimensional requirements for the grade of fiberboard of PPP-B-636 shall not be exceeded. When specified (see 6.2), fiberboard shipping containers for bulletin boards and stands shall conform to grade V3c, V3s, or V4s, style FOL of PPP-B-636; or class 2, style optional of PPP-B-640. Closure shall be in accordance with the appendix of the applicable container specification.

3.2.3 Level C. Bulletin boards, packaged as specified in 3.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification and National Motor Freight Classification, as applicable.

3.3 Marking. Marking shall be as specified in 3.3.1 or 3.3.2 (see 6.2).

3.3.1 Military requirements. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

3.3.2 Civil agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with FED-STD-123.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:52Z
Check the source to verify that this is the currentversion before use.

the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herein.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3 Inspection of the end item.

4.3.1 Examination of the end item for packaging, packing, and marking. The end item shall be examined for packaging, packing, and marking in accordance with the classification of defects set forth in tables I and II. The sample unit shall be one package or one shipping container as applicable. The lot for determining the sample size shall be expressed in terms of the sample unit. The acceptable quality levels shall be as follows:

Examination table	Inspection levels	AQLs
I	S-3	2.5
II	S-2	2.5

TABLE I. Examination for packaging

Examine	Defect
Package	
Stand	
Type II, class 1 and 2	Stand not disassembled and wrapped in kraft paper specified. Hardware not replaced in mating parts and secured.
Bulletin board	
Type I and II, class 1	Not wrapped in material specified and taped. Finished surfaces not covered to prevent marring or abrasion.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:52Z
Check the source to verify that this is the currentversion before use.

TABLE I. Examination for packaging (cont'd)

Examine	Defect
Package (cont'd)	
Bulletin board (cont'd)	
Type I and II, class 2 Style 1 and 2	Doors not locked. Keys not in cotton cloth drawstring bag and secured to back of board. Board not wrapped and cushioned as specified.
Style 1 only	Tube or bulbs not secured in place with tape. Cable not coiled and secured with tape.
Assembly (when specified)	Slide cover not taped securely in closed position. Not cushioned and secured in place to prevent damage or movement in transit.

TABLE II. Examination for packing and marking

Examine	Defect
Shipping container	Not style specified. Mixed types or classes in same container. Weight of contents exceeds that specified for style container.
Fiberboard container	Not waterproofed by method specified.
Wood container	Case liner missing or not completely sealed.
Marking	Omitted; incomplete; incorrect; illegible; of improper size, location, sequence or method of application.

4.3.1.1 Inspection of shipping containers. Inspection for closure and strapping shall be in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:52Z
Check the source to verify that this is the currentversion before use.

4.3.1.2 Inspection of packing. When cushioning, bracing and blocking is required to be in accordance with MIL-STD-1186, inspection shall be in accordance with the appendix of that standard.

5. PREPARATION FOR DELIVERY

(Not applicable).

6. NOTES

6.1 Intended use. This specification provides two levels of packaging and three levels of packing for Boards; Bulletin and Control.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Selection of the applicable levels of packaging and packing (see 3.1 and 3.2).
(c) When weather-resistant fiberboard is required for level B shipments (see 3.2.2).
(d) Marking required (see 3.3).

Custodians:

Army - GL
Air Force - 84

Review activity:

Army - SM

User activity:

Navy - YD

Preparing activity:

Army - GL

Civil Agency Coordinating Activity:

GSA - FSS

Project No. 7195-0079

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 70 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:52Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
Boards; Bulletin and Control; Packaging and Packing Of PPP-B-1980

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   a. GIVE PARAGRAPH NUMBER AND WORDING.

   b. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:52Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK Research & Development Command
NATICK, MA 01760
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



DRXNM-TDT

Commander
US Army Natick Research & Development Command
ATTN: DRXNM-TDT
Natick, MA 01760

NATICK OP 1 MAY 75
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:52Z
Check the source to verify that this is the current version before use.