MIL-C-52269A
2 August 1971

SUPERSEDING
MIL-C-52269
11 February 1963

MILITARY SPECIFICATION

CLAMP ASSEMBLY, HINGE, BRIDGE: STEEL; TREADWAY BRIDGE, FLOATING, FOOT, ALUMINUM

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a hinge clamp assembly to be used with the treadway of the aluminum floating footbridge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Box, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

Military

MIL-T-704	- Treatment and Painting of Materiel.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

MIL-C-16173 - Corrosion Preventive Compound, Solvent Cutback, Cold-Application.

STANDARDS

Federal

FED. STD. No. 595 - Colors.

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

ME

DL13218E9940 - Clamp Assembly, Hinge, Bridge.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN WELDING SOCIETY

A5.1 - Mild Steel Covered Arc-Welding Electrodes.

A5.18 - Mild Steel Electrodes for Gas Metal-Arc Welding.

B3.0 - Standard Qualification Procedure.

D2.0 - Welded Highway and Railway Bridges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Welding Society, 345 East 47th Street, New York, N. Y. 10017.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, N. Y. 10017.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D.C. 20036.)

3. REQUIREMENTS

3.1 Description. The hinge clamp assembly shall be as shown on DL 13218E9940 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

3.2 First article (Preproduction model). The supplier shall furnish one or more hinge clamp assemblies for examination and testing within the time frame specified to prove, prior to starting production, that his production methods will produce hinge clamp assemblies that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.4 Welding electrodes. Welding electrodes shall conform to AWS A5.1 or A5.18, classification E60 or E70 series, size as required.

3.5 Identification marking. The hinge clamp assembly shall be metal-die stamped as shown on the drawing. Die stamping shall be legible after painting.

3.6 Treatment and painting. The hinge clamp assembly except the pins and the threaded portion of the bolt shall be cleaned, treated, and painted in accordance with MIL-T-704, type B, except that the color number designation shall be 34087 in accordance with FED.STD. No. 595 The pins and the threaded portion of the bolt shall be coated with a corrosion preventive solvent cutback coating,hard film type, conforming to MIL-C-16173, grade 1.

3.7 Workmanship.

3.7.1 Steel fabrication. Steel may be cut by shearing, sawing, or flame cutting. Burned surfaces of flame-cut material shall be ground or machined to remove cooling checks. All burrs shall be removed.

3.7.2 Welders and welding.

3.7.2.1 Welders. Before assigning any welder to manual welding work covered by this specification, the supplier shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the material joined and the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

Standard Qualification Procedure of the American Welding Society (B3.0).

Welding Qualifications of the ASME Boiler and Pressure Vessel Code (Section IX).

3.7.2.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded metal-arc or gas metal-arc (MIG) process and shall conform to the provisions of the American Welding Society publication "D2.0 - Welded Highway and Railway Bridges". All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed and the deposit and adjoining base metal shall be wire brushed clean.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction hinge clamp assembly shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The hinge clamp assembly shall be examined for the following defects:

Major

101. Nonconformance to the dimensions shown on the drawing.
102. Material not as specified.
103. Workmanship not as specified.
104. Components missing or not as specified.

Minor.

201. Identification marking incorrect, missing, or illegible.
202. Treatment and painting not as specified.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

105.	Clamps packaged together in quantities other than specified for level A or B.
106.	Boxes not as specified for level A or B.
107.	Clamps not blocked within the box in a manner to prevent movement for level A or B.
108.	Quantities packed together exceed the size or weight limitations of the applicable box specification for level A or B.
109.	Strapping not zinc coated as specified for level A.
110.	Marking missing, illegible, incorrect or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified.

5.1.1 Level A. The clamps shall be packaged together in quantities of eight in a close-fitting box conforming to PPP-B-636, W6c, style optional. The contents shall be blocked within the box to prevent movement.

5.1.2 Level B. The clamps shall be packaged as specified in 5.1.1 except the box shall be type CF, class domestic, variety SW, grade 125.

5.1.3 Level C. The clamps shall be packaged in a manner to provide protection against mechanical and physical damage from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C as specified.

5.2.1 Level A. The clamps, packaged as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed the weight limitation of the box specification. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc coated.

5.2.2 Level B. The clamps, packaged as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-640, class 2, style optional, or PPP-B-636, V3c, or V15c, style optional. The gross weight or size of each box shall not exceed the limitation of the applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

box specification. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.3 Level C. The clamps, packaged as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at lowest rating in wooden or fiberboard containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The hinge clamp assembly is intended for use in connecting the treadway to aluminum floating footbridge when the treadway is being used as a ramp.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of the preproduction model (see 3.2).
(c) Level of packaging and level of packing required (see 5.1 and 5.2). Level B packaging and packing is intended to provide economical but limited protection and should be specified only when it has been determined the clamps will be held in covered storage.

6.3 Preproduction model. Any changes or deviations of production hinge clamp assemblies from the approved preproduction model during production will be subject to approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish hinge clamp assemblies conforming to this specification

6.4 Certain provisions of this specification are the subject of International Standardization Agreement ABC, Standard 88. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Custodians:

Army - ME

User Activity:

Navy - MC

Preparing activity:

Army - ME

Project no. 5420-0091

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-C-52269A, Clamp Assembly, Hinge, Bridge: Steel; Treadway Bridge, Floating, Foot, Aluminum

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.