MIL-F-63337(AR)
19 October 1979

MILITARY SPECIFICATION

FIRING ATTACHMENT, BLANK AMMO: XM19

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings, and provides quality assurance provisions for the fabrication of parts, assembling and packing for Firing Attachment, Blank Ammo: XM19.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents - The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC 1005

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:41Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9324931 -	Firing Attachment, Blank Ammo: XM19
PDS 9324931	Blank Firing Attachment

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 18 -	Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials
ASTM B 117 -	Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. - All parts shall comply with applicable drawings, specifications and standards.

3.3 Blank firing attachment,- The Blank Firing Attachment shall comply with all requirements specified on Drawing (Dwg.) F9324931, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.4 Assembleability. - Blank ammunition firing attachments shall readily attach to and detach from the specified weapon or a fixture simulating the specified weapon. When attached, firing attachments shall be securely retained on a simulator fixture or the specified weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

3.5 Functioning. - When assembled to the applicable weapon, the blank firing attachments shall permit the weapon to function properly. There shall be no more than one (1) stoppage or malfunction per one hundred (100) rounds directly attributable to the blank ammunition firing attachment. Testing shall be as specified in **4.5.4.**

3.6 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract and 4.3.

3.7 Workmanship. - All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, oil, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First Article Inspection.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. Unless otherwise specified in the contract, the first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Blank Firing Attachment	F9324931	25
Chamber	D9326857	10
Spacer, Rod	C9327080	10
Guide	C9326859 (2 sheets)	10
Link	B9326862	10
Guide Assembly	C9326868	10
Support	F9327085	10
Clamp, Threaded	C9326860	10

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION,

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE: Firing Attachment, Blank and Components		SHEET 1 OF 2		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: —
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	CHAMBER (DWG D9326857)				
	Examination for Defects	10		3.2	4.4.2.1
	SPACER, ROD (DWG C9327080)				
	Examination for defects	10		3.2	4.4.2.2
	Salt Spray Test	(a)		3.2	4.5.2
	Hardness	(a)		3.2	4.5.3
	GUIDE (DWG C9326859)				
	Examination for defects	10		3.2	4.4.2.3
	Salt Spray Test	(a)		3.2	4.5.2
	Hardness	(a)		3.2	4.5.3
	LINK (DWG B9326862)				
	Examination for defects	10		3.2	4.4.2.4
	Salt Spray Test	(a)		3.2	4.5.2
	Hardness	(a)		3.2	4.5.3
	GUIDE ASSEMBLY (DWG C9326868)				
	Examination	10		3.2	4.4.2.5

NOTES:

(a) This test shall be performed on the 10 samples subjected to the examination for defects.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:41Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Firing Attachment, Blank Components				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	SUPPORT				
	(DWG F9327085)				
	Examination for Defects	10		3.2	4.4.2.6
	Salt Spray Test	(a)		3.2	4.5.2
	Hardness	(a)		3.2	4.5.3
	CLAMP, THREADED				
	(DWG 09326857)				
	Examination for Defects	10		3.2	4.4.2.7
	Salt Spray Test	(a)		3.2	4.5.2
	Hardness	(a)		3.2	4.5.3
	BLANK FIRING ATTACHMENT				
	(DWG F9324931)				
	Examination for defects	25		3.2 & 3.4	4.4.2.8
	Functioning Test	(b)		3.5	4.5.4

NOTES:

(a) This test shall be performed on the 10 samples subjected to the examination for defects.
(b) This test shall be performed on the 25 samples subjected to the examination for defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Chamber				D 9326857
					NEXT HIGHER ASSEMBLY
					F 9324931
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Salt Spray test	4.5.2		3.2	4.5.2
102.	Diameter of smallest hole in center		0.65%(a)	3.2	Gage
103.	Total length		0.65%(a)	3.2	Gage
104.	Outside diameter between fins (6 places)		0.65%(a)	3.2	Gage
105.	Thickness of fins (12)		0.65%(a)	3.2	Gage
106.	Spacing of fins (12)		0.65%(a)	3.2	G a g e
107.	Diameter of rod spacer holes, min (3)		0.65%(a)	3.2	Gage
108.	Diameter above rod spacer hole (.85) (3)		0.65%(a)	3.2	Gage
109.	True position of rod spacer holes		0.65% (a)	3.2	Gage
110.	Diameter of large inside cavity for specified depth		0.65%(a)	3.2	Gage
111.	Perpendicularity of large inside cavity with specified surface		0.65%(a)	3.2	Gage
112.	Depth to bottom of large cavity to start of taper		0.65%(a)	3.2	Gage
113.	Internal (32) finish improper		0.65%(a)	3.2	Gage/Visual
MINOR					
201.	Distance between forward face and rod spacer hole surface (.95)		1.50%(a)	3.2	Gage
202.	Inside radius around the edge missing (.05)		1.50% (a)	3.2	Visual
203.	External finish improper		1.50%(a)	3.2	Visual/Measure
204.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

(a) See 4.5.1 for alternate inspection procedure for cast parts.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Spacer, Rod		c 9327080
			NEXT HIGHER ASSEMBLY
			F 9324911

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Hardness	4.5.3		3.2	4.5.3
102.	Salt Spray Test	4.5.2		3.2	4.5.2
103.	Length of larger diameter		0.65%	3.2	Gage
104.	Distance between longer thread face and start of largest diameter		0.65%	3.2	Gage
105.	Distance between shorter thread face and start of largest diameter		0.65%	3.2	Gage
106.	True position of largest diameter with designated threads		0.65%	3.2	Gage
107.	True postition of larger threads with shorter threads		0.65%	3.2	Gage
108.	Diameter of spacer		0.65%	3.2	Visual
109.	Thread damaged		0.65%	3.2	Visual
110.	Part bent or cracked		0.65%	3.2	Visual
111.	Wrench flat missing		0.65%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-0-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.3	Guide		C 9326859
			NEXT HIGHER ASSEMBLY
			C 9326868

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Hardness	4.5.3		3.2	4.5.3
102.	Salt Spray Test	4.5.2		3.2	4.5.2
103.	Width of hex slot		0.65%	3.2	Gage
104.	Depth to center of hex slot		0.65%	3.2	Gage
105.	Distance between hex slot and top surface (.20)		0.65%	3.2	Gage
106.	Width of link slots, max		0.65%	3.2	Gage
107.	Distance between extensions (3.90)		0.65%	3.2	Gage
108.	Thickness of part (.50)		0.65%	3.2	Gage
109.	Distance between link slot and top of extension (1.22)		0.65%	3.2	Gage
110.	Distance between link slot and surface before extension (.74)		0.65%	3.2	Gage
111.	Distance between link slot and top face (1.30) (2 places)		0.65%	3.2	Gage
112.	Outside diameter (4.17)		0.65%	3.2	Gage
113.	True position of outside diameter		0.65%	3.2	Gage
	(cont'd)				

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Guide	2 OF 2	C 9326859
			NEXT HIGHER ASSEMBLY
			C 9326868

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR					
114.	True position of pin holes (2)		0.65%	3.2	Gage
MINOR					
201.	Finish improper (63) (where noted on drawing)		1.50%	3.2	Visual/Measure
202.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Link		B 9326862
			NEXT HIGHER ASSEMBLY
			C 9326868

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Salt Spray Test	4.5.2		3.2	4.5.2
102.	Hardness	4.5.3		3.2	4.5.3
MINOR					
201.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23 02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Guide Assembly		C 9326868
			NEXT HIGHER ASSEMBLY
			F 9324931

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Protrusion of link, max (.39)		0.65%	3.2	Gage
102.	Drive screw, straight pin, or link missing		0.65%	3.2	Visual
103.	Wire rope assy missing or improperly positioned (not clear of pin hole)		0.65%	3.2	Visual
MINOR					
201.	Pin stake missing or improper		1.50%	3.2	Visual
202.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	ITLE			SHEET 1 OF 2	DRAWING NUMBER
4.4.2.6	Support				F 9327085
					NEXT HIGHER ASSEMBLY
					F 9324931
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	EQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Salt Spray Test	4.5.2		3.2	4.5.2
102.	Hardness	4.5.3		3.2	4.5.3
103.	Largest inside diameter (3.25)		0.65%(a)	3.2	Gage
104.	Second largest inside diameter (3.130)		0.65% (a)	3.2	Gage
105.	Smallest inside diameter (2.50)		0.65%(a)	3.2	Gage
106.	Distance between bottom of largest cavity and opposite face (1.10)		0.65%(a)	3.2	Gage
107.	Width of part (1.88)		0.65%(a)	3.2	Gage
108.	Diameter of hole counterbore (6 places) **(.82)**		0.65%(a)	3.2	Gage
109.	Diameter of clamp holes (3 places)		0.65% (a)	3.2	Gage
110.	Diameter of clamp hole counterbore **(.500)**		0.65%(a)	3.2	Gage
111.	Depth of clamp hole counterbore (3 places) **(.95)**		0.65% (a)	3.2	Gage
112.	True position of clamp counterbore (3 places)		0.65% (a)	3.2	Gage
113.	Perpendicularity of clamp hole counterbore (3 Places)		0.65% (a)	3.2	Gage
114.	True position of 3 clamp holes		0.65% (a)	3.2	Gage
	(cont'd)				

NOTES:

(a) See 4.5.1 for alternate inspection procedure for cast parts.

Source: https://assist.dla.mil -- Downloaded: 2026-04-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.6	Support		F 9327085
			NEXT HIGHER ASSEMBLY
			F 9324931

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR					
115.	Minor diameter of spacer holes thread (3) max.		0.65%(a)	3.2	Gage
116.	True position of 3 spacer holes		0.65%(a)	3.2	Gage
117.	Depth of thread in spacer hole (.87)		0.65%(a)	3.2	Gage
118.	Diameter of disconnect pin holes (2)		0.65%(a)	3.2	Gage
119.	True position of disconnect pin holes		0.65%(a)	3.2	Gage
MINOR					
201.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

(a) See 4.5.1 for alternate inspection procedure for cast parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Clamp, Threaded				C 9326860
					NEXT HIGHER ASSEMBLY
					C 11833399
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Salt Spray Test	4.5.2		3.2	4.5.2
102.	Hardness	4.5.3		3.2	4.5.3
103.	Outside diameter under bolt head		0.65%(a)	3.2	Gage
104.	Major diameter of thread		0.65%(a)	3.2	Gage
105.	Distance between underside of head and thread face (2.450)		0.65%(a)	3.2	Gage
106.	Total length		0.65%(a)	3.2	Gage
MINOR					
201.	Finish improper		1.50%	3.2	Visual
202.	Evidence of poor workmanship		2.50%	3.7	Visual

NOTES:

(a See 4.5.1 for alternate inspection procedure for cast parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.8	Blank Firing Attachment				F 9324931
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Functioning		0.65%	3.5	4.5.4
102.	Assembleability		0.65%	3.4	3.4
103.	Torque of rod spacer to support assembly improper		0.65%	3.2	Gage
104.	Torque of hex nut to rod spacer improper		0.65%	3.2	Gage
105.	Perpendicularity of rod spacer with noted surface of support		0.65%	3.2	Gage
106.	Part missing or loose		0.65%	3.2	Visual/Manual
107.	Rod spacer finish with burrs, raised metal, or slivers		0.65%	3.2	Visual
108.	Lockwire at nuts of chamber missing or improperly secured		0.65%	3.2	Visual
109.	Any part cracked		0.65%	3.2	Visual
110.	Any part improperly assembled		0.65%	3.2	Visual
111.	Finish improper, (burrs, sliver, raised metal, or sharp edges)		0.65%	3.2	Visual
	(cont'd)				

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-63337(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.8	Blank Firing Attachment				F 9324931
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR					
201.	Marking of support or guide missing, incorrect or unidentifiable		1.50%	3.2	Visual
202.	Indentification missing from support plate		1.50%	3.2	Visual
203.	Evidence of poor workmanship (Excluding 107, 109, and 111 above)		2.50%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:41Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Dimensional control of cast parts. - In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least five (5) parts (as cast) from each cavity shall be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 500 parts. Individual cavity identification shall be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

4.5.2 Salt spray test. - Five (5) of each specified part shall be selected from each lot and subjected to the salt spray test in accordance with the procedures specified in ASTM B 117. The minimum exposure time shall be one and one half (1 1/2) hours using a 5% sodium chloride solution. If any part shows evidence of corrosion, it shall be classed defective and the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

4.5.3 Hardness. - Ten (10) of each of the specified parts shall be selected from each heat treatment batch (See NOTE) and subjected to this test. If any part fails to comply with the requirement specified on the applicable drawing, the batch represented by the failing part shall be rejected. The hardness test shall be performed in accordance with the procedure specified in ASTM E 18.

NOTE - A heat-treatment batch shall be defined as parts that have been heat treated at the same time in the same furnace and quench bath for each of all phases of the entire heat treatment process.

4.5.4 Functioning. - The assemblies selected for the functioning test shall be assembled to the .50 Caliber M2 Heavy Barrel, Machine gun. Government standard Caliber .50, M1E1 blank cartridges shall be used for this test. A total of 100 rounds of 20/belt shall be fired. Any assembly which fails to comply with the requirements specified in 3.5 shall be classed defective. All test results shall be recorded.

5. PACKAGING

5.1 Levels A and B. - The blank firing attachments shall be packaged in accordance with the Packaging Data Sheet 9324931 and as specified in the contract.

5.2 Marking. - Marking shall be in accordance with applicable Packaging Data Sheet 9324931 and as specified in the contract.

5.3 Shipping. - When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. - The assembly covered by this specification is intended for use with Machine Gun, .50 Cal., Heavy Barrel, M2.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - See MIL-A-48078. Submit equipment designs as required to Commander, ATTN: DRDAR-QAA-I, ARRADCOM, Dover, NJ 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects or test paragraph number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

6.4 Drawings. - Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity
Army-AR

Project 1005-A592

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-63337 Firing Attachment, Blank Ammo: XM19

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ .MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMEN? USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:41Z
Check the source to verify that this is the current version before use.