NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time the document is revised.

INCH-POUND

MIL-PRF-83401/8C
AMENDMENT 1
26 November 1993

PERFORMANCE SPECIFICATION

RESISTOR NETWORK, FIXED, FILM
STYLE RZ080, 8 PIN SIP

This amendment forms a part of MIL-R-83401/8C, dated 14 December 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Add the following new paragraph:

"4.2 H schematic tests. For the test on H schematic, the dc resistance measurements, resistance temperature characteristic measurement, and short time overload power application shall be made between each terminal and the applicable common terminal without compensation for the shunt circuits. The pin to pin dc resistance measurements shall be used directly to determine the acceptability to section 3 requirements."

PAGE 5

FIGURE 1: Delete ".076 +.027 -.026" and substitute ".098 max" in two places.

PAGE 6

FIGURE 1, Inches mm: Delete ".026 0.66", ".027 0.69" and ".076 1.93". Add ".098 2.49", in proper sequence.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, AT, AV, ME, MI
Navy - AS, CG, MC, OS
Air Force - 17, 19
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5905-1349-05)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:57Z
Check the source to verify that this is the current version before use.