MILITARY SPECIFICATION

RESISTOR-CAPACITOR NETWORK, FIXED FILM RESISTORS AND CERAMIC CAPACITOR, STYLE RZ110, 16 PIN DIP

This amendment forms a part of MIL-R-83401/11, dated 9 March 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.3.4, delete and substitute:

"3.3.4 Power rating (70°C). The power rating shall be 0.1 watt for each resistor. Total network power rating shall be 1.2 watts."

After 3.3.4, add the following:

"3.3.4.1 Power conditioning. The power applied for power conditioning shall be 0.15 watt per resistor and 1.5 watts for the network."

PAGE 4

FIGURE 2, note 5, delete and substitute:

"5. Pin 1 locator shall be a dot, stripe, notch, or numeral 1 adjacent to pin 1, in the shaded area."

PAGE 6

4.1.1b, delete and substitute:

"b. The inspections specified in table II shall be conducted on the number of samples specified. Samples may be of any schematic but shall be of the highest resistance value for which qualification is requested."

PAGE 10

After 6.1, add the following:

"6.2 Power rating at 25°C. The power rating at 25°C for 1,000 hours of life test shall be 0.125 watt per resistor and 1.5 watts for the network."


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:57Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 17
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5915-0335)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:57Z
Check the source to verify that this is the current version before use.