INCH-POUND

MIL-M-28787/297A(SH)
AMENDMENT 2
3 December 1991
SUPERSEDING
AMENDMENT 1
28 August 1986

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE RHF

This amendment forms a part of Military Specification MIL-M-28787/297A(EC), dated 2 August 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.3, second line: Delete "0.043" and substitute "0 091".

3.3, third line: Delete "0.097" and substitute 0.136".

PAGE 4

TABLE I, Test conditions N13-N24, Min columns: Delete "10" (five places) and substitute "5" (five places).

* TABLE I, Test conditions E1-E12 and F1-F24, Test type column: Delete "X" and substitute "S".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:29Z
Check the source to verify that this is the current version before use.

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, E, and F where applicable, followed by the remaining tests in the sequence."

* 4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through W in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions D, G through V shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

* 4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests D, G through V shall be performed in the order specified in 4 4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests D, G through V shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 43

TABLE XV, Test conditions N13-N20, Min column: Delete "10" and substitute "5".

PAGE 44

TABLE XV, Test conditions N21-N24, Min column. Delete "10" and substitute "5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:29Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy – SH

(Project 5963-N785)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:29Z
Check the source to verify that this is the current version before use.