INCH-POUND

MIL-M-28787/300A
AMENDMENT 2
28 April 1993
SUPERSEDING
AMENDMENT 1
19 November 1990

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COMPARATOR, MAGNITUDE, DIGITAL, KEY CODE HFB

This amendment forms a part of Military Specification MIL-M-28787/300A(EC), dated 21 July 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions D1-D6, E1-E6, and F1-F30, Test type column: Delete "X" and substitute "S".

PAGE 7

*TABLE I, Test conditions R43-R50, R63-R66, R75-R82, R91-R98, 25°C, 0°C, and -55°C columns, Min columns: Delete "6" (three places) and substitute "5" (three places).

*TABLE I, Test conditions R43-R50, R63-R66, R75-R82, R91-R98, 60°C and 85°C columns, Min columns: Delete "7" (two places) and substitute "5" (two places).

*TABLE I, Test conditions R59-R62, 25°C, 0°C, and -55°C columns, Min columns: Delete "6" (three places) and substitute "3" (three places).

*TABLE I, Test conditions R59-R62, 60°C and 85°C columns, Min columns: Delete "7" (two places) and substitute "3" (two places).

*TABLE I, Test conditions R59-R62, 25°C, 0°C, and -55°C columns, Max columns: Delete "68" (three places) and substitute "34" (three places).

*TABLE I, Test conditions R59-R62, 60°C column, Max column: Delete "72" (one place) and substitute "36" (one place).

*TABLE I, Test conditions R59-R62, 85°C column, Max column: Delete "75" (one place) and substitute "37" (one place).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:30Z
Check the source to verify that this is the current version before use.

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

*4.5.1, fifth line: Delete "D through V" and substitute "G through V".

*4.5.3, third line: Delete "D through V" and substitute "G through V".

*4.5.3, fifth line: Delete "D through W" and substitute "G through W".

PAGES 56 through 60

*TABLE XII, Test conditions R43-R50, R63-R66, R75-R82, R91-R98, 25°C column, Min column: Delete "6" and substitute "5".

*TABLE XII, Test conditions R59-R62, 25°C column, Min column: Delete "6" and substitute "3".

*TABLE XII, Test conditions R59-R62, 25°C column, Max column: Delete "68" and substitute "34".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0278)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:30Z
Check the source to verify that this is the current version before use.