INCH-POUND

MIL-M-28787/301A
AMENDMENT 3
31 December 1992
SUPERSEDING
AMENDMENT 2
7 May 1985

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MICROPROCESSOR, KEY CODE ERD

This amendment forms a part of Military Specification MIL-M-28787/301A(EC), dated 9 July 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGES 4, 5, 6, 7, 8, 9, 10, AND 11

TABLE I, Class II table heading: Delete "100°" (eight places) and substitute "85°" (eight places).

PAGE 4

*TABLE I, Test conditions E1-E13, Test type column: Delete "X" and substitute "S".

*TABLE I, Test conditions K1-K4, All temperatures, Min column: Delete "-1" (five places) and substitute "-5" (five places).

*TABLE I, Test conditions K5-K8, All temperatures, Min column: Delete "-1" (five places) and substitute "-10" (five places).

PAGE 5

*TABLE I, Test conditions L1-L4, All temperatures, Max column: Delete "1" (five places) and substitute "5" (five places).

*TABLE I, Test conditions L5-L8, All temperatures, Max column: Delete "1" (five places) and substitute "80" (five places).

*TABLE I, Test condition N, 25° ± 5°C, Max column: Delete "250" and substitute "280".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:31Z
Check the source to verify that this is the current version before use.

PAGE 5

*TABLE I, Test condition N, Class I, 0° ± 5°C, Max column: Delete "265" and substitute "280".

*TABLE I, Test condition N, Class I, 60° ± 5°C, Max column: Delete "265" and substitute "280".

PAGE 10

*TABLE I, Test conditions U1-U4 and U9-U12, All temperatures, Min column: Delete "6" (three places) and "7" (two places) and substitute "2" (five places).

PAGE 11

*TABLE I, Test conditions U5-U8 and U13-U16, All temperatures, Min column: Delete "6" (four places) and "7" (one place) and substitute "2" (five places).

PAGE 12

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through DD shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and E are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and E where applicable, followed by the remaining tests in the sequence."

*4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through DD in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions F through Z, and DD shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:31Z
Check the source to verify that this is the current version before use.

PAGE 12

*4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests F through Z, and DD shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests F through DD shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 30

*FIGURE 8, Digital multifunction meter box: Reverse the "+" and "-" signs.

PAGE 51

*TABLE XII, Test conditions K1, K2, K3, and K4, Min column: Delete "-1" (one place) and substitute "-5" (one place).

*TABLE XII, Test conditions K5, K6, K7, and K8, Min column: Delete "-1" (one place) and substitute "-10" (one place).

PAGE 52

*TABLE XIII, Test conditions L1, L2, L3, and L4, Max column: Delete "1" (one place) and substitute "5" (one place).

*TABLE XIII, Test conditions L5, L6, L7, and L8, Max column: Delete "1" (one place) and substitute "80" (one place).

PAGE 56

*TABLE XV, Test condition N, Max column: Delete "250" and substitute "280".

PAGE 90

*TABLE XXI, Test conditions U1 through U16, Min column: Delete "6" (one place) and substitute "2" (one place).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:31Z
Check the source to verify that this is the current version before use.

*FIGURE 39, ITEM C01 box: Delete "C01" and substitute "C06".

*FIGURE 39, NOTE 3, first line: Delete "(C01)" and substitute "(C06)".
FIGURE 39, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 kHz.".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0233)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:31Z
Check the source to verify that this is the current version before use.