INCH-POUND

MIL-M-28787/310B(SH)
AMENDMENT 2
19 March 1992
SUPERSEDING
AMENDMENT 1
14 February 1986

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COMPONENTS, MISCELLANEOUS, KEY CODE FMD

This amendment forms a part of Military Specification MIL-M-28787/310B(EC), dated 13 July 1984, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

TABLE I, Test condition F1, Initial, Max columns: Delete "50" (three places) and substitute "100" (three places).

TABLE I, Test condition F1, Initial, Class I 60 ± 5°C Max column: Delete "150" (one place) and substitute "500" (one place).

TABLE I, Test condition F1, End-of-life, Max columns: Delete "150" (three places) and substitute "300" (three places).

TABLE I, Test condition F1, End-of-life, Class I 60 ± 5°C Max column: Delete "500" (one place) and substitute "1000" (one place).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:38Z
Check the source to verify that this is the current version before use.

PAGE 6

* TABLE I, Test conditions G5 and G6, Max columns: Delete "8.00" (three places) and substitute "8.25" (three places).

* TABLE I, Test conditions G5 and G6, Max column: Delete "8.15" (one place) and substitute "8.30" (one place).

PAGE 9

* 4.5.1, fifth line: Delete "A through R" and substitute "A through P".

PAGE 20

TABLE VI, Test condition F1, Max column: Delete "50" (one place) and substitute "100" (one place).

PAGE 22

* TABLE VII, Test condition G5, Max column: Delete "8.00" (one place) and substitute "8.25" (one place).

* TABLE VII, Test condition G6, Max column: Delete "8.00" (one place) and substitute "8.25" (one place).

PAGE 26

FIGURE 9, Note 8: Delete "PRR" and substitute "PRP".

PAGE 32

* FIGURE 11, Note 5C: After "Adjust item P01 for 10V ± 1%", insert "for test conditions L1 and L2, and 15V ± 1% for test condition L3,".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:38Z
Check the source to verify that this is the current version before use.

PAGE 38

FIGURE 14, Note, PRP: Delete "10.0 ± 0.5s" and substitute "10.0 ± 0.5µs".

PAGE 40

FIGURE 16, Note, PRP: Delete "10.0 ± 0.5s" and substitute "10.0 ± 0.5µs".

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH

(Project 5963-N806)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:38Z
Check the source to verify that this is the current version before use.