INCH-POUND

MIL-M-28787/312(SH)
AMENDMENT 2
24 August 1990
SUPERSEDING
AMENDMENT 1
11 April 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, TRANSLATOR, DIGITAL, KEY CODE DLB

This amendment forms a part of Military Specification MIL-M-28787/312(SH), dated 14 July 1980, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 3.3, second line: Delete "0.060" and substitute "0.230".

PAGE 2

* 4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through U shall be performed in any order with the following exceptions. Test conditions A, B, C, and E are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, and E where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:39Z
Check the source to verify that this is the current version before use.

PAGE 4

TABLE I, Test conditions D1–D18, Max columns: Delete "15" (four places) and substitute "20" (four places).

* TABLE I, Test conditions E1–E18, Test type column: Delete "X" and substitute "S".

PAGE 6

* 4.5.1, fifth and sixth lines: Delete "E through U" and substitute "F through P and T".

* 4.5.3, third line: Delete "E through U" and substitute "F through P and T".

* 4.5.3, sixth line: Delete "D through U" and substitute "F through P and T".

PAGE 16

TABLE VI, Test conditions D1 through D18, Max column: Delete "15" and substitute "20".

PAGE 22

FIGURE 10: Delete and substitute new figure 10 as printed on page 3 of this amendment.


NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy – SH

(Project 5963–N787)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:39Z
Check the source to verify that this is the current version before use.



NOTE: R1 = R2 = 51Ω ± 5%, 1W.

FIGURE 10. Static output voltage (high-level and low-level) test circuit for tables VIII and IX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:39Z
Check the source to verify that this is the current version before use.