INCH-POUND

MIL-M-28787/313A(SH)
AMENDMENT 1
29 March 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RECEIVER, TRANSLATOR, DIGITAL, KEY CODE DLC

This amendment forms a part of Military Specification MIL-M-28787/313A(EC), dated 27 April 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 2

3 3, second line: Delete "0.168" and substitute "1 106".

PAGE 4

TABLE I, Test conditions D1-D12, Test type column: Delete "X" and substitute "S"

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through T shall be performed in any order with the following exceptions. Test conditions A, B, and D are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, or D are part of a sequence of tests, the order of testing shall be as follows. A, B, and D, where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:39Z
Check the source to verify that this is the current version before use.

4 5 1, fifth line: Delete "D through T" and substitute "E through P, and T"

4.5.3, third line: Delete "D through T" and substitute "E through P, and T".

4.5.3, sixth line. Delete "C through T" and substitute "E through P, and T".

Preparing activity
Navy – SH

(Project 5963–N788)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:39Z
Check the source to verify that this is the current version before use.