INCH-POUND

MIL-M-28787/315
AMENDMENT 1
28 April 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

FLIP-FLOP, JK, DIGITAL, KEY CODE FRE

This amendment forms a part of Military Specification MIL-M-28787/315(EC), dated 21 October 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through Y shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and E are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and E where applicable, followed by the remaining tests in the sequence."

4.5.1, line 6: Delete "D through X" and substitute "F through X".

4.5.3, lines 3 and 4: Delete "D through X" and substitute "F through X".

4.5.3, line 6: Delete "D through X" and substitute "F through X".

PAGE 5

TABLE I, Test conditions D1-D12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E26, Test type column: Delete "X" and substitute "S".

PAGE 71

FIGURE 28, ITEM C01 box: Delete "C01" and substitute "C06".

FIGURE 28, NOTE 3, first line: Delete "(C01)" and substitute "(C06)".

FIGURE 28, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:40Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0241)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:40Z
Check the source to verify that this is the current version before use.