INCH-POUND
A-A-59326/18C
12 May 2014
SUPERSEDING
A-A-59326/18B
April 22, 2011

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

COUPLING HALF, FEMALE REDUCER BY INTERNAL PIPE THREAD, TYPE XVIII

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring couplings described herein shall consist of this document and the latest issue in effect of A-A-59326.



NOTES: Dimensions are in inches.

FIGURE 1. Coupling Half.

Comments, suggestions, or questions on this document should be addressed to Tank-automotive and Armaments Command, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or emailed to usarmy.detroit.rdecom.mail.tardec-standardization@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 4730

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

1. SCOPE. This specification covers a Female Reducer by Internal Pipe Thread, Type XVIII Coupling Half.

2. CLASSIFICATION: The size of the coupling halves is designated in Table 1.

TABLE 1. Coupling Half Size

Dash No.	Cam-Lock Nom. Size	Thread NPT	Gasket Reqd.	Working Pressure (psi)	Hydrostatic Test Pressure (psi)
1	3	2-11½	-8	150	300
2	4	3-8	-9	150	300
3	6	4-8	-10	75	150
4	6	4-8	-10	150	225

NOTE: Sizes are in Inches

3. SALIENT CHARACTERISTICS. The following characteristics differ from those listed in A-A-59326.

3.1 Accessories. The coupling shall be provided with the gasket and pull ring indicated.

3.2 Threads. The coupling threads shall conform to National Tapered Pipe Thread per ANSI/ASME B1.20.1.

3.3 Hydrostatic test pressure. See Table 1.

3.4 Working pressure. See Table 1.

3.5 Cam-arms The dash number 1(one) through (3) couplings shall have two cam arms. The dash 4 (four) coupling, 6-inch, 150 psi working pressure shall have 4 (four) cam arms.

4 NOTES

4.1 Part Identification Number (PIN). The following PIN procedure is for government purposes and does not constitute a requirement for the contractor. This example describes a part numbering system for specification sheet A-A-59326/18.

AA59326/18-1-SS-1; where /18 indicates a Female Reducer by Internal Pipe Thread Coupling Half; -1 indicates a 3-inch cam-locking by 2-inch NPT size; -SS indicates Stainless Steel body and -1 indicates a style 1 coupling half.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.

Material: A – Aluminum Alloy
B – Copper Alloy (Brass or Bronze)
BA – Aluminum Bronze
SS – Stainless Steel

Style 1 – Style 1 couplings do not require the incorporation of a positive locking mechanism to lock the cam arms in the closed position but the cam arms shall stay in the closed position when the coupling halves are assembled.

Style 2- Style 2 couplings shall incorporate a positive locking mechanism to lock the cam arms in the closed position when the coupling halves are assembled. The locking mechanism shall be manually released (the release doesn't have to stay in the released position) before the cam arms can be moved to the open position.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - YD
Air Force – 99

Review Activities:
Army - AV, GL
Navy - MC, SH
Air Force - 71
DLA - CC

Civil Coordinating Activity:
GSA - FSS

CIVIL AGENCY COORDINATION ACTIVITY:
GSA-FAS

Preparing Activity:
Army - AT

(Project 4730-2014-045)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:11Z
Check the source to verify that this is the current version before use.