MIL-D-16196D(SHIPS)
AMENDMENT 5
15 August 1985
SUPERSEDING
AMENDMENT 4
19 October 1962

MILITARY SPECIFICATION

DISTILLATION UNIT, WATER, THERMOCOMPRESSION

This amendment forms a part of Military Specification MIL-D-16196D(SHIPS), dated 19 October 1960, and is approved for use within the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Under "SPECIFICATIONS" delete reference to "FEDERAL QQ-R-175 - Resistance Wire."

2.1: Under "SPECIFICATIONS, MILITARY": Add

"MIL-Q-9858 - Quality Control System Requirements.
"MIL-H-22577 - Heating Elements, Electrical, Cartridge, Ship and Tubular Type."

PAGE 2

2.1: Under "PUBLICATIONS BUREAU OF SHIPS" add the following:

"NAVSHIPS 250-637-2 - Instructions for Torch Brazing of Ferrous and Non-Ferrous Piping."

2.2: Under "American Society for Testing Materials" add "ASTM B 165 - Nickel-Copper Alloy Seamless Pipe and Tube."

* 3.1: Delete and substitute:

"3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2)."

FSC 4620

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:23Z
Check the source to verify that this is the current version before use.

PAGE 6

3.14.2.1, 3.14.2.2 and 3.14.2.3: Delete and substitute:

"3.14.2.1 Heating units shall consist of tubular type electric heating elements conforming to MIL-H-22577, secured to cast bronze flanges by means of brazing or compression fittings. The heating element sheath material shall be nickel-copper alloy, ASTM B 165. The ends of the elements shall be hermetically sealed by ceramic-to-metal seals. Each heating unit shall be provided with an identification plate giving connection data."

3.16: Delete and substitute:

"3.16 Welding and allied processes. Welding shall be in accordance with MIL-STD-278. Brazing of piping joints including root connections shall be accomplished in accordance with NAVSHIPS 250-637-2; where these joints are 1/2 inch or above in nominal size, preinserted ring fittings shall be used. Face feed fittings may be used in sizes below 1/2 inch."

PAGE 10

3.25, line 2: Delete "type II of".

* 3.28: Delete in its entirety.

4.1: Delete and substitute:

"4.1 Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

4.1.1, 4.1.1.1, 4.1.1.2 and 4.1.1.3: Delete and substitute:

"4.1.1 Quality control system. The contractor shall provide and maintain a quality control system acceptable to the Government for the supplies covered by this specification. The system of quality control shall be in accordance with MIL-Q-9858 supplemented as specified in 4.1.1.1, 4.1.1.2 and 4.1.1.3.

"4.1.1.1 Description of procedures. Procedures shall be assembled in manual form and shall include a flow chart showing the developments of the product through the manufacturing cycle. The procedures shall indicate organization and responsibility for the control of quality.

"4.1.1.2 Inspection during manufacture. The contractors shall establish as a minimum, four inspection points located as follows:

(a) Initial set-up.
(b) First assemble.
(c) Second assemble.
(d) Roving floor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:23Z
Check the source to verify that this is the current version before use.

"4.1.1.3 Storage. Supplies shall be stored in a dry area."

* 4.2, line 1: Delete "Qualification" and substitute "First article".

* 4.2, line 1: Delete "footnote 1/" in its entirety.

PAGE 14

* 6.1, Add as item (o):

"(o) Whether first article inspection is required (see 3.1)."

* 6.2 and 6.3: Delete and substitute:

"6.2 First article inspection. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection as to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4620-N036)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:23Z
Check the source to verify that this is the current version before use.