INCH-POUND

MIL-W-22759/6B
AMENDMENT 2
16 October 1998
SUPERSEDING
MIL-W-22759/6B
AMENDMENT 1
31 December 1990

MILITARY SPECIFICATION SHEET

* WIRE, ELECTRICAL, FLUOROCARBON - INSULATED, ABRASION RESISTANT EXTRUDED PTFE, NICKEL - COATED COPPER CONDUCTOR, 600 VOLT

This amendment forms a part of MIL-W-22759/6B, dated 31 December 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title, second line: Delete "TFE" and substitute "PTFE."

* Note between drawing and table I: Delete and substitute:

"Note: Outer surface is smooth, homogeneous PTFE with no mineral filler exposed."

Delete FSC 6145 and substitute "FSC 6145."

* Add: "DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited." at the bottom of page 1.

PAGE 2

Delete and substitute:

Under "Additional requirements"

Low temperature (cold bend):
Bend temperature: -65 ±2°C (-85 ±3.6°F)
Dielectric test, 3000 volts (rms), 60 Hz

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:44Z
Check the source to verify that this is the current version before use.

Dielectric test after immersion: 3000 volts (rms), 60 Hz
* Acid resistance: Not required.
Dielectric test, 3000 volts (rms), 60 Hz

Conductor strand adhesion requirements shall be in accordance with 3.6.11 of MIL-W-22759.

Changes from previous issue. The margins of this amendment are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force – 85

Preparing activity:
Navy - AS

(Project 6145-2172-02)

Review Activities:
Army - AR, AT, AV, CR4, MI
Navy - EC, MC, OS
Air Force - 11, 80, 99
DLA – CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:44Z
Check the source to verify that this is the current version before use.