INCH-POUND

MIL-W-22759/7B
AMENDMENT 1
31 December 1990

MILITARY SPECIFICATION SHEET

WIRE, ELECTRICAL, FLUOROPOLYMER-INSULATED, ABRASION RESISTANT EXTRUDED TFE, MEDIUM WEIGHT, SILVER-COATED COPPER CONDUCTOR, 600 VOLT

This amendment forms a part of Military Specification MIL-W-22759/7B, dated 19 July 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Note: Delete and substitute:

Note: Outer surface must be smooth, homogeneous TFE with mineral filler exposed.

Delete FSC 6145 and substitute FSC 6145

Add DISTRIBUTION STATEMENT A. at the bottom of page 1.

PAGE 2

Delete and substitute:

Under " Additional requirements"

Low temperature (cold bend):
Bend temperature: -65 $\pm$2°C (-85 $\pm$3.6°F)
Dielectric test, 3000 volts (rms), 60 Hz

Dielectric test after immersion: 3000 volts (rms), 60 Hz

Acid Resistance: Required
Dielectric test, 3000 volts (rms), 60 Hz

Conductor strand adhesion requirements shall be in accordance with 3.6.11 of MIL-W-22759.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:45Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR, ME, MI
Navy - EC, OS
Air Force - 80, 99
DLA - IS

User activities:
Army - AT, AV
Navy - MC
Air Force - 11

Preparing activity:
Navy - AS

Agent:
DLA - IS

(Project 6145-1152-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:45Z
Check the source to verify that this is the current version before use.