INCH-POUND

MIL-PRF-27/187D
18 July 2008
SUPERSEDING
MIL-T-27/187C
2 June 2003

MILITARY SPECIFICATION SHEET

TRANSFORMER, POWER, STEP-DOWN, AUTOTRANSFORMER

Inactive for new design
after 13 March 1991

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification and MIL-PRF-27.





FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:47Z
Check the source to verify that this is the current version before use.



ALTITUDE = 80,000 FT MAX

Inches	mm	Inches	mm	Inches	mm
.005	0.13	.28	7.1	.875	22.22
.031	0.79	.31	7.9	1.187	30.15
.100	2.54	.37	9.4	1.53	38.9
.164	4.17	.38	9.7	1.562	41.96
.190	4.83	.437	11.10	1.69	42.9
.20	5.1	.593	15.06	2.270	57.69
.251	6.38	.770	19.56		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm) for three place dimensions and ±.03 (0.8 mm) for two place dimensions.
4. Marking shall be on the top of the case.
5. Stud shoulder shall form an integral part of the threaded stud terminal.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:47Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When designations or colors in parentheses, i.e., (COM-HV) (BLK-WHT) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary (COM-HV): 173 volts ampere, 115 volts rms, 400 hertz.

Secondary (BLK-WHT): 12.5 volts rms, 11.2 amperes rms.

Working voltage:

(COM-HV): 179 volts maximum.
(BLK-WHT): 20 volts maximum.

DC resistance: At ambient temperature of +20°C.

(BLK-WHT): 0.057 ohm ±15 percent.
(WHT-HV): 1.45 ohms ±15 percent.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Diallyl phthalate (ASTM D 5948-96).

Weight: 0.820 pound maximum.

Terminal type:

Primary: Corrosion-resistant steel, threaded integral shoulder-stud.

Secondary: Number 18 AWG insulated lead wire in accordance with MIL-DTL-16878, type EE.

Terminal height:

Primary: See figure 1.

Terminal length:

Secondary: 16 ±1 inch.

Altitude: 80,000 feet maximum.

Operating temperature range: -54°C to +170°C.

Operating temperature: +170°C maximum.

Insulating materials:

Magnet wire insulation: Modified polyester base, polyamide-imide overcoat, +200°C.

Encapsulating material: Epoxy, +170°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:47Z
Check the source to verify that this is the current version before use.

Paper: Aramid, +220°C.

Tape:

Backings: Polyamide film, glass cloth, aramid paper, +220°C.

Adhesive: Silicone, +180°C.

Bobbin: Aramid, +220°C.

Housing: Diallyl phthalate, +180°C.

Terminal strength: MIL-STD-202, method 211, test condition A, 5 pounds.

Vibration, high frequency: MIL-STD-202, method 204, test condition D.

Salt spray (corrosion): MIL-STD-202, method 101, test condition B.

Dielectric withstanding voltage:

At sea level: 500 volts rms.

At barometric pressure: 300 volts rms.

Electrical characteristics:

No load: With 115 volts rms, 400 hertz across (COM-HV).

Current in (COM-HV): 150 milliamperes maximum.

Power in (COM-HV): 2.9 watts maximum.

Voltage across (BLK-WHT): 13.7 volts rms ±2 percent.

Rated load: With 115 volts rms, 400 hertz across (COM-HV).

Voltage across (BLK-WHT): 12.5 -0, +0.4 volts rms at an ambient temperature of +70°C.

Voltage across (BLK-WHT): 12.5 -0, +0.7 volts rms at an ambient temperature of +25°C.

Temperature rise: +100°C with 115 volts rms, 400 hertz across (COM-HV) at an ambient temperature of +70°C.

Voltage regulation: 10 percent maximum.

VERIFICATION:

Qualification inspection: Not applicable.

Quality conformance inspection: Groups A and B tests of MIL-PRF-27 shall be applicable.

Marking location: See figure 1.

Part or Identifying Number (PIN): M27/187-01.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:47Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202
MIL-DTL-16878
ASTM D 5948-96
NASM 15795
NASM 21043

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA – CC

(Project 5950-2008-023)

Review activities:
Army – AR, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:47Z
Check the source to verify that this is the current version before use.