

MILITARY SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS
(AUDIO, POWER AND HIGH-POWER PULSE),
INDUCTOR, POWER, TF5S04ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the inductor described herein shall consist of this document and the latest issue of Specification MIL-T-27.





WORKING VOLTAGE: 500 V MAX

CIRCUIT DIAGRAM AND MARKING

INCHES	MM
.010	.25
.030	.76
.050	1.27
.125	3.18
.175	4.44
.250	6.35
.350	8.89
.500	12.70
.710	18.03
.740	18.80
.865	21.97

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Marking shall be on the side of the case.

FIGURE 1. Dimensions and configuration.

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:48Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:
Inductance (1-2): 40 microhenries to 60 microhenries.
Voltage (1-2): 0.5 volts rms, 16 kilohertz.
Current (1-2): 4.8 amperes dc.
DC resistance (1-2): .030 ohms, maximum.
Working voltage: 500 volts, maximum.

Design and construction:
Dimensions and configuration: See figure 1.
Duty cycle: Continuous.
Case: Encapsulated.
Material: Epoxy.
Terminals: Pin type, tinned copper.
Height: .500 inch, minimum.
Diameter: .030 inch.
Weight: 27.21 grams, maximum.
Operating temperature range: -55°C to +130°C.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Shock (specified pulse): MIL-STD-202, method 213, test condition A.

Vibration (high frequency): MIL-STD-202, method 204.

Dielectric withstanding voltage (at sea level): 500 volts rms.

Electrical characteristics:
Inductance: With .5 volt rms, 16 kilohertz and 4.8 amperes dc applied to (1-2), the inductance shall be 40 microhenries, minimum, 60 microhenries, maximum.
Temperature rise: 20°C with .5 volt rms, 16 kilohertz 4.8 amperes, dc applied to (1-2) at an ambient temperature of 125°C, maximum.

Marking location: See figure 1.

Part number: M27/191-01.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH, OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME, AR, WC
Navy - MC, AS
Air Force - 19

Preparing activity:
Army - EL

Agent:
DLA - ES

(Project 5950-0538-51)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:48Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Electronics Command
ATTN: DRSEL-RD-TS-S
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-27/191 TRANSFORMERS AND INDUCTORS (AUDIO, POWER AND HIGH-POWER PULSE) INDUCTOR, POWER, TF5SOLZZ

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDO ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT
UC ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.
GIVE PARA R P I NUMBER AND WORDING

3 RECOMMENDED WORDING CHANGE

REASON FOR REC MENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:48Z
Check the source to verify that this is the current version before use.