INCH-POUND

MIL-DTL-3628/265
31 March 2015

DETAIL SPECIFICATION SHEET

# BADGE, QUALIFICATION, NATIONAL GUARD CHIEF'S 50 MARKSMANSHIP, RIFLE AND PISTOL CHAMPIONSHIPS, PENDANT AND SUSPENSION BAR

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.




MATERIAL: PENDANT AND SUSPENSION BAR: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: PENDANT AND SUSPENSION BAR: 24K Gold Plated, Matte Finish, Polished Highlights and shall match the Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT (Overall):
ASSEMBLED: 2 Inches (REF)
PENDANT: 1-15/32 inches (REF)
SUSPENSION BAR (Without lugs): 3/8 inch (REF)
WIDTH (Overall):
PENDANT: 1-9/32 inches (REF)
SUSPENSION BAR: 1-15/32 inches (REF)
THICKNESS:
PENDANT: 0.109 ± .010 inch
SUSPENSION BAR: 0.103 ± .010 inch



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:26Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. The attaching device shall be prong and flat ball type clutch.

2. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-11/32 inches ± 1/32 inch apart.

NOTES:

1: The term (REF) refers to the measurements taken from the Government furnished hub or die.

2: The links shall be gold plated with the option of using Nickel Silver as the base metal

3. The lugs are integral to the suspension bar and pendant.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2015-257)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:26Z
Check the source to verify that this is the current version before use.