INCH-POUND

MIL-DTL-3628/269
28 October 2016

DETAIL SPECIFICATION SHEET


BADGE, DEFENSE POW/MIA ACCOUNTING AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



ASSEMBLE



BASE



EAGLE DEVICE



WREATH DEVICE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:26Z
Check the source to verify that this is the current version before use.

FINISH:
BASE: Epoxy resin, Nickel Plated, Mirror-like Polish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
DEVICE: Epoxy resin, 24K Gold Plated, Mirror- like Polish and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT -1:
BASE: 2 inches (REF)
EAGLE DEVICE: 23/32 inch (REF)
LEFT WREATH DEVICE: 1-1/4 inches (REF)
RIGHT WREATH DEVICE: 1-1/4 inches (REF)
HEIGHT -2:
BASE: 1-1/2 inches (REF)
EAGLE DEVICE: 17/32 inch (REF)
LEFT WREATH DEVICE: 15/16 inch (REF)
RIGHT WREATH DEVICE: 15/16 (REF)
THICKNESS -1:
BASE: 0.098 ± 0.010 inch
EAGLE DEVICE: 0.077 ± 0.010 inch
LEFT WREATH DEVICE: 0.086 ± 0.010 inch
RIGHT WREATH DEVICE: 0.086 ± 0.010 inch
OVERALL: 0.180 ± 0.010 inch
THICKNESS -2:
BASE: 0.096 ± 0.010 inch
EAGLE DEVICE: 0.073 ± 0.010 inch
LEFT WREATH DEVICE: 0.086 ± 0.010 inch
RIGHT WREATH DEVICE: 0.086 ± 0.010 inch
OVERALL: 0.172 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device will be three (3) prongs and flat ball clutch.

2. A three prong configuration will be used. Two prongs will be place at the top of the badge 1-1/4 inches apart and one prong 1-1/2 inches ± 1/4 inch below them on the vertical centerline. All prongs will be fused or soldered to the badge.

EPOXY: Epoxy resin shall be applied to the Badge Qualification as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:26Z
Check the source to verify that this is the current version before use.

used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Red	#1
Blue	#18
Black	#26
White	#28

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The regular size badge has 7 stripes on the eagle device (4 white and 3 red).

3. The miniature badge only has 5 stripes on the eagle device. (3 White and 2 Red)

4. The torse above the MIA/POW symbol will alternate white #28 and black #26.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-833)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:26Z
Check the source to verify that this is the current version before use.