NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/292
07 March 2022

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, INSPECTOR GENERAL, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



ASSEMBLED **DEVICE** **BASE**

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (BASE and DEVICE): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
BASE: 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
DEVICE: 24K Gold Plated, Matte Finish Polished Highlights and shall match the TIOH Medal Finish Chip Number 8.

DIMENSIONS:
HEIGHT (Overall):
-1: DEVICE: 1 inch (REF)
BASE: 2 inches (REF)
-2: DEVICE: 3/4 inch (REF)
BASE: 1-1/2 (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: DEVICE: 1-7/16 inches (REF)
BASE: 2 inches (REF)
-2: DEVICE: 1-1/16 inches (REF)
BASE: 1-1/2 inches (REF)
THICKNESS (At thickest point):
-1: DEVICE: 0.080 ± 0.010 inch
BASE: 0.100 ± 0.010 inch
ASSEMBLED: 0.182 ± 0.010 inch
-2: DEVICE: 0.080 ± 0.010 inch
BASE: 0.095 ± 0.010 inch
ASSEMBLED: 0.175 ± 0.010 inch

ATTACHING DEVICE:

1. Attaching device shall have 3 prongs and wing type clutch.

2. For -1, three prongs shall be located on the reverse on an approximate 1-3/4 inch diameter circle. Each prong shall be placed 120 degrees apart with the bottom prong located on the vertical centerline 1/8th inch from the bottom. For -2, three prongs shall be located on the reverse, on an approximate 1-1/4 inch diameter circle. Each prong shall be placed 120 degrees apart with the bottom prong located on the vertical centerline 1/8 inch from the bottom.

3. The device shall be swaged in the 2 areas located on the center base pad and glued for a secure and tight fit.

PIERCING: For the -1, -2 device, the 4 recessed areas inside of the wreath and the area in between the sword handle will be pierced as shown above.

EPOXY: Epoxy resin shall be applied to the Badge as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR CHIP NUMBER	**LOCATIONS**
Blue #18	Letters on device.
Blue #20	Base background.

NOTES:

1: The term (REF) refers to the measurements taken from the Government furnished hub or die.

2: The specification slash sheet for the lapel button is MIL-DTL-11484/445

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-067)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.