NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/295(IH)
9 February 2023

DETAIL SPECIFICATION SHEET

BADGE, SECURITY, DEFENSE HEALTH AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



-1



-2, -3



-4


DEVICE

DASH NO.
-1: Anti-Terrorism
-2: Guard
-3: Guard Supervisor
-4: Physical Security

MATERIAL: Red Brass 85/15 (UNS Alloy No. C230)

FINISH:
-1, -2: Epoxy resin, Nickel Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

-3, -4: Epoxy resin, 24K Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.

DEVICE: Epoxy resin, 24K Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
BASE:
WIDTH: 2-3/16 inches (REF)
HEIGHT: 3-1/16 inches (REF)
THICKNESS (At thickest point): 0.120 ± 0.010 inch
DEVICE:
DIAMETER: 3/4 inch (REF)
THICKNESS (At thickest point): 0.075 ± 0.010-inch
ASSEMBLED THICKNESS: 0.145 ± 0.010 inch

ATTACHING DEVICE:
1: The attaching device shall be a coil type pin with heavy-duty catch.

2: The pin stem shall be 2 inches ± 1/64 inch long.

3: The pin and catch shall be hard soldered or fused on the vertical center line between the top and bottom scrolls.

4: The joint and catch shall be positioned on the same level plane to each other.

Epoxy resin shall not be stoned. Both hard enamel and soft baked enamel may be used at the option of the manufacturer in lieu of epoxy resin. If hard enamel and soft baked enamel are used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210). Epoxy and enamel colors shall conform to TIOH Hard Enamel Chip Numbers listed below:

COLOR AND CHIP NUMBER	LOCATIONS
BASE	
Black #28	Letters on all scrolls
DEVICE	
Red #3	Right side of shield
Blue #18	Left side of shield
White #28	Motto scroll
Blue #33	Globe

DEVICE: (Also see TIOH Drawing B-5-214)

FORCER: A full forcer shall be used to bring up the details of the base design.

DAPPED: The badge shall be dapped to a radius of 5 inches □ 1/4 inch along the horizontal plane.

ENGRAVING: All engraving lettering shall be block font, optically balanced, and shall match the lettering of TIOH master samples:

TOP SCROLL:
-1: “ANTI-TERRORISM” Letters shall be approximately 11/64 inch in height and block style.
-2: "GUARD” Letters shall be approximately 11/64 inch in height and block style.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.

-3: “GUARD SUPERVISOR” Letters shall be approximately 11/64 inch in height and block style.

-4: “PHYSICAL SECURITY” Letters shall be approximately 5/32 inch in height and block style.

SECOND SCROLL:

-1, -2, -3, -4: "DEFENSE HEALTH” Letters already engraved in government furnished die.

THIRD SCROLL:

-1, -2, -3, -4: "AGENCY" Letters already engraved in government furnished die.

BOTTOM SCROLL: (Letters or numbers on the bottom scroll shall be approximately 1/4 inch in height and block style.):

-1, -2, -3, -4: Engraved consecutively as specified in the procurement document for badge number, i.e., "125," "126."

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. TIOH Drawing Number B-5-210, B-5-211, B-5-212, B-5-213 and B-5-214 shall be used as additional reference.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2023-076)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:31Z
Check the source to verify that this is the current version before use.