NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/301A(IH)
30 March 2026
SUPERSEDING
MIL-DTL-3628/301(IH)
19 August 2025

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, MOUNTAINEERING, U.S. ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: Regular Size
-2: Miniature Size
-3: Subdued, Regular Size

MATERIAL (-1thru-3): Red Brass 85/15 (UNS Alloy NO. C-230)

FINISH:

1. -1 and -2: RAM'S HEAD, BAYONET AND ICE AXE: Nickel Plated, Mirror-Like Polish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16. RAM'S HORNS: 24K Gold Plated, Mirror Like Polish and shall match TIOH Metal Finish Chip Number 6.

2. -1 and -2 RAM'S HEAD, BAYONET AND ICE AXE: Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14. RAM'S HORNS: 24K Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:32Z
Check the source to verify that this is the current version before use.

3. -3 Dull Flat Black and shall match TIOH Metal Finish Chip Number 21.

DIMENSIONS:
HEIGHT:
-1: and -3: 1-1/2 inches (REF)
-2: 1 - 1/16 inches (REF)
WIDTH:
-1: and -3: 1-1/2 inches (REF)
-2: 1-1/16 inches (REF)
THICKNESS AT THICKEST POINT:
-1: and -3: 0.135 ± 0.010 inch
-2: 0.119 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be three prongs with wing type clutch.

2. Prongs for -1 and -3 shall be located on the reverse on an approximately 1-inch diameter circle.

3. Prongs for -2 will be approximately 11/16 inches in diameter circle. The prongs shall be positioned approximately 135 degrees clockwise and counterclockwise from the bottom prong's origin located along the vertical center line 1/4 inch from the bottom edge for -1 and -3. 3/16 inch for -2.



Prong Placement Indicators

OBVERSE: The Ram's Head shall be raised and modeled. Ram's horns to be gold-plated. Shaded area to be pierced.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.
2. Piercing shall be as indicated above in the shaded area.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:32Z
Check the source to verify that this is the current version before use.

inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-237)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:32Z
Check the source to verify that this is the current version before use.