INCH-POUND

MIL-DTL-55302/7D
3 February 2003
SUPERSEDING
MIL-C-55302/7C
12 December 1979

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, PIN CONTACTS, RIGHT-ANGLE, FOR MULTILAYERED PRINTED WIRING BOARDS (.100 SPACING)

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-55302.



FIGURE 1. Connectors, plug (.100 spacing).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.



TYPICAL HOLE GRID LAYOUT
COMPONENT SIDE

TABLE 1. Dimensions and dash numbers.

Dash no.	No. of contacts	A	B basic	C ref	D ref
01	13	.800 ± .005	.600	.300	.400
02	25	1.200 ± .005	1.000	.700	.800
03	37	1.600 ± .005	1.400	1.100	1.200
04	49	2.000 ± .008	1.800	1.500	1.600
05	61	2.400 ± .008	2.200	1.900	2.000

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.002	0.05	.039	0.99	.187	4.75	.400	10.16	1.600	40.64
.004	0.10	.044	1.12	.200	5.08	.600	15.24	1.800	45.72
.005	0.13	.050	1.27	.202	5.13	.700	17.78	1.900	48.26
.007	0.18	.055	1.40	.208	5.28	.800	20.32	2.000	50.80
.008	0.20	.059	1.50	.300	7.62	1.000	25.40	2.200	55.88
.009	0.23	.065	1.52	.340	8.64	1.100	27.94	2.400	60.96
.012	0.30	.069	1.65	.345	8.76	1.200	30.48		
.026	0.66	.070	2.01	.350	8.89	1.400	35.56		
.028	0.71	.080	2.03	.355	9.02	1.500	38.10		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .005 (0.13 mm) on three place decimals and ± 2° on angles.
4. These connectors mate with connectors specified in MIL-DTL-55302/8 and are primarily for use with multilayered printed wiring boards.
5. Positional tolerances of guide pins shall apply at datum plane X.
6. Pad(s) suitable for printed circuit board support are required. Dimensions and location(s) are optional.
7. The terminating side and the side opposite mating face of the plug may be open or solid construction.

FIGURE 1. Connectors, plug (.100 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Material:

Guide pins and guide bushing: Brass composition B, 60,000 to 70,000 PSI tensile, as specified in ASTM B134, or FC brass as specified in ASTM B16, or stainless steel in accordance with ASTM A484 and ASTM A582, passivated in accordance with SAE-AMS-QQ-P-35.

Plating:

Guide pins and guide bushings: Gold over copper, type II, class 1.27, grade C, as specified in ASTM B488.

Contact: Gold in accordance ASTM B488, type II, grade C, class 1.27, over nickel plating in accordance with SAE-AMS-QQ-N-290, class 2, 50 to 150 microinches.

Contact identification: Shall be alphabetical and sequential in the pattern indicated.

Pin size: 23.

Wire size: 22.

Current rating: 5 amperes, maximum.

Mating and unmating: The maximum insertion force, in pounds shall not exceed a value equal to 0.5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of 0.11 times the number of contacts, and shall not exceed the measured insertion force.

Contact resistance: The average resistance of all contact pairs measured shall not exceed .010 ohm, and no individual contact pair shall have a resistance exceeding .020 ohm.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 60 Hz, ac.
High altitude: 500 volts rms, 60 Hz, ac.

Part or Identifying Number (PIN): M55302/7-(dash number from figure 1).

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AT, AV
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5935-4411-006)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.