MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
50 OHMS, M17/155-00001

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Components	Construction details
Inner conductor	Nineteen strands of tinned copper wire, each strand 0.0072 inch diameter. Overall diameter: 0.0355 inch ±0.0020.
Dielectric core	Type A-1: Solid polyethylene. Diameter: 0.116 inch ±0.004.
Outer conductor	Single braid of AWG #36 tinned copper wire. Diameter: 0.150 inch maximum. Coverage : 92.8% nominal — Alternate: 94.2% nominal Carriers : 12 — Alternate: 16 Ends : 9 — Alternate: 7 Picks/inch: 7.7 ±10% — Alternate: 10.3 ±10%
Jacket	Type IIa: PVC. Diameter: 0.195 inch ±0.004.

CAUTION IS DIRECTED TO THE APPLICATION OF THIS CABLE ABOVE 400 MHZ. ATTENUATION IS TESTED ONLY AT 400 MHZ. SRL AND POWER HANDLING CAPABILITIES ARE NOT STIPULATED HEREIN.

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 202610-15T16:20Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Continuous working voltage: 1,400 Vrms, maximum.

Velocity of propagation: 65.9 percent, nominal.

Operating temperature range: -40° to +85°C.

Inner conductor properties:

DC resistance (maximum at 20°C): 1.480 ohms per 100 feet.

Elongation: 20 +2.5, -0.0 percent.

Tensile strength: Not applicable.

Engineering note: This cable is useful in general purpose low temperature applications. (See connector series "TNC", "BNC", and "SMA" per MIL-C-39012.)

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1 and table I.

Environmental and mechanical:

Visual and mechanical examination: Applicable.

Out-of-roundness: Not applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 5 pounds, minimum; 15 pounds, maximum.

Aging stability: +98° ±2°C.

Stress crack resistance: Not applicable.

Outer conductor integrity: Not applicable.

Cold bend: Not applicable.

Dimensional stability: +85° ±2°C.

Inner conductor from core: 0.062 inch, maximum.

Inner conductor from jacket: 0.125 inch, maximum.

Contamination: Applicable.

Bendability: Not applicable.

Flammability: Not applicable.

Weight: 0.031 pound per foot, maximum.

Electrical:

Continuity: Applicable.

Spark test: 5,000 Vrms, minimum.

Voltage withstanding: 5,000 Vrms, minimum.

Insulation resistance: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:20Z
Check the source to verify that this is the current version before use.

Corona extinction voltage: 1,900 Vrms, minimum.

Characteristic impedance: 50 ±2 ohms.

Attenuation: 17.0 dB/100 ft maximum at 400 MHz.

Structural return loss: Not applicable.

Capacitance: 30.8 pF per foot, nominal.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.

Transmission unbalance: Not applicable.

Phase stability: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

Part number: See table II.

Supersession data: See table II.

TABLE II. Cross reference of part number.

Part number	Superseded part number
M17/155-00001	RG-58C/U per MIL-C-17D

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AT, ME
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0814-1)

☆U.S. GOVERNMENT PRINTING OFFICE: 1982—668-022/1360

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:20Z
Check the source to verify that this is the current version before use.