MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, 50 OHMS, M17/175-00001

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Component	Construction details
Inner conductor	Nineteen strands of silver-coated, copper wire at .008 inch each. Overall diameter: 0.0384 inch ±.0010.
Dielectric core	Type F-1: Solid extruded PTFE. Diameter: .116 inch ±.005.
Outer conductor	Double braid of AWG No. 36 silver-coated wire. Diameter: .171 inch maximum.
Inner braid	Coverage : 94.8% nominal Carriers : 16 Ends : 7 Picks/inch: 11.5 ±10%
Outer braid	Coverage : 93.6% nominal Carriers : 16 Ends : 7 Picks/inch: 14.5 ±10%
Jacket	Type IX: FEP. Diameter: .195 inch ±.005.

CAUTION IS DIRECTED TO THE APPLICATION OF THIS CABLE ABOVE 400 MHZ. ATTENUATION IS TESTED ONLY AT 400 MHZ. SRL AND POWER HANDLING CAPABILITIES ARE NOT STIPULATED HEREIN.

FSC 6145

(B) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:24Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Continuous working voltage: 1,400 V rms, maximum.

Velocity of propagation: 69.5 percent, nominal.

Operating temperature range: -55°C to +200°C.

Inner conductor properties:

DC resistance (maximum at 20°C): 0.91 ohm per 100 feet.

Elongation: 10 percent, minimum.

Tensile strength: Not applicable.

Engineering note: This cable is useful in general purpose, high temperature applications. (See connector series "TNC", "BNC", and "SMA" per MIL-C-39012.)

REQUIREMENTS:

Dimensions, configuration, and description: See figure 1 and table I.

Environmental and mechanical:

Visual and mechanical inspection:

Out-of-roundness: Not applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 4 pounds, minimum; 30 pounds, maximum.

Aging stability: Not applicable.

(B) Stress crack resistance: +230°C ±5°C; mandrel size 5 times the jacket diameter.

Outer conductor integrity: Not applicable.

(B) Cold bend: -55°C ±2°C.

Dimensional stability: +200°C ±5°C.

Inner conductor from core: 0.187 inch, maximum.

Inner conductor from jacket: 0.312 inch, maximum.

Contamination: Not applicable.

Bendability: Not applicable.

Flammability: Applicable.

Weight: 0.05 pound per foot, maximum.

Electrical:

Continuity: Applicable.

(B) Spark test: 2,000 V rms, +10, -0%.

(B) Voltage withstanding: 3,000 V rms, +10%, -0%.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:24Z
Check the source to verify that this is the current version before use.

Insulation resistance: Not applicable.

Corona extinction voltage: 1,900 V rms, minimum.

Characteristic impedance: 50 ohms ±2.

Attenuation: 10.5 dB/100 feet maximum at 400 MHz.

Structural return loss: Not applicable.

Capacitance: 32 pF per foot, maximum.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.

Transmission unbalance: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

Part number: See table II.

Supersession data: See table II.

TABLE II. Cross-reference of part number.

Part number	Superseded part number or type designation
M17/175-00001	RG-400 per MIL-C-17D

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH, TD
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0911-47)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:24Z
Check the source to verify that this is the current version before use.