INCH-POUND

MIL-W-5086/3B
AMENDMENT 1
16 October 1998

MILITARY SPECIFICATION SHEET

# WIRE, ELECTRICAL, POLYVINYL CHLORIDE INSULATED PVC-GLASS-PVC-NYLON, TIN COATED COPPER CONDUCTOR, 600 VOLT, 105 °C

This amendment forms a part of MIL-W-5086/3B, dated 23 November 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Thermal Shock requirement, maximum change in measurement, delete and substitute: "The maximum shrinkage permitted for PVC insulation is .060 inch. Sizes 8 through 0000 gauge wire is permitted to have the polyamide insulation layer shrink .125 maximum.

Surface resistance, first sentence: Delete.

Non-use and replacement of MIL-W-5086/3 in aerospace applications statement: Delete and substitute: "Cable or wire with polyvinyl chloride insulation shall not be used in aerospace applications."

PAGE 4

International Standardization Agreement: Delete "STANAG 3317."



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:16Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – AS
Air force – 85

Review:
Army – AR, AT, AV, CR4, MI
Navy – EC, MC, OS, SH
Air Force - 11

Preparing activity:
Navy – AS
(Project 6145-2173-02)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:16Z
Check the source to verify that this is the current version before use.