MIL-E-23155B(SHIPS)
AMENDMENT 2
14 September 1981
SUPERSEDING
AMENDMENT 1
12 October 1964

MILITARY SPECIFICATION

ESCAPE APPLIANCE, HOODED, AIR INFLATABLE, WITH POUCH, SUBMARINE PERSONNEL

This amendment forms a part of Military Specification MIL-E-23155B(SHIPS), dated 9 March 1964, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, under "SPECIFICATIONS, FEDERAL": Add:

"MMM-A-139 - Adhesive, Natural or Synthetic-Natural Rubber."

* 2.1, under "SPECIFICATIONS, MILITARY": Delete reference to "MIL-C-5539 - Cement, Natural Rubber."

PAGE 3

* 3.3.12, line 4: Delete "type C of MIL-C-5539." and substitute "class 3, form B of MMM-A-139."

* 3.3.13: Delete and substitute:

"3.3.13 Snorkel valve. Each escape appliance shall be provided with a snorkel valve and a hood relief valve conforming to 608-1895223."

PAGE 6

~~* 4.3.1: Delete and substitute:~~

"4.3.1 Preproduction test samples shall be forwarded to the Commander, David Taylor Naval Ship Research and Development Center, Code 2843, Annapolis, MD 21402, plainly identified by securely attached durable tags marked with the following information:

(a) Sample for preproduction test.
(b) Name of product, together with complete identifying data such as Manufacturer's designation number.
(c) Name of manufacturer.
(d) Contract or order number."

FSC 4220

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:43Z
Check the source to verify that this is the current version before use.

4.5, line 12: Delete "6 samples per 100" and substitute "6 samples per 1000"; line 13, delete "Oral inflation tube (valve adhesion) - 6 samples per 100" and substitute "Oral inflation valve adhesion - 6 samples per 1000".

PAGE 9

4.10.4: Add "and shall close at not less than 1 p.s.i."

4.10.7, line 1: Delete "installed within" and substitute "clamped in".

PAGE 10

* 4.10.11: Delete and substitute:

"4.10.11 Hood leakage. With the slide fastener sealed with tape, seal off the snorkle and the hood relief valve to prevent water leakage. Fill the hood with water up to but not including the slide fastener, and allow to stand for 5 minutes. There shall be no evidence of leakage at the end of the test."

PAGE 12

FIGURE 1: Delete.

NOTE: The margins of this amendment are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4220-N283)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:43Z
Check the source to verify that this is the current version before use.