MILITARY SPECIFICATION

METER, FREQUENCY, EXPANDED SCALE SWITCHBOARD TYPE

(NAVAL SHIPBOARD USE)

This amendment forms a part of Military Specification MIL-M-23167B(SHIPS), dated 29 December 1969.

PAGE 4

3.14: Delete and substitute:

"3.14 Shock (high-impact). When tested in accordance with 4.3.15, no screws, bearings, pivots, windows or other parts shall become loosened, cracked (except as specified hereinafter), or unduly damaged. Minor cracking or distortion of pivots will be permissible only when conformance to the post shock performance has been demonstrated. Cracking of glass windows is permissible only when readability of the complete scale is retained and no fragment has become dislodged. The permanent change in indication based on claibration made after resetting the pointer to zero shall not exceed the value specified in 3.19."

PAGE 8

4.3.15, last sentence: Delete "(see table I)" and substitute " then disassembled and examined for damage (see 3.14)."

PAGE 9

6.3: In line 3, delete "suppliers" and substitute "contractors" and in lines 7 and 8, delete "Prince George's Center, Center Building, Hyattsville, Maryland 20782" and substitute "Department of the Navy, Washington, DC 20362".

Preparing activity:
Navy - SH
(Project 6625-N739)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:45Z
Check the source to verify that this is the current version before use.