MILITARY SPECIFICATION

NETWORK, PULSE FORMING, RADAR, TYPE PN3E202C262Q500

This amendment forms a part of Military Specification MIL-N-23182/1A, dated 25 June 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Shock (medium impact): Delete in its entirety and substitute the following:

"Shock (specified pulse):
Method 213, test condition H of MIL-STD-202.
The following details and exceptions shall apply:
Method of mounting: By normal means.
Number and direction of applied shocks: 30 impact shocks,ten in of three mutually perpendicular planes.
After the test, units shall be examined for evidence of physical or mechanical damage. In addition, units shall be subjected to and shall comply with requirements, at standard test conditions, for corona discharge, dielectric withstanding voltage, barometric pres: (reduced), insulation resistance, and capacitance."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - SH, YD
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - MI, SM
Navy - MC, AS, OS
Air Force - 19

Preparing acti
Navy - EC

Agent:
DLA - ES

(Project 5915-

FSC 5915

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:46Z
Check the source to verify that this is the current version before use.