MILITARY SPECIFICATION

INFLATION ASSEMBLIES, LIFE PRESERVER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for three types of life preserver inflation assemblies and three different styles of lanyards,

1.2 Classification. The life preserver inflation assemblies and lanyards shall be of the following types and styles, as specified (see 6.2,1):

Type	Lanyard style	Application
I	1	MIL-C-601 cylinders.
11	1, 2 or 3	MIL-C-25369, type II or III cylinders.
III	1 or 3	Dual inflator, MIL-C-601, type I or II cylinders.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-349	Plastic Molding and Extrusion Material, Cellulose Acetate Butyrate.
BB-C-1OI	Carbon Dioxide (C02) Technical and USP.
QQ-A-591	- Aluminum Alloy Die Castings.
QQ-P-416	- Plating, Cadmium (Electrodeposited).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering center Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter,

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T15:42Z
Check the source to verify that this is the currentversion before use.

QQ-S-763	Steel Bars, Shapes and Forgings, Corrosion Resisting.
QQ-W-423	Wire, Steel, Corrosion-Resisting.
PPP-B-566	Boxes, Folding, Paperboard,
PPP-B-636	Boxes, Shipping, Fiberboard.
PPP-B-676	Boxes, Set-up.
PPP-C-843	Cushioning Material, Cellulosic.
PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

MILITARY

MIL-P-116	Preservation-Packaging, Methods of.
MIL-C-601	Cylinders, Carbon Dioxide Filled, Technical.
MIL-C-5040	Cord, Nylon.
MIL-R-6855	Rubber, Synthetic, Sheets, Strips, Molded or Extruded Shapes.
MIL-I-6869	Impregnates for Aluminum Alloy and Magnesium Alloy Castings,
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys,
MIL-S-8660	Silicone Compound.
MlL-P-19834	Plates, Identification, Metal Foil, Adhesive Backed.
MIL-C-25369	Cylinder, Carbon Dioxide, for Inflation of Pneumatic Life Preservers.

STANDARDS

FEDERAL

FED-STD-151	Metals, Test Methods.
FED-sTD-H28	Screw Thread Standards for Federal Services.

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of U.S. Military Property.

AIR FORCE - NAVY AERONAUTICAL

AN6227 Packing, “O” Ring Hydraulic

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

62A120H1	- Manifold Stem Assembly and Details, for Life Preservers.
975AS121	- Handle, Beaded, Inflation, Life Preserver.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the acquiring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2,1c) the contractor shall furnish sample units for first article inspection and approval (see 4.3 and 6.3).

3.2 Materials and components. Materials and components shall conform to the applicable specifications and drawings as listed or required herein. Unless otherwise specified, the manufacturer shall certify that the materials and components, except for the metallic parts used in the construction of the life preserver inflation assemblies, shall have been manufactured not more than 18 months prior to the date of delivery of the inflation assemblies (see 6.2.2).

3.3 Design and construction. The design and construction of the life preserver inflation assemblies shall be in accordance with figures 1 through 10, as applicable, and applicable drawings.

3.3.1 General design requirements, The life preserver inflation assemblies shall be designed to be compatible with the manifold stem assemblies conforming to Drawing 62A120H1. The inflation assemblies shall consist of a body, with a seat seal gasket (for use with the designated carbon dioxide filled cylinder), two manifold stem gaskets, an internal retractable piercing pin, having an “O” ring and a spring. The assemblies shall also be provided with an outlet having two gas passages, an external actuating lever and a lanyard assembly used for activation of the inflation assembly. “The opening in the body shall contain a chamfered portion and shall be designed to permit the top area of the carbon dioxide filled cylinder to seat firmlY against the metal seat of the body. The metal seat shall be smooth, flat and perpendicular to the threads. When not in operation, the lever of the inflation assembly shall rest firmly against the side of the inflation assembly body as shown in figures 1 and 4.

3.3.2 Specific design and construction requirements.

3.3.2.1 Inflation assembly body. The inflation assembly body shall be constructed with a high pressure aluminum die casting conforming to QQ-A-591, alloy A380. The body shall be anodized in accordance with MIL-A-8625, type II class 1 and then impregnated in accordance with MIL-I-6869. The body shall have two gas passages and an outlet for mounting on the manifold stem assemblies conforming to Drawing 62A120H1. One of the gas passages in the outlet shall be aligned with the opening in the side of the manifold stem. Each inflation body shall be threaded

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

with cold rolled internal threads as specified in figures 1 and 4. The threads shall be lightly coated with silicone grease conforming to MIL-S-8660.

3.3.2.2 Gaskets, All gaskets shall be fabricated from synthetic rubber conforming to MIL-R-6855, class 2, grade 80 (type optional).

3.3.2.2.1 Manifold stem gasket. The manifold stem shall be provided with two gaskets, one each for the top and bottom of the manifold stem, The top gasket shall be positioned between the body outlet and the cap nut conforming to Drawing 62A120H1-9, The bottom gasket shall be positioned between the body outlet and the manifold stem conforming to Drawings 62A120H1-1 or 62A120H1-2, as applicable. The location and dimensional requirements for the top and bottom gaskets shall be as specified in figure 10,

3.3.2.2.2 Seat seal gasket. The seat seal gasket shall be positioned on the metal seat of the body. The top area of the carbon dioxide filled cylinder shall seat firmly against the upper surface of the seat seal gasket. The seat seal gaskets shall conform to figures 1 or 4, as applicable.

3.3.3 Screw threads. The screw threads shall conform to FED-STD-H28 and the requirements specified in figures 1 through 5.

3.3.4 Piercing pins. The piercing pins shall be fabricated with hardened steel, cadmium plated in accordance with QQ-P-416, type II, class 2. The pins shall have a smooth machine finish, free from tool or chatter marks. They shall be constructed to move in a straight line when activated and shall not waver from side to side. Upon activation, the pins shall retract to their original position. The detail construction of the piercing pins shall be as specified in figures 3 and 7, as applicable.

3.3.4.1 Piercing pin point (for type I and type III). The point of the piercing pin for the type I and type III inflation assemblies shall have four flats. The normal position of the point shall be a minimum of 0.005 inch below the surface of the metal seat of the body.

3.3.4.2 Piercing pin point (for type II). The point of the piercing pin for the type II inflation assemblies shall have four flats. The normal position of the point shall be a minimum of 0.10 inch below the surface of the metal seat of the body.

3.3.4.3 Packing, “O” ring. The top portion of the piercing pin shall contain an “()” ring conforming to AN6227-1 which shall be installed as shown in figures 1 and 4.

3.3.4.4 Spring. The piercing pin shall be supported by a corrosion resistant spring fabricated from wire conforming to QQ-W-423, form I, composition 302, condition B. The diameter of the wire shall be 0.028 inch. The spring shall be positioned around the piercing pin as shorn in figures 1 and 4. The ends of the spring shall be squared and ground.

3.3.5 Lever. The lever shall be fabricated from hardened steel having a case depth of 0.010. The steel shall be cadmium plated in accordance with QQ-P-416, type II, CbSS 2. The lever shall be securely held in position by a grooved taper pin as specified in figures 1 and 4. When not in operation, the lever shall rest against the inflation assembly body.

Source: https://assist.dla.mil - Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

3.3.5.1 Grooved taper pin, The grooved taper pin shall be fabricated from corrosion resistant steel conforming to QQ-S-763, class 302, condition A and shall conform to figure 6.

3.3.6 Lanyard assemblies,

3.3.6.1 Style 1 and 2 lanyard assemblies, The style 1 and 2 lanyard assemblies shall consist of a continuous length of braided nylon cord conforming to MIL-C-5040, type I (color optional), a plastic knob, and two or three commercial grade brass clips, as required, The knob shall be fabricated from plastic material conforming to L-P-349, grade H, class optional, black in color. The knob shall be constructed as shown in figure 2. The cord shall be looped through the hole at the end of the lever so that equal lengths extend on each side. The clips shall be 0.023 + 0.003 inch in thickness and 3/8 + 1/32 inch in length.

3.3.6.1.1 Style 1. The style 1 lanyard assembly shall be as specified in 3.3.6.1. In addition, the two free ends of the cord shall be inserted through the holes in the knob, one end through each hole and shall be tied securely together with a sheet bend knot. Two brass clips, as specified in 3.3.6.1, shall be crimped around the looped cord, one adjacent to the knob and the other adjacent to the lever, to hold the looped cord together. The assembled style 1 lanyard shall conform to figure 2.

3.3.6. 1.2 Style 2. The style 2 lanyard shall be as specified in 3.3.6.1. In addition, the style 2 lanyard assembly shall contain a nylon release pin and three brass clips as specified in 3.3.6.1. The release pin shall be fabricated from nylon and shall conform to figure 6. The nylon cord shall be threaded through the hole in the lever. One end of the specified nylon cord, extending from the lever, shall be adjusted to the desired length as specified in figure 6. The longer end of the cord. shall then be threaded through one hole in the knob (see figure 6) looped through the second hole in the knob, and subsequently looped through the eye of the release pin as shown in' figure 6. The free ends of the cord shall then be inserted through the holes in the knob, respectively, and securely tied together with a sheet bend knot. The cut ends of the cord shall be seared and no sharp edges shall be formed. The three brass clips shall be crimped around the looped cord, one adjacent to the lever, one adjacent to the release pin, and one adjacent to the knob to hold the looped cord together. The configuration for the style 2 lanyard assembly shall conform in its entirety to figure 6.

3.3.6.2 Style 3 lanyard assemblies. The style 3 lanyard assemblies shall be as specified in Drawing 975AS121.

3.4 Performance characteristics.

3.4,1 Rockwell hardness. The piercing pin and lever, when inspected as specified in 4.6.2, shall have a core Rockwell hardness of C30 to C35.

3.4.2 Weight. The weight of the inflation assemblies, when inspected as specified in 4.6.4, shall not exceed 40 grams for the type I assembly, 55 grams for the type II assembly and 60 grams for the type III assembly.

3.4.3 Leakage.

Source: https://assist.dla.mil -- Downloaded: 2026t0-19T15:42Z
Check the source to verify that this is the currentversion before use.

3.4.3.1 At 40 psig The inflation assembly, when inspected as specified in 4.6.5.1, shall show no evidence of leakage. This inspection shall be conducted in sequence with 3.4.3.2. Upon completion of this inspection, the inflation assembly shall be inspected for conformance to leakage at 2 psig, 3.4.3.2.

3.4.3.2 At 2 psig. The inflation assembly, when inspected as specified in 4.6.5.2, shall show no evidence of leakage. In addition, the inflation assembly shall not show any evidence of material or mechanical failure.

3.4.4 Operating force. The inflation assemblies, when inspected as specified in 4.6.6 without the carbon dioxide filled cylinder, shall require a load of not more than 2.0 pounds for effective operation. The assembly shall not be safety wired, The lever shall travel through one normal cycle. The piercing pin shall move in a straight line, shall not waver from side to side, shall advance to its maximum point of travel, and shall retract to its original position.

3.4.5 Piercing pin and lever.

3.4.5.1 Position and travel. The piercing pin, when inspected as specified in 4.6.7, shall perform as specified herein. The normal position of the piercing pin point for the type I and type III assembly shall be as specified in 3.3.4.1. The point of the piercing pin shall travel 0.100 to 0.130 inch beyond the surface of the metal seat of the body. The normal position of the piercing pin point for the type 11 assembly shall be as specified in 3.3,4.2. The point of the piercing pin shall travel 0.090 to 0.120 inch beyond the surface of the seat seal gasket. In both cases, the piercing pin point shall be capable of puncturing the carbon dioxide filled cylinder. The lever shall travel through an arc not greater than 115 degrees in line with the longitudinal axis of the body. The piercing pin shall move in a straight line, shall not waver from side to side, and shall retract to its original position.

3.4.5.2 Dimensions of piercing pin and lever. The dimensions of the piercing pins for the types I and 111 and type II inflation assemblies, when inspected as specified in 4.6.1 and table II, shall conform to figure 3 and figure 7, respectively. The dimensions for the types I and III and type 11 levers shall conform to figures 1 and 4, respectively.

3.4.6 Operation. The inflation assembly, when inspected as specified in 4.6.8, shall not permit the piercing pin to make any contact with the sealing cap area of the cylinder prior to activation of the lever. The cylinder shall not be punctured nor shall indentation be made. The lever shall not be safety wired. Upon activation of the lever, the piercing pin shall completely operate, and shall advance to its maximum point of travel. The piercing pin shall pierce the center of the punctu-rable area of the installed carbon dioxide cylinder. The piercing pin shall not stick in the cylinder but shall retract to its original position. The gas in the cylinder shall be released into the atmosphere immediately upon activation and shall not be restricted in any manner. The piercing pin shall not obstruct or retard the flow of carbon dioxide gas in any way, and the gas shall not pass through any part of the inflation assembly into the atmosphere other than through the passages in the outlet.

3.4.7 Hydrostatic pressure. The life preserver inflation assembly, when in-spected as specified in 4.6.9, shall not deform or leak. The internal hydrostatic pressure applied shall be 1500 psig.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

3.4.8 Breaking strength of lanyard assembly. The lanyard assembly, when inspected as specified in 4.6.10, shall not break off or fail under a load of less than 70 pounds.

3.4.9 Salt spray, The life preserver inflation assembly, when inspected as specified in 4.6.11, shall show no evidence of corrosion or damage which adversely affects the operation of the assembly. The lever and piercing pin shall not become frozen and shall operate freely. Following the salt spray test, the inflation assembly shall be inspected for conformance to the requirements of 3,4.6.

3.5 Markings. Each inflation assembly shall be marked with legible, durable and sharply defined letters and numerals. The markings shall be molded characters conforming to MIL-STD-130 or inscribed on metal foil identification plates conforming to MIL-P-19834, type I, and shall be as follows:

INFLATION ASSEMBLY, LIFE PRESERVER
MIL-I-23145B
Contract no.
Manufacturer's name or trademark and part number
Date of manufacture (month and year)

3.6 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with respect to installation and performance.

3.7 Workmanship. The inflation assemblies shall not be misaligned, deformed nor contain any rough surface, nick, burr, sharp edge) crack, embedded foreign matter? detached or loose component, mend, spot, stain, corrosion or scale, pit or dent. The inflation assemblies shall be uniform in quality and free from any mechanical or other irregularities or defects which could adversely affect performance, reliability or durability. The life preserver inflation assemblies shall conform to the quality and grade of product established by this specification, The occurrence of defects shall not exceed the acceptance criteria established herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inpection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection. First article inspection consists of examinations and tests performed on samples which are representative of the production item after award of a contract to determine that the production item meets the requirements of this specification (see 3.1 and 4.3 through 4.3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

b. Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots to the requirements set forth in this specification (see 4.4 through 4.4.1.2).

4.3 First article,

4.3.1 First article samples. Unless otherwise specified, as soon as practicable after the award of the contract or order, the manufacturer shall submit twelve inflation assemblies. The samples shall be representative of the construction, workmanship, components, and materials to be used during production. When a contractor is in continuous production of these inflation assemblies from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the acquiring activity (see 6.2. 1c). Approval of the first article samples or the waiving of the first article inspection does not preclude the requirements for performing the quality conformance inspection. The first article samples shall be forwarded as specified in the contract or order (see 6.2. 1d).

4.3.1.1 First article sample approval. Upon completion of the first article inspection program, recommendations and comments pertinent for use in monitoring production will be forwarded by the Government activity responsible for the inspection program (see 6.2.1d) to the contracting officer. Two of the approved first article inspection sample assemblies will be returned to the manufacturer for use in monitoring production. The other ten will be destroyed in the first article inspection and shall not be considered as part of the quantity to be delivered under the contract.

4.3.2 First article inspection. The first article inspection Of the life Preserver inflation assemblies shall consist of the examination and tests specified in table I.

4.4 Quality conformance inspection. The sampling and inspection levels shall conform to MIL-STD-105. The quality conformance inspection shall consist of the following examinations and tests:

Dimensional check of the piercing pins
Visual examination of the inflation assemblies
Dimensional check of the inflation assemblies
Weight
Leakage at 40 psig
Leakage at 2 psig
Piercing pin position and travel and lever operation
Operation with carbon dioxide filled cylinder
Hydrostatic pressure
Packaging

4.4.1 Sampling.

4.4.1.1 Inspection lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

4.4. 1.1.1 Piercing pins. An inspection lot size shall be expressed in units one piercing pin, unfinished (without cadmium plating), for one type of inflatio. assembly, made essentially under the same conditions and from the same materials The sample unit shall be one piercing pin, unfinished (without cadmium plating), representing one type of inflation assembly.

4.4. 1.1.2 Inflation assemblies. An inspection lot size shall be expressed in units of one inflation assembly of one type made essentially under the same conditions and from the same materials and components. The sample unit shall be one inflation assembly of one type.

4.4.1. 1.3 Packaging, An inspection lot size shall be expressed in units of one fully prepared shipping container, containing inflation assemblies of one type, fully prepared for delivery from essentially the same materials and components. The sample unit shall be one shipping container, containing inflation assemblies of one type, fully prepared for delivery except that it need not be sealed.

4.4.1.2 Sampling for examinations and tests of the inflation assemblies and packaging. The sample size, acceptance criteria, examinations and tests required for the inflation assemblies and packaging shall be as specified in table II.

4.5 Inspection conditions.

4.5.1 Atmospheric conditions. Unless otherwise specified, all the inspections set forth by this specification shall be conducted at an atmos heric pressure of 28 to 32 inches of mercury and at a temperature of 25° + 10°C (77 g + 18°F).

4.5.1.1 Inflation assembly. When the inflation assemblies are inspected at atmospheric pressures or temperatures other than specified in 4.5.1, proper corrections shall be made for the change in instrument readings,

4.5.1.2 Lanyard assemblies. The lanyard assemblies shall be inspected under standard atmospheric conditions of a temperature of 21 + 2°c (70° + 2°F) and a relative humidity of 65 + 2 percent.

4.5.2 Moisture equilibrium. Moisture equilibrium is considered to have been reached when, after free exposure of the material to air in motion controlled at standard atmospheric conditions as defined in 4.5.1.2, and change in weight in successive weighings made at intervals of 1 hour is no greater than 0.25 percent.

4.5.3 Installation of cylinders.

4.5.3.1 Carbon dioxide filled cylinders. When use of a carbon dioxide filled cylinder is specified in an inspection, the filled carbon dioxide cylinder shall conform to MIL-C-601 or MIL-C-23569 (type 11 or III) and shall be charged with carbon dioxide conforming to BB-C-101, grade B, type 1. The cylinder shall be installed in the inflation assembly, by hand tightening, and shall not make contact with the point of the piercing pin.

Source: https://assist.dla.mil -- Downloaded: 2026t0-19T15:42Z
Check the source to verify that this is the currentversion before use.

4.5.3.2 Empty carbon dioxide cylinders. Unless otherwise specified, the discharged carbon dioxide cylinders conforming to 4.5.3.1, required in conjunction with the leakage and hydrostatic pressure inspections, shall be held firmly in a vise and the inflation assembly shall be tightened to a maximum Of 20 inch pounds for the type I and III inflation assemblies and a maximum of 30 inch pounds for the type II assembly.

4.6 Inspection methods.

4.6.1 Dimensional check of the piercing pins. Each of the piercing pins representing one type inflation assembly, selected as a sample unit from the lot, shall be thoroughly checked dimensionally, by use of any suitable measuring device, to determine conformance to this specification. The list of defects, table 111, shall be used to enumerate the defects found.

4.6.2 Rockwell hardness. The Rockwell hardness of the piercing pin and lever, as applicable, shall be determined in accordance" with FED-STD-151, method 243, hardness scale C. At least three hardness determinations shall be made on the piercing pin and lever, as applicable. For the piercing pin, the hardness shall be determined at the head, center and near the point. For the lever, the hardness shall be determined on the flat side that is near the portion which makes contact with the head of the piercing pin. The hardness shall be determined at a minimum distance of 1/4 inch apart . The three hardness determinations for each piercing pin and lever, as applicable, shall be averaged.

4.6.3 Visual examinations.

4.6.3.1 Inflation assemblies. Every inflation assembly shall be examined visually for major defects to determine conformance to this specification. Each inflation assembly, selected as a sample unit from the lot, shall be examined visually for minor defects and thoroughly checked dimensionally to determine conformance to this specification. The classification and list of defects, tables IV and V shall be used to classify and enumerate the defects found.

4.6.3.2 Packaging. Each of the fully prepared shipping containers, containing inflation assemblies, selected as a sample unit from the lot, shall be examined visually to determine that the packaging, packing and marking conform to this specification. The list of defects, table VI, shall be used to enumerate the defects found.

4.6.4 Weight. The weight of the inflation assembly shall be determined on any scale or balance capable of weighing to the nearest 0.1 of a gram.

4.6.5 Leakage.

4.6.5.1 40 psig. An applicable discharged carbon dioxide cylinder shall be installed in the inflation assembly as specified in 4.5.3.2. The lever shall be in the actuated position during this inspection. The actuated position is considered to be the position of' the lever after the piercing pin has punctured the carbon dioxide filled cylinder as specified in 4.6,8. The inflation assembly shall be immersed in water and air pressure of 40 psig, free of oil and condensed water vapor, shall be applied at the outlet of the inflation assembly for a minimum of 10 seconds. While the pressure is applied, the inflation assembly shall be

Source: https://assist.dla.mil - Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

observed for leakage. Upon completion of this inspection, the pressure shall be reduced to zero and the inflation assembly shall be subjected to the 2 psig leakage inspection, 4.6.5.2.

4.6.5.2 2 psig. An applicable discharged carbon dioxide cylinder shall be inserted in the inflation assembly as specified in 4.5.3.2. The lever shall be in the unoperated position. The inflation assembly shall be immersed in water and air pressure of 2 psig, free of oil and condensed water vapor, shall be applied at the outlet of the inflation assembly for a minimum of 10 seconds, While the pressure is applied, the lever shall be slowly moved through at least one complete normal operation and the inflation assembly shall be observed for leakage. Upon completion of this inspection, the inflation assemblies shall be dried without the application of heat.

4.6.6 Operating force. For this inspection, no carbon dioxide cylinder is required. The inflation assembly shall be held in a vertical position, with the opening at the top, or in a horizontal position, with the lever on the bottom. The lever shall be in the normal position and a maximum load of 2 pounds shall be attached to the free end of the lever. The load shall operate the lever through one normal cycle and the travel, movement and motion of the piercing pin shall be observed for conformance to 3.4.5.1".

4.6.7 Piercing pin position and travel and lever operation. An accurately calibrated suitable measuring device shall be used to determine the requirements of 3.4.6. If desired, the seat seal gasket may be removed for this inspection. During this inspection, the movement and motion of the piercing pin shall also be observed for conformance to 3.4.5.1.

4.6.8 Operation. For this inspection, a carbon dioxide filled cylinder conforming to MIL-C-601 or MIL-C-25369, type II or III, as applicable, shall be fully installed in the applicable inflation assembly with hand tightening. The inflation assembly shall be examined to assure that the top of the cylinder has not made contact with the point of the piercing pin by listening for the sound of escaping gas. The carbon dioxide filled cylinder shall then be removed and the top of the cylinder shall be examined. The cylinder shall not have been punctured and there shall not be any evidence of indentation by the piercing pin. Upon completion of the examination, the carbon dioxide cylinder shall be fully reinstalled in the infaltion assembly with hand tightening. The inflation assembly shall be held in the vertical position, with the cylinder at the top, or in a horizontal position, with the lever on the bottom. The lever shall be in its normal position and a maximum load of 15 pounds shall be attached to the free end of the lever. The load shall operate the lever through one normal cycle. The piercing pin shall advance to its maximum point of travel and shall puncture the carbon dioxide filled cylinder in the center of the puncturable area. The piercing pin shall not stick in the carbon dioxide filled cylinder but shall retract to its original position. The gas shall be immediately released and the piercing pin shall not obstruct or retard the flow of the gas. The gas shall not pass through any part of the inflation assembly into the atmosphere other than through the gas passages in the outlet. The empty cylinder shall be removed and the top shall be examined for the location of the puncture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

4.6.9 Hydrostatic pressure. An applicable discharged carbon dioxide cylinder shall be installed in the inflation assembly as specified in 4.5.3.2. The lever shall be in the actuated position during this inspection. The actuated position is considered to be the position of the lever after the piercing pin has punctured the carbon dioxide filled cylinder as specified in 4.6.6. A hydrostatic pressure of 1500 psig shall be applied to the outlet of the inflation assembly for a minimum of 5 minutes. While the pressure is applied, the inflation assembly shall be observed for leakage and deformation.

4.6.10 Breaking strength of the lanyard assembly. The breaking strength of the lanyard assembly shall be determined by securing the lever to the upper jaw of a suitable inspection apparatus and the knob, in a suitable jig, shall be attached to the bottom jaw. The portion of the lever containing the cord shall be between the upper and lower jaws. The speed of the inspection apparatus under no load shall be . 12 + 1/2 inches per minute. The jaws shall be separated until failure occurs. When applicable, the cord, looped through the eye of the release pin of the type II inflation assembly, shall hang free and shall not be attached to any jaw of the inspection apparatus.

4.6.11 Salt spray. The inflation assembly shall be exposed to salt spray for 100 hours in accordance with FED-STD-151, method 811. The inflation assembly shall be exposed in a vertical position with the opening at the top and in a manner that the conditioned air circulates completely around the inflation assembly. Upon completion of the salt spray, the inflation assembly shall be examined for conformance to 3*4.9. Upon completion of this examination, the inflation assembly shall be subjected to the operation with the carbon dioxide filled cylinder inspection, 4.6.8.

5. PACKAGING

5.1 Packaging. Packaging shall be level A or Industrial, as specified (see 6.2).

5.1.1 Level A, Each inflation assembly shall be cleaned in accordance with MIL-P-116, process C-1 and preserved and packaged in accordance with MIL-P-116, method IC-3. No contact preservative is required. The top and bottom gaskets shall be heat sealed within a clear snug fitting bag of 0,00125 + 20 percent inch thick material. The bagged gaskets shall be placed in a draw string type cloth bag. The bag shall be closed and then attached, by the draw string, to the outlet portion of the inflation assembly.

5.1.1.1 Unit package. Each inflation assembly, after cleaning and attaching the cloth bag containing the gaskets, shall be-placed into a clear polyethylene bag. A paper label shall also be inserted for identification (see 5.3.1). The inflation assembly shall then be heat sealed within a snug fitting polyethylene bag of 0.00125 + 20 percent inch thick material. The heat seal seams shall be straight, continuous and parallel to each other and the edges of the polyethylene bag. The closing heat seal seam shall be as close as possible to the edge of the bag. Prior to or during the heat sealing operation, excess air shall be expelled to the extent necessary to permit packaging of the required quantity of inflation assemblies in the container, The sealed inflation assembly shall be suitably cushioned with cellulosic material conforming to PPP-C-843, type II, class A or B and packaged within a snug fitting

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

0.045 inch thick kraft lined chipboard folding box conforming to PPP-B-566, variety 1, style 111, class i; or within a snug fitting 0.048 inch thick non-bending set-up box conforming to PPP-B-676, type I, variety 1. The inflation assembly shall be cushioned in such a manner as to prevent damage during handling and storage.

5.1.1.2 Intermediate package, Twenty four unit packages of one type only, bagged, cushioned and packaged as specified in 5.1,1.1, shall be packaged within a snug fitting intermediate fiberboard container conforming to PPP-B-636, type CF, domestic class, variety SW, grade 125. The boxes containing the inflation assemblies shall be stacked in two tiers. The weight of the contents of the intermediate box shall not exceed 20 pounds. The containers shall be constructed and closed in accordance with the appendix to PPP-B-636. All the seams and joints shall be sealed with a minimum of 3 inch wide tape conforming to PPP-T-45, type III, grade A, B or C.

5.1.2 Industrial. The inflation assemblies of one type shall be packaged to afford the minimum degree of protection necessary to prevent corrosion, deterioration or damage during shipment under normal environmental conditions and commercial modes of transportation.

5.2 Packing. Packing shall be level A, B or Industrial, as specified (see 6.2).

5.2.1 Level A. Four containers (ninety-six inflation assemblies), packaged as specified in 5.1.1.2, shall be packed as specified in 5.2.2, except that the container shall be weather resistant class, variety SW, grade V3C or V3S. In addition each container shall be constructed, closed and reinforced with flat steel strapping or tape banding in accordance with the appendix to PPP-B-636. All the seams, corners and manufacturer’s joints of the box shall be sealed with 3 inch wide tape conforming to PPP-T-45, type 111, grade A, B or C.

5.2.2 Level B. Four containers (ninety-six inflation assemblies), packaged as in 5.1.1.2, shall be packed within a snug fitting fiberboard shipping container conforming to PPP-B-636, type CF or SF, domestic class, variety SW, grade 275. Each container shall be constructed and closed in accordance with the appendix to PPP-B-636. All the seams, corners and manufacturer’s joints of the box shall be sealed with 3 inch wide tape conforming to PPP-T-45, type III, grade A, B or C. The fiberboard container shall not contain any metal fastenings or stitches.

5.2.3 Industrial, All packaged inflation assemblies, which require over-packing for acceptance by the carrier, shall be packed in exterior type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall meet the uniform freight classification rules or regulations of other common carriers as applicable to the mode of transportation selected,

5.3 Marking. In addition to any special marking required by the contract or order, all unit, intermediate and exterior shipping containers shall be marked in accordance with MIL-STD-129. The date of manufacturer (month and year) and the contract or order number shall be indicated on all unit, intermediate and exterior containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

5.3.1 Polyethylene bags. Prior to heat sealing, each polyethylene bag shall contain a white paper label with legible and durable black letters and numerals (see 5.1.1.1). The label shall be placed in the bag so that it may be read through the bag and shall contain the same markings as required in 5.3. In addition, the label shall contain the specification number.

6. NOTES

6.1 Intended use. The inflation assemblies covered by this. specification are intended for use as a component of the mechanical inflation systems used for inflating life preservers.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Type of assembly, style of lanyard, type of cylinder and quantity desired. (see 1.2).
c. Whether first article inspection is waived. (see 4.3.1).
d. Name and address of the first article inspection laboratory (see 4.3.1) including the Government activity responsible for conducting the inspection program (see 4.3.1.1).
e. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
f. Whether any special markings are required (see 5.2).

6.2.2 Contract data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 and invokes the provisions of 7-104,9(n) of the Defense Acquisition Regulations, the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR-7-104.9(n) are not invoked, the data specified below will be delivered by the contractor in accordance with the contract requirements, Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data requirement	Applicable DID
3.2	Certificate of compliance for the age of materials and components	DI-E-2121 - Certificate of compliance
4.3.1.1	First article inspection reports	DI-T-5329 - Inspection test reports

(Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the acquiring activity or as directed by the contracting officer).

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.

6.3 First article. When first article is required, it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulations. The first article should be a first production item. The first article should consist of twelve units. The contracting officer should include specific instructions in all acquisition instruments, regarding arrangements for examinations, test and approval of the first article.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness Of the changes.

Custodians:
Army - ME
Navy - AS
Air Force - 99

Review activities:
Army - AV
Navy - SH
Air Force - 11

User activities:
Navy - YD, MC

Preparing activity:
Navy - AS

(project No. 4220-0267)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

TABLE I. First article examinations and tests.

Inspection	Paragraph	
	Requirement	Method
Visual examination	3.3 through 3.3.6.2, as applicable, applicable drawings and figures	4.6.3.1
Rockwell hardness	3.4.1	4.6.2
Weight	3.4.2	4.6.4
Leakage at 40 psig	3.4.3.1	4.6.5.1
Leakage at 2 psig	3.4.3.2	4.6.5.2
Operating force	3.4.4	4.6.6
Piercing pin position and travel	3.4.5.1	4.6.7
Operation	3.4.6	4.6.8
Hydrostatic pressure	3.4.7	4.6.9
Breaking strength of lanyard	3.4.8	4.6.10
Salt spray	3.4.9	4.6.11
Dimensional check	3.3 through 3.3.6.2, as applicable, 3.4.5.2 and applicable figures and drawings	4.6.1 and 4.6.3.1

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.

TABLE II. Sample size, acceptance criteria, examinations and tests of the inflation assemblies and prenaration for delivery.

Inspection	Paragraph		Sample size	Acceptance criteria
	Requirement	Method		
Dimensional check of the piercing pins	3.4.5.2 and figures 3 and 7, as applicable	4.6.1	Inspection level S-3	An acceptable quality level of 2.5 defects per 100 units.
Visual examination of the inflation assemblies	Section 3 and applicable figures	4.6.3.1	Every inflation assembly for major defects and inspection level II for minor defects	Reject all units with any major defect and an acceptable quality level of 4.0 defects per hundred units for minor defects.
Dimensional check of inflation assemblies	Section 3 and applicable figures	4.6.3.1	Inspection level S-3	An acceptable quality level of 2.5 defects per 100 units
Weight	3.4.2	4.6.4	Inspection level S-1	An acceptable quality level of 2.5 defects per 100 units
Leakage at 40 psig	3.4.3.1	4.6.5.1	Every inflation assembly	Reject all defective units
Leakage at 2 psig	3.4.3.2	4.6.5.2	Inspection level S-2	An acceptable quality level of 1.0 defects per 100 units
Piercing pin position and travel and lever operation	3.4.5.1	4.6.7	Every inflation assembly	Reject all defective units
Operation with carbon dioxide filled cylinder	3.4.6	4.6.8	Inspection level S-2	An acceptable quality level of 1.0 defects per 100 units
Hydrostatic pressure	3.4.7	4.6.9	Inspection level S-1	An acceptable quality level of 2.5 defects per 100 units
Packaging	Section 5	4.6.3.2	Inspecton level S-2	An acceptable qualtiy level of 2.5 defects per 100 units

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.

TABLE III. List of defects for the finished dimensions of the piercing pins.

Examine	Defect
Check the various dimensions of the piercing pin as specified in figures 3 and 7, as applicable, and the "O" ring.	Any measurement deviating from 3.3.4 through 3.3.5 and figures 3 and 7, as applicable, and applicable tolerances shall be enumerated as dimensional defect.

TABLE IV. Classification of defects for the visual examination of the inflation assemblies.

Major	
101.	Any surface rough, misaligned or contains any nick, unspecified sharp edge, crack, burr, pit, dent, sliver, scale, embedded foreign matter, loose particle or other imperfection.
102,	Any finish missing or any component improperly finished.
103.	Any component missing, malformed, corroded, fractured, chipped, bent, distorted or damaged.
104.	Any component loose, detached, not assembled as specified or otherwise not securely retained.
105.	Any end of the grooved taper pin protruding from the body.
106.	Any functional part that works with difficulty.
107.	Any gas passage missing.
108.	Any threads missing, stripped, torn, broken or otherwise defective.
109.	Any component not as specified or any defect of a component or defect of assembly not herein classified which seriously affects the serviceability or appearance.
110	Any component, component part or required operation omitted or any operation not herein classified improperly performed thereby seriously affecting serviceabiltiy or appearance.
Minor	
201.	Any markings, missing, incorrect, illegible, incomplete, not of a permanent nature or improperly located.
202.	When applicable, contract number and date of manufacture not coated (see 3.5).
203.	Surface unclean; or foreign matter appearing on surface.
204.	Any component not as specified or any defect of a component not herein classified which does not seriously affect the serviceability or appearance.
205.	Any component, component part or required operation omitted or any operation not herein classified improperly which does not affect serviceability or performance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.


TABLE V. List of defects for the finished dimensions of the inflation assemblies.

Examine	Defect
Measure the assembly outline, outlet, body, thickness of the lever, set screw, when applicable, lanyard assembly, knob, threads and top and bottom gaskets.	Any measurement deviating from the dimensions specified in figures 2 through 8 and allowable tolerance, as applicable? shall be enumerated as a dimensional defect.

TABLE VI. List of defects for preparation for delivery.

Item	Defects
Exterior and interior markings	Missing, incorrect, incomPlete, illegible; of improper size, location, sequence or method of application; markings not the same on the interior and exterior containers; information on the paper and label in the polyethylene bag not legible through the film or no label in the film bag.
Packaging and packing materials	Any non-conforming component; any missing damaged or otherwise defective.
Workmanship	Inadequate application of the components; incomplete closure of the polyethylene bag, unit or intermediate package, container flaps or loose strapping; bulging or distortion of the containers. Any portion of the lanyard assembly caught in any of the heat sealed seams.
Exterior and interior weight or content	Gross or net weight exceeds the requirements; more than o e type of inflation assembly packed in the same container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.




MENSIONS IN INCHES.
LESS OTHERWISE SPECIFIED,
LERANCES: FRACTIONS ±1/64,
CIMALS ±.005.


R SECTION A-A, SEE FIGURE 2.

FIGURE 1. TYPE IINFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.



SAFETY WIRE OMITTED
SECTION A-A




LANYARD ASSEMBLY


DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED,
TOLERANCES SHALL BE
AS SPECIFIED IN FIGURE 1.

FIGURE 2. SECTION A-A AND LANYARD ASSEMBLY FOR TYPE I INFLATION ASSEMBLY


Source: https://assist.dla.mil -- Downloaded: 2026l0-19T15:42Z
Check the source to verify that this is the currentversion before use.



PIERCING PIN



DETAIL B




(POINT BEFORE GRINDING FLATS)

DETAIL C

FIGURE 3. PIERCING PIN FOR TYPE I INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.




DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED,
TOLERANCES SHALL BE
AS SPECIFIED IN FIGURE 1.


FOR SECTION D-D, SEE FIGURE 5.

FIGURE 4. TYPE II INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.



SECTION D-D




NYLON INSERT

SET SCREW ASSEMBLY

DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED,
TOLERANCES SHALL BE
AS SPECIFIED IN FIGURE 1.


FIGURE 5. SECTION D-D, NYLON INSERT, AND SET SCREW ASSEMBLY DETAILS FOR TYPE II INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 20261O-19T15:42Z
Check the source to verify that this is the currentversion before use.



A	3-3/8	4-3/8
B	4-1/8	5-1/8

LANYARD ASSEMBLY



NYLON RELEASE PIN

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ON DIMENSIONS SHALL BE AS FOLLOWS:

DIMENSIONS	TOLERANCES
0 TO 1/2 INCL	±1/32
OVER 1/2 TO 1 INCL	±1/16
OVER 1 TO 5 INCL	±1/8
OVER 5	±1/4

FIGURE 60 LANYARD ASSEMBLY AND NYLON RELEASE PIN DETAILS FOR TYPE II INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 20261O-19T15:42Z
Check the source to verify that this is the currentversion before use.





FIGURE 7. PIERCING PIN AND SEAT SEAL GASKET DETAILS FOR TYPE II INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.



DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED,
TOLERANCES SHALL BE
AS SPECIFIED IN FIGURE 1.

FOR SECTIONS H-H, AND J-J, SEE FIGURE 9

FIGURE 8. TYPE III INFLATION ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.






FIGURE 9. SECTIONS H-H AND J-J FOR TYPE III INFLATION ASSEMBLY


Source: https://assist.dla.mil -- Downloaded: 20261O-19T15:42Z
Check the source to verify that this is the current version before use.




GROOVED TAPER PIN




TOP GASKET



BOTTOM GASKET



KNOB
DESIGN A




KNOB
DESIGN B


DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED,
TOLERANCES SHALL BE
AS SPECIFIED IN FIGURE 6.

FIGURE 10. GROOVED TAPER PIN, TOP GASKET, BUTTOM GASKET , AND KNOB DETAILS

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.




TOP GASKET




BOTTOM GASKET

FIGURE II, MANIFOLD STEM GASKET

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.



STANDARD GAGE FOR TYPE I AND III INFLATION ASSEMBLIES



STANDARD GAGE FOR TYPE II INFLATION ASSEMBLY

DIMENSIONS IN INCHES

FIGURE 12. TYPICAL EXAMPLE OF STANDARD CYLINDER GAGE FOR TYPE I, II, AND III INFLATION ASSEMBLIES

☆U.S. GOVERNMENT PRINTING OFFICE: 1982-505-022/731

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-I-23145B, INFLATION ASSEMBLIES, LIFE PRESERVER

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426
1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:42Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE AIR FORCE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

Commanding Officer
Naval Air Engineering Center
Engineering Specifications and
Standards Department (ESSD) Code 93
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:42Z
Check the source to verify that this is the current version before use.