MILITARY SPECIFICATION

PLOTTING TABLE, ANTI-SUBMARINE AND

DEAD RECKONING (NAVAL SHIPBOARD)

This amendment forms a part of Specification MIL-P-23141D(SHIPS), 7 June 1968

Page 3

Paragraph 3.2.1, line 18: After "spot of light" insert "projected".

Page 7

Paragraph 3.5.8, line 2: Delete "11 volt" and substitute "115 volt".

Page 9

Paragraph 3.5.19, line 4: At end of line delete "pa".

Page 12

Paragraph 3.7.5, line 6: Delete "TPA go go to" and substitute "TPA to go to".

Page 13

Paragraph 3.9.3: Delete and substitute:

"3.9.3 Scale selection. Scale selection for both own ship and all TPAs shall be achieved by a single rotary switch with eight usable positions. These scale positions are listed in 3.5.4.

Page 15

Paragraph 3.10.5, line 4: Delete "arc tor" and substitute "arc tan".

Page 16

Paragraph 3.12: In line 10, delete "$A_o = \frac{(1000 - \overline{M}t}{1000} \times 100)$ percent" and substitute "$A_o = \frac{(1000 - \overline{M}t}{1000} \times 100$ percent"; in line 12, delete "($\overline{M}o = \frac{1000 \text{ hours}}{\text{mean time between failure (mtbf)}}$" and substitute "where $\overline{M}o = \frac{1000 \text{ hours}}{\text{Mean time between failure (mtbf)}}$", and in the line preceding table I, insert "maximum" before "specified mtbf".

Preparing activity:
Navy - SH
(Project 6605-N173)

FSC 6605

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:41Z
Check the source to verify that this is the current version before use.