NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/322B
31 March 2021
SUPERSEDING
MIL-DTL-3943/322A
8 June 2016

DETAIL SPECIFICATION SHEET

DECORATION, NOAA CORPS COMMENDATION MEDAL, NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943.



OBVERSE REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy NO. C-230)

FINISH: Nickel Plated, Silver Plated, Oxidized, Buffed Relieved, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 15.

DIMENSIONS:
HEIGHT: (including lug):
-1: 1-3/4 inches (REF)
-2: 13/16 inch (REF)
WIDTH:
-1: 1-3/8 inches (REF)
-2: 5/8 inch (REF)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:05Z
Check the source to verify that this is the current version before use.

THICKNESS (at thickest point):
-1: 0.125 ± 0.010 inch
-2: 0.090 ± 0.010 inch

DECORATION SET: Decoration set shall consist of a regular size medal, a miniature size medal and a service ribbon all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, with a Class 2A or 4 Pad.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-353)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:05Z
Check the source to verify that this is the current version before use.