INCH-POUND
MIL-T-47303A (MI)
30 September 1992
SUPERSEDING
MIL-T-47303 (MI)
20 April 1979

MILITARY SPECIFICATION

TEST SET, ELECTRICAL, MK IV

This specification is approved for use by the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the fabrication, inspection and testing of the MK IV electrical test set. The test limits in this specification do not necessarily define maximum capabilities. The MK IV electrical test set is a self-contained, multipurpose test set powered by a rechargeable battery. It is used with the 2.75 inch FAAR system (less rockets) and any other system utilizing the MK I squib or a similar device. This test set shall not be used on any ordnance.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4927
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-E-17555	-	Electronic and Electrical Equipment, Accessories, and Provisioned Items (Repair Parts): Packaging of
MIL-T-21200	-	Test Equipment for use with Electronic and Electrical Equipment, General Specification for

STANDARDS

FEDERAL

FED-STD-H28	-	Screw-Thread Standards for Federal Service

MILITARY

MIL-STD-108	-	Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment
MIL-STD-130	-	Identification Marking of US Military Property
MIL-STD-454	-	Electronic Equipment, Standard General Requirements for
MIL-STD-461	-	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-781	-	Reliability Testing for Engineering Development, Qualification and Production
MIL-STD-810	-	Environmental Test Methods and Engineering Guidelines

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing, and Marking

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Ave., Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

ARMY

11554129 - Test Set Electrical Assembly, MK IV

(Copies of the drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified, (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.4. The supplier shall furnish eight complete tests sets for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. The approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

3.2 Design. The test set is designed to ensure prope operation of the intervalometer/launcher combination, and t the presence of a ground on the firing lines.

3.3 Construction. The construction of the MK IV elec test set shall be in accordance with Drawing 11554129 and t requirements specified herein. The applicable requirements T-21200 for class 2 equipment shall apply whenever design requirements are not specified in the drawing.

3.3.1 Manufacturing. Unless otherwise specified by t procuring activity, test set drawings or this specification, manufacturing shall conform to the applicable MIL-STD-454 requirements as specified by MIL-T-21200. Responsibility sh assumed by the contractor for any malfunction, or failure o part, subassembly, or assembly to pass the tests specified (see 4.6).

3.3.2 Interchangeability. All replaceable parts shal manufactured to definite tolerances and clearances in order any such parts of a particular type or model may be replace adjusted without requiring modification.

3.3.3 Screw threads. All screw threads shall conform STD-H28.

3.3.4 Surfaces. Surfaces of all parts shall be clean free from extraneous materials. External surfaces shall be and free from sharp edges. All exterior corners shall be r

3.3.5 Fastening devices. All screws, pins, bolts, an similar parts shall be installed with means for preventing tightness. All such parts when subjected to removal or adj shall not be permanently deformed.

3.3.6 Identification of parts. All parts shall be ma accordance with the applicable requirement of MIL-STD-130.

3.3.7 Dimensions. The MK IV electrical test set dime shall-be in accordance with drawing 11554129.

3.4 Performance characteristics.

3.4.1 Functionals. The MK IV electrical test set sha incorporate provisions for performing the following test fu

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

3.4.1.1 Firing current. The test set shall function to indicate that a satisfactory firing signal has been received when stimulated with a proper current and time flow. In addition, upon receipt of a correct firing signal the load produced in the test set shall automatically disconnect between 10 and 14 milliseconds. The current firing signal is defined as a current of 0.810 ampere or greater for 10 milliseconds or longer. The test set shall indicate non-satisfactory condition if the stimulating signal is less than 0.810 ampere or its duration is less than 10 milliseconds (see 4.6.2.1).

3.4.1.2 Ground. The test set shall provide, through the indicator lamp and protection circuit, a current to the test leads. It is essential that the test set shall not, under any conditions, deliver an output current through the external circuit greater than 15 milliamperes direct current (de) (see 4.6.2.2).

3.4.1.3 Stray current test. The test set shall function to indicate that a "stray" signal has been received when stimulated with a specific current and time flow. In addition, upon receipt of a "stray" signal the load produced in the test set shall automatically disconnect between 10 and 14 milliseconds. The "stray" signal is defined as a current of 0.054 ampere or greater for 10 milliseconds or longer. The test shall indicate no stray current if the stimulating signal is less than 0.054 ampere or its duration is less than 10 milliseconds.

3.4.1.4 Test switch. The test switch is used to check if the test set system is operating properly. With test leads shorted the selector switch is placed in position 1. The indicator lamp shall come on and remain lit until the test switch is depressed. When the selector switch is placed in position 2 and/or 3 the indicator lamp (PLI) shall not come on until the test switch is depressed.

3.4.2 Operating environments. The MK IV electrical test set shall comply with requirements of the applicable conditions specified in MIL-T-21200 as listed herein and other conditions specified in table I.

3.4.2.1 Electromagnetic compatibility. The test set shall meet the requirements of MIL-STD-461 with respect to conducted and radiated emissions (see 4.6.3).

3.4.2.2 Temperature/altitude. The test set shall operate at all possible combinations of temperature from -40° Celsius (C) to +71°C and altitudes from 0 to 10,000 feet. In addition, the test

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

set shall withstand storage temperatures from -62°C to 85°C a altitudes up to 50,000 feet (4.6.4.1).

3.4.2.3 Humidity. The test set shall be operable afte subjected to relative humidities of 95 + 5% for 10 days (see 4.6.4.2).

3.4.2.4 Salt fog. The test set shall be operable afte exposed to a 5% salt fog solution for a period of 48 hours (4.6.4.7).

Table I. First article inspection - schedule and sequen

Test No.	Tests	Test Para.	Two arti samp A
A	Inspection	4.6.1	1
B	Functional	4.6.2	2
C	Electromagnetic compatibility	4.6.3	3
D	Temperature/altitude	4.6.4.1	4
E	Humidity	4.6.4.2	X
F	Dust	4.6.4.3	5
G	Shock	4.6.4.4	6
H	Vibration	4.6.4.5	X
I	Watertightness	4.6.4.6	X
J	Salt fog	4.6.4.7	7
K	Impact	4.6.4.8	X
L	Reliability	4.6.5	(6 unit designa C,D,E,F 2/

Notes:

1. Under the right-hand column, the numbers from one to seven are the test requirements and sequences to follow for each unit.
2. The reliability units C, D, E, F, G, and H are tested to paragraph 4.6.5 only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

3.4.2.5 Shock. The test set shall be operable after being exposed to shock levels up to 20 g's having a time duration of 11 + 1 milliseconds (see 4.6.4.4).

3.4.2.6 Impact. The test set case shall be operable after being subjected to impacts on a concrete surface from a height of 30 inches (see 4.6.4.8).

3.4.2.7 Vibration. The test set shall be operable after being subjected to the vibration requirements for class 2 equipment of MIL-T-21200 (see 4.6.4.5).

3.4.2.8 Watertightness. The test set case shall not leak when subjected to the spraytight requirements of MIL-STD-108 (see 4.6.4.6).

3.4.2.9 Dust. The test set shall be operable after being subjected to exposure to sand and dust particles for a period of 28 hours.

3.5 Reliability. The test set shall have a specified mean time between failures (MTBF) of 1000 hours (see 4.6.5).

3.6 Workmanship. The workmanship of the MK IV electrical test set shall conform to Requirement 9 of MIL-STD-454. The standards of workmanship exhibited in the approved first article sample, subject to any qualification stated in the Government's notice of approval, shall determine the requirements of the remainder of the contract relative to workmanship.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

this specification shall become a part of the contractor's c inspection system or quality program. The absence of any inspection requirements in the specification shall not relie contractor of the responsibility of ensuring that all produc supplies submitted to the Government for acceptance comply w requirements of the contract. Sampling inspection, as part manufacturing operations, is an acceptable practice to ascer conformance to requirements, however, this does not authoriz submission of known defective material, either indicated or nor does it commit the Government to accept defective materi

4.2 Classification of inspections. The inspection requirements of the MK IV electrical test set specified here classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified inspections shall be performed under the following condition

a. Room temperature. Indicated room ambient tempera shall be 23 + 10°C.

b. Test temperature. All parts of the test item shall stabilized at the specified temperature + 2.8°C indicated pr conducting any operational tests. Unless otherwise specifie temperature stabilization will have been attained when the indicated temperature of the surface of the largest mass of test item does not change more than + 2.8°C per-hour.

c. Humidity. Humidity shall be room ambient to 95 per (%) relative humidity. When humidity testing is required, t tolerance shall be + 5% relative humidity.

4.4 First article inspection. First article inspectio consist of the tests outlined in table I. The procuring act reserves the right to delete tests and alter the test sequen table I. First article approval is valid only on the contra purchase order under which it is granted unless extended by Government to other contracts or purchase orders.

4.4.1 Test set samples. First article MK IV electrica set samples shall consist of the first eight test sets manuf on the contract or purchase order. The test sets shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

permanently labeled for ease of identification and shall have been produced with the equipment and procedures that will be used for the production of all test sets designated in the contract or purchase order. Prior to submission, the contractor shall inspect the samples to the degree necessary to assure that they conform to the requirements, including statements of findings and certificates of conformance for materials and tests A and B of table I. A sample containing known defects shall not be submitted unless specifically authorized by the contracting officer (see 6.2d).

4.5 Quality conformance inspection. Quality conformance inspection consists of those examinations and tests specified in 4.6.1 and 4.6.2, to be conducted on MK IV electrical test sets, and submitted for acceptance under the contract or purchase order. Acceptance test sets shall be on an inspection lot basis (4.5.1).

4.5.1 Inspection lots. Each month's production shall be considered a lot for acceptance purposes.

4.5.1.1 Sampling. Test sets shall be selected for sampling in accordance with table 11.

TABLE II. Sampling plan for quality conformance tests.

Lot Size	Sample Size
2 to 5	100%
6 to 50	5
51 to 90	7
91 to 150	11
151 to 280	13
281 to 500	16
501 to 1200	19
1201 to 3200	23
3201 to 10,000	29
10,001 to 35,000	35
35,001 and over	40
In all cases: Acceptance number is ZERO Rejection number is ONE	

4.5.1.2 Resubmission of rejected lots. When a lot is rejected, the contractor, at the discretion of the procuring activity, may have the opportunity of reworking and resubmitting the entire affected lot. The procuring activity shall determine

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

which inspection and tests of this specification are to be performed on the reworked inspection lot samples (see 6.2e).

4.5.1.3 Sampling inspection. Samples selected in accordance with table II shall undergo examinations in accordance with 4.6.1. Failure of any sample to meet any of the examinations specified shall constitute rejection of the lot.

4.5.1.4 100 percent inspection. Each test set shall undergo tests in accordance with 4.6.2. Failure of any test set to meet any of the tests specified shall constitute rejection of that test set.

4.6 Examination methods.

4.6.1 Examination. The test set shall be examined as follows:

4.6.1.1 Assembly. The test set shall be inspected to ensure that it has been properly assembled and adjusted, the electrical connections are secure, and the workmanship is as specified herein.

4.6.1.2 Documentation. The test set shall be thoroughly examined to determine conformance to the requirements of Drawing 11554129 and this specification.

4.6.1.3 Preparation for delivery. The test shall be examined to ascertain that the preparation for delivery conforms to contract requirements.

4.6.2 Functional tests. Each test set shall be operated five times in each mode described herein.

4.6.2.1 Ground test. The test set shall simulate a condition in which the test set leads are connected together. Current flow through the leads shall be measured and shall be not 15 milliamperes dc with the indicator lamp lit.

NOTE: The test equipment shall not increase the resistance of a simulated short circuit connection of the test leads by more than 1 ohm.

4.6.2.2 Fire current test. Connect the test set leads to the test equipment. Set the selector switch on the test set to the “Fire” position. The test equipment will initiate a fire pulse and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

measure the time and current flow through the test leads to the test set. The indicator lamp (PL1) shall come on and remain lit until the reset switch (S2) is depressed. This test procedure shall be conducted for conditions 1 through 4 below. The output parameters of the fire pulse by contractor's test equipment, when connected to a 1 ohm load, shall be as follows:

Condition	Time (milliseconds)	Current (amperes dc)
1	t=16	I=0.90
2	t=16	I=6.0
3	t=5000	I=0.90
4	t=5000	I=6.0

The indicator lamp shall not come on when the fire switch is depressed for conditions 5 through 7 below. The parameters of the fire pulse generated by the test equipment shall be as follows:

Condition	Time (milliseconds)	Current (amperes dc)
5	t=5	I=0.50
6	t=5	I=6.0
7	t=5000	I=0.50

Notes:

1. Tolerance for t= + 10% and I = + 10% in conditions 1 through 7.
2. For conditions 1 through 4 the load shall disconnect between 10 and 14 milliseconds.
3. For conditions 5 through 7 the load shall not disconnect from the stimulating signal.

4.6.2.3 Stray current check sequence. Connect the test set leads to the test equipment. Set the selector switch on the test set tot he "Stray current" position. The test equipment will initiate a simulated stray current and measure the time and current flow to the test set. The indicator lamp (PL1) shall come on and remain lit until the reset switch (S2) is depressed. This test procedure shall be conducted for each of the conditions 1 through 4 below. The output parameters of the stray current by the test equipment, when connected to a 1 ohm load, shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

Condition	Time (milliseconds)	Current (amperes dc)
1	t=16	I=0.060
2	t=16	I=1.00
3	t=5000	I=0.060
4	t=5000	I=1.00

The indicator lamp shall not come on when the fire switch is depressed for conditions 5 through 7 below. The parameters of the fire pulse generated by the test equipment shall be as follows:

Condition	Time (milliseconds)	Current (amperes dc)
5	t=5	I=0.020
6	t=5	I=0.225
7	t=5000	I=0.020

Notes:

1. Tolerance for t= + 10% and I = + 10% in conditions 1 through 7.
2. For conditions 1 through 4 the load shall disconnect between 10 and 14 milliseconds.
3. For conditions 5 through 7 the load shall not disconnect from the stimulating signal.

4.6.2.4 Test switch. Place the selector switch to position 1. Connect the test leads to each other. The indicator lamp (PL1) shall come on and remain lit until the test switch (S3) is depressed. When the test switch is released, the indicator lamp shall again come on. With the test leads disconnected, place the selector switch to position 2. The indicator lamp (PL1) shall not light until the test switch (S3) is depressed. Place the selector switch to position 3. The indicator lamp shall not light until the test switch is depressed. The above procedure shall be repeated after each condition in 3.4.1.2 and 3.4.1.3 has been completed.

4.6.3 Electromagnetic capability. The test set shall be tested in accordance with MIL-STD-462 to the requirements of MIL-STD-461 limits for CE02, CE04, RE01, and RE02.

4.6.4 Environmental tests. The test set shall be subjected to the following environmental tests in accordance with the requirements of MIL-T-21200 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

4.6.4.1 Temperature altitude. The test set shall be subjected to the temperature altitude test of MIL-STD-810, method 504, procedure I except the conditions shall be in accordance with MIL-T-21200, class 3 equipment. While at ambient conditions, the test set shall meet the requirements of 4.6.2. At the completion of testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.2 Humidity. The test set shall be subjected to the humidity test of MIL-STD-810, method 507, procedure I. At the completion of testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.3 Dust. The test set shall be subjected to the dust test of MIL-STD-810, method 510, procedure 1. At the completion of the testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.4 Shock. The test set shall be subjected to the transit and combination cases shock test in accordance with MIL–T-21200. At the completion of each axis of testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.5 Vibration. The test set shall be subjected to the vibration test in accordance with MIL-T-21200. At the completion of each axis of testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.6 Watertightness. The test set case shall be subjected to the spraytight requirements of MIL-STD-108. Entry of water during the test shall be cause for rejection.

4.6.4.7 Salt fog. The test set shall be subjected to the salt fog test of MIL-STD-810, method 509, procedure I. At the completion of testing, the test set shall be visually inspected and tested in accordance with 4.6.2.

4.6.4.8 Impact . The test set case shall be subjected to the drop test in accordance with MIL-T-21200.

4.6.5 Reliability demonstration. The MTBF of the test set shall be demonstrated according to MIL-STD-781, test plan III C, using an MTBF of 1000 hours. Six units shall be used for demonstration. The duty cycle shall be 19 functional cycles every 5 minutes during operation for the duration of the test. A functional cycle shall consist of one ground check, one fire check

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

and one stray voltage check. No-go conditions for each function shall be checked every 100 hours of operating time (see table I).

4.6.5.1 Manufacturing run-in. If a manufacturing run-in test or burn-in is performed, it shall be performed in accordance with MIL-STD-781.

4.6.6 Inspection of packaging. The sampling and inspection of the preservation, packaging, and container marking shall be in accordance with the requirements of MIL-E-17555 and MIL-STD-1190.

5. PACKAGING

5.1 Preservation, packing, unitization, and marking. The preservation, packing, unitization, and marking of the test sets shall be Level A, B, or C, as specified (see 6.2).

5.1.1 Level A or B. Preservation, packing, unitization, and marking shall be in accordance with MIL-E-17555.

5.1.2 Level C. Preservation, packing, unitization, and marking shall be in accordance with MIL-STD-1190.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The MK IV electrical test set is intended for use with the 2.75 inch FAAR system (less rockets) and any other system using the MK I squib or a similar device used to perform the following functions:

a. To detect the presence of any stray current sufficient to initiate the squib.
b. To ensure sufficient energy in the firing pulse to initiate the squib.
c. To detect the presence of a ground on the firing lines.

6.1.1 Restriction. This test set will not be used in the presence of ammunition or explosive devices.

6.2 Acquisition requirements. Acquisition documents must specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of the specification

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)

c. Whether a first article sample is required (see 3.1)

d. Samples subjected to the acceptance tests shall be over and above the quantity procured for delivery to the user (see 4.4.1)

e. Rework and retest requirements for inspection test samples (see 4.5.1.2)

f. Applicable levels of preservation, packing, unitization and marking (see 5.1).

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerers whether the item(s) should be a first article sample, a first production item, or a number of items to be tested as specified in 4.4. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.3.1 First article sample information. Deviation from, or requirements for six first article test sets to do MTBF 1000 hours (3.1) and (3.5) reliability demonstration (4.6.5) will be determined by the Product Assurance Directorate prior to procurement.

6.4 Metrication. Metric equivalents in accordance with FED-STD-376 are acceptable for use in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Electronic testing devices
Testing equipment
Testing and evaluation devices
Testing and measurement devices

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army – MI

Preparing activity:
Army - MI

Project 4927 – A009

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	MIL-T-47303A (MI)	920930

3. DOCUMENT TITLE

TEST SET, ELECTRICAL, MK IV

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
COMMANDER U.S. ARMY MISSILE COMMAND	(1) Commercial (205) 876-6980	(2) AUTOVON 746-6980
c. ADDRESS (Include Zip Code) ATTN: AMSMI-RD-SE-TD-ST REDSTONE ARSENAL, AL 35898-5270	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-0-22119:082
Check the source to verify that this is the current version before use.