MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

ACTUATORS,

ELECTROMECHANICAL, ROTARY

TO ALL HOLDERS OF MIL-STD-35-72(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-72(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
Cover	22 May 1974	(REPRINTED WITHOUT CHANGE)	
ii	6 September 1976	ii	22 May 1974
iii	6 September 1976	iii and iv	22 May 1974
5	6 September 1976	5	15 January 1975
6	15 January 1975	(REPRINTED WITHOUT CHANGE)	
41	22 May 1974	(REPRINTEO WITHOUT CHANGE)	
42	6 September 1976	42 through 46	15 January 1975

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE
167	6 September 1976

3. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

4. Holders of MIL-STD-35-72(MI) will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A179)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

MIL-STD-35-72(MI)

22 MAY 1974

MILITARY STANDARD

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

ACTUATORS, ELECTROMECHANICAL, ROTARY

Reprinted without change.

FSC-EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Automated Engineering
Document Preparation System,
Actuators, Electromechanical, Rotary

MIL-STD-35-72(MI)

1. This Military Standard is approved by the U.S. Army Materiel Development and Readiness Command, Department of the Amy, and is approved for use by all its activities. All other military activities are required to employ this Standard where suitable.

2. Recommended corrections, additions, or deletions should be addressed to Commander, U.S. Army Missile Command, ATTN: DRSMI-RCS, Redstone Arsenal, Alabama 35809.

Supersedes page ii of 22 May 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of MIL-STD-35-72(MI) is to facilitate the preparation of Military Specification, Exceptions for Actuators, Electromechanical, Rotary.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the basic MIL-STD-35.

3. It is important that the procedure described in the basic document (MIL-STD-35C) and subsequent revisions be followed explicitly in order for the computer to produce a document suitable for competitive procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of MIL-STD-35C. This information is not repeated in each dash-numbered part.

Supersedes pages iii and iv of 22 May 1974.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these instructions is to establish the procedures to be followed, and the format to be used, for submission of requirements to obtain a computer generated procurement document.

The requester will find it impossible to complete an SRS using only this dash-numbered part of MIL-STD-35. Information which is standard for all generic families has been included in the master document at the issuance of MIL-STD-35C. This information is not repeated for each dash-numbered part. The following list contains the subjects which are pertinent to every family unless otherwise excepted. ”

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables

Supersedes page 5 of 15 January 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for an actuator, to be entered on the SRS with Code 1007, is selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Actuator, Electromechanical, Rotary	11006
Unapproved Name	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3.

1.2.4 Dimensions

MIL-STD-35 must be used in conjunction with this dash numbered part to completely delineate the dimensions for an actuator.

The figures and corresponding legends, representing different configurations of actuators, are located in the rear of this document. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009. The figure legends in this document (AA, AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimensioning actuators are in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation are found in MIL-STD-35. Candidates for tabulation for this part are the dimensional codes shown in Table A of MIL-STD-35 and the following.

Tabulation CANDIDATES FOR ROTARY ACTUATORS

Characteristic Code	Title
1562	Minimum Starting Current (amperes)
1564	Maximum Starting Current (amperes)
1566	Minimum Starting Current (milliamperes)

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

1.2.69 Electrical and Environmental Test Methods and Requirements

The instructions contained in this paragraph shall be followed when it is desired to make exceptions to the test methods and requirements of any of the following tests:

Altitude

High Temperature

Low Temperature

Temperature Shock

Rain

Humidity

Fungus Resistance

Salt Fog

Dust

Explosive Atmosphere

Leakage (Immersion)

Acceleration

vibration

Acoustical Noise

shock

Combined Temperature-Humidity-Altltude

When a code is shown for any test method, it is mandatory that a requirement code be shown. However, the first test method code and the first requirement code should not be used together, since that combination makes no exception to the specification referenced with Code 1006.

1.2.69.1 Test Methods

The test method may be specified on the SRS by using one of the following codes:

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

a. If the first test method is desired, use the first test method code with an "X" to specify testing per the specification referenced with Code 1006.

b. If the second test method is desired, use the second test method code and complete the sentence with the specified exceptions, for testing per the referenced specification with exceptions. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. If testing is to be detailed, one or more of the test method codes should be used to specify test conditions. All codes marked with an asterisk "*" must be used.

If the specification referenced with Code 1006 specifies a MIL-STD-810 test method and exceptions are to be taken, the second test method code (see b. above) should be used if the exceptions can be stated within the 189 character limitation; the third test method (see c. above) should be used if the exceptions cannot be stated within the limitation.

1.2.69.2 Requirements

If the requirements" specified in the specification shown with Code 1006 are to be used, the first requirements code should be shown, with an "X" on the SRS. If exceptions to the requirements specified in the specification shown with Code 1006 are to be made, the second requirements code should be shown with exceptions written in on the SRS to complete the sentence. If the requirements are to be changes in parameter values as a result of the environmental test, one or more of the remaining requirements codes with the applicable fill-in values must be shown. When the third requirements code is shown, the requirements that there be no evidence of physical damage or degradation of performance will be included automatically.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MI

Review activities:
Army - AT
Army - AV
Army - EL
Army - ME
Army - MR
Army - SG
Army - WC

User activity:
Army - MU

Preparing activity:
Army - MI

(Project EDS-A024-13)

New page.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1976-603-766/6714

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Missile Command
ATTN: DRMSI-RCS
Redstone Arsenal, Al 35809

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-STD-35-72 -	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.