

RATINGS	
Style	LT10
Grade	1
Class	A
Temperature rise	15°C
Ambient temperature	90°C
Operating temperature	-55° to +105°C
Dielectric withstanding Voltage (sea level)	1000 volts rms for minimum of 60 sec
Dielectric withstanding Voltage (reduced barometric pressure)	200 volts rms for a minimum of 60 sec.
Terminal pull	5 pounds
Altitude	70,000 feet
Weight	4.0 grams max.

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	365 (9 27)	.385 (9.78)
B	615 (15 62)	.635 (16.13)
C	1.250 (31.75)	1.625 (41.28)
D	026 (66)	.030 (.76)

ELECTRICAL CHARACTERISTICS (INITIAL)

Dash No. 1/	Type designation 2/	Former type designation	Superseded MS part no.	Inductance ±10%	Q min	Test freq.	Self-resonant frequency Min	DC resistance Max	Rated DC current
				uh		MHz	MHz	Ohms	Ma
-1	LT10K148	LT4K064	MS75054-1	470	80	.790	3.7	9.0	125
-2	LT10K149	LT4K065	-2	560	80	.790	3.5	10.0	118
-3	LT10K150	LT4K066	-3	680	75	.790	3.2	11.2	112
-4	LT10K151	LT4K067	-4	820	75	.790	3.0	13.0	105
-5	LT10K152	LT4K068	-5	1000	70	.790	2.7	14.5	95

1/ The dash number added to the MS military-standard number constitutes the MS part number; for example, MS 14049-1

2/ The decrease in maximum operating temperature from 125°C to 105°C does not downgrade these coils but assures satisfactory operation at 105°C for a minimum of 2000 hours of life rather than a shorter period of operation at 125°C.

APPROVED 15 February 1972 REVISED

User activities: Army-WC,ME,SL Navy-AS,MC,SH Air Force-19
Reviewer activities Army-MI,MU,SL Navy-OS Air Force-11,17,80 DSA-ES
This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P A NAVY-EC Other Cust AF-80 ARMY-EL	International interest	TITLE Coils, radio frequency, molded, fixed, subminiature (iron core) types LT10K148 to LT10K152 incl.	MILITARY STANDARD MS14049
Procurement Specification MIL-C-15305		SUPERSEDES: MS75054	SHEET 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5950

Electrical Characteristics (Final)				
Inspection Group	Allowable variation from initial measurement		Allowable % from specified minimum value in Electrical Characteristics (initial) table	
	Inductance Percent	DC resistance	Self-resonant frequency	Q
Qualification Inspection				
Group II	±2	--	--	- 10
Group III	±5	±(3%+.001ohm)	- 8	- 10
Group IV	±5	±(2%+.001ohm)	- 10	- 15
Quality Conformance Inspection				
Group C				
Subgroup I	±2	--	--	- 10
Subgroup II	±5	±(2%+.001ohm)	- 10	- 15
Subgroup III	±5	±(3%+.001ohm)	- 8	- 10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm
3. These coils are intended to be mounted by the body
4. The polarizing voltage during the moisture-resistance tests is applied with the positive lead connected to the coil terminals tied together, and the negative lead connected to the metal strap.
5. Terminal strength (Pull) test, is not applicable in "Group B" inspection Table VI
6. Solderable/weldable lead wire, AWG #21.
7. Barometric pressure test (test condition C) is applicable
8. Shock, specified pulse, method 213, test condition I, is applicable
9. Referenced document shall be the issue in effect on date of invitation for bid
10. This standard takes precedence over the procurement specification referenced herein

User activities: Army, Navy, Air Force

Reviewer activities: Army, Navy, Air Force

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED REVISED

P A NAVY EC Other Cust A F -80 ARMY EL	International interest	TITLE Coils, radio frequency, molded, fixed, subminiature (iron core) types LT10K148 to LT10K152 incl.	MILITARY STANDARD MS14049
Procurement Specification MIL-C 15305		SUPERSEDING MS75051	SHEET 2

DD FORM 10 APR 64 672

☆ U S GOVERNMENT PRINTING OFFICE 197

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel (either government or contractor) involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided to obtain information for use of this specification which will insure that suitable products can be procured when needed at the lowest cost. Cooperation and the return of this form will be appreciated. Fold on lines, staple in corner and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

DIRECT GOVERNMENT CONTRACT | SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATION FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

4. REMARKS

5. SUBMITTED BY (Printed or typed name and address - Optional)

DATE

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.